

MATERIAL SAFETY DATA SHEET Nashua ASJ

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATIONS AND OF THE COMPANY UNDERTAKING

Product Name Nashua ASJ

Product Description Pressure sensitive adhesive tape

Manufacturer/Supplier Berry Plastics Corporation, Tapes and Coatings Division

Address 25 Forge Parkway

Franklin, MA 02038

Phone Number (800) 248-7659 (Monday – Friday 8:00 am to 5:00 pm)

Chemtrec Number (800) 424-9300

Revision Date:

MSDS Date: June 11, 2010

Safety Data Sheet according to EC directive 2001/59/EC and OSHA's Hazcom Standard (29 CFR 1910.1200)

2. HAZARDS IDENTIFICATION

EU Main Hazards

Not classified as hazardous.

Routes of Entry

Inhalation - Skin contact

Carcinogenic Status

Not considered carcinogenic by NTP, IARC, and OSHA.

Target Organs

Skin - Reproductive

Health Effects - Eyes

Contact may cause irritation due to mechanical abrasion.

Health Effects - Skin

Contact may cause irritation and allergic sensitization. Material can be absorbed through the skin and cause effects similar to those resulting from inhalation.

Health Effects - Ingestion

Not an expected route of entry during normal handling and use.

Health Effects - Inhalation

Prolonged, repeated inhalation of adhesive may cause dizziness, drowsiness and adverse reproductive effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component Name	CAS#/Codes	Concentration <50%	R Phrases	Classification
Polymers	N.A.		None	None
Toluene	108-88-3 203-625-9	0.1 - <1%	R11, R38, R48/20, R63, R65, R67	F, Xn, Repr Cat. 3

4. FIRST AID MEASURES

Eves

Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention if soreness or redness persists.

Revision Date: June 11, 2010 Page 1 of 5

4. FIRST AID MEASURES

Skin

Wash skin thoroughly with soap and water. Obtain medical attention if blistering occurs or redness persists.

Ingestion

Obtain medical attention immediately.

Inhalation

Remove person to fresh air. Seek medical attention if symptoms persist.

Advice to Physicians

Treat symptomatically.

5. FIRE - FIGHTING MEASURES

Extinguishing Media

Water spray, carbon dioxide and dry chemical.

Unusual Fire and Explosion Hazards

May release hazardous vapors during a fire.

Protective Equipment for Fire-Fighting

Wear full protective clothing and self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

No specific measures necessary. Prevent the material from entering drains or watercourses.

7. HANDLING AND STORAGE

Keep away from heat and sources of ignition. Storage area should be: - cool - dry - well ventilated - away from incompatible materials

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Standards

Exposure limits are listed below, if they exist.

Polymers and resins

None established

Toluene

ACGIH: TLV 20 ppm (75mg/m³) 8hTWA.

OSHA:PEL 200 ppm 8h TWA, Ceiling (C) 300 ppm, 500ppm 10-min peak per 8-hr shift

Engineering Control Measures

No specific measures necessary. Good general room ventilation is expected to be adequate to control airborne levels.

Respiratory Protection

Respiratory protection not normally required.

Hand Protection

Not required under normal conditions of use. However, care should be taken to avoid contact with the adhesive.

Eye Protection

Safety glasses

Body Protection

Normal work wear.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State Paper/scrim/foil backing coated with pressure sensitive adhesive

protected by a paper liner

Color Silver/white backing with clear adhesive and white liner

Odor

pH

Not applicable

Specific Gravity

No data available

Boiling Range/Point (°C/F)

Melting Point (°C/F)

Not applicable

Not applicable

Not applicable

Not known

Explosion Limits (%)

Vapor Pressure

Density

No data available

Not applicable

No data.

Not known

Vapor Density (Air = 1)

Not applicable

10. STABILITY AND REACTIVITY

Stability

Stable under normal conditions.

Conditions to Avoid

Heat - High temperatures

Materials to Avoid

Acids - bases - oxidizers

Hazardous Polymerization

Will not occur.

Hazardous Decomposition Products

Oxides of carbon – hydrocarbons

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Toluene: Oral LD50 rat 636 mg/kg

Dermal LD50 rabbit 12124 mg/kg Inhalation LC50 rat 28.1 mg/l 4h

Specific Target Organ Systemic Toxicity (single and repeat)

No relevant studies identified.

Serious Eye damage/Eye Irritation

May cause irritation due to mechanical abrasion.

Skin Corrosion/Irritation

May cause irritation on prolonged, repeated contact.

Respiratory or Skin Sensitization

This product may cause an allergic skin reaction.

Carcinogenicity

Not considered carcinogenic by NTP, IARC, and OSHA.

Germ Cell Mutagenicity

Toluene: Negative Ames Test with and without metabolic activation.

Toxicity to Reproduction

Toluene: In laboratory studies, birth defects, increased fetal lethality and delayed fetal development have been observed in offspring of female animals exposed during pregnancy. Toluene has been demonstrated to be embryofetotoxic and teratogenic in laboratory animals.

Revision Date: June 11, 2010 Page 3 of 5

12. ECOLOGICAL INFORMATION

Mobility

No relevant studies identified.

Persistence/Degradability

No relevant studies identified.

Bio-accumulation

No relevant studies identified.

Ecotoxicity

Toluene: EC50 Fathead minnow 96hr 34mg/l EC50 Daphnia magna 48hr 11.5 mg/l

EC50 Algae (Selenastrum capricornutum) 433 mg/l 96 hr

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with all applicable local and national regulations.

14. TRANSPORT INFORMATION

UN Proper Shipping Name

Not Regulated

Not Regulated

UN Class None.
UN Number None.
UN Packaging Group None.

Classification for AIR Transportation (IATA)

Consult current IATA Regulations prior to shipping by air.

15. REGULATORY INFORMATION

EU Label Information

Classification and labelling have been performed according to EU directives 67/548/EEC and 99/45/EC including amendments(2001/60/EC and 2006/8/EC)

EC Annex I Classification

According to EC Commission Directive 67/548/EEC this product is not classified.

R phrases

None.

S phrases

None.

US REGULATIONS (Federal, State) and INTERNATIONAL CHEMICAL REGISTRATION LAWS

TSCA Listing

This product contains ingredients that are listed on or exempt from listing on the EPA Toxic Substance Control Act Chemical Inventory.

EINECS Listing

All ingredients in this product have not been verified for listing on the European Inventory of Existing Commercial Chemical Substances (EINECS).

DSL (Canadian) Listing

This product contains ingredient(s) that are not listed on the Domestic Substance List (DSL).

California Proposition 65

This product contains the following materials which the State of California has found to cause cancer, birth defects or other reproductive harm: Toluene(108-88-3) - Benzene (71-43-2) trace - Acetaldehyde (75-07-0) trace

Revision Date: June 11, 2010 Page 4 of 5

15. REGULATORY INFORMATION

SARA Title III Sect. 311/312 Categorization

Immediate (acute) Delayed (chronic)

SARA Title III Sect. 313

This product contains the following chemicals that are listed in Section 313 at or above de minimis concentrations: None

16. OTHER INFORMATION

NFPA Ratings

NFPA Code for Flammability - 0

NFPA Code for Health - 1

NFPA Code for Reactivity - 0

NFPA Code for Special Hazards - 0

HMIS Ratings

HMIS Code for Flammability - 0

HMIS Code for Health - 1

HMIS Code for Reactivity - 0

HMIS Code for Personal Protection - See Section 8

Abbreviations

N/A: Denotes no applicable information found or available

CAS#: Chemical Abstracts Service Number

ACGIH: American Conference of Governmental Industrial Hygienists

OSHA: Occupational Safety and Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

STEL: Short Term Exposure Limit

NTP: National Toxicology Program

IARC: International Agency for Research on Cancer

R: Risk

F: Highly Flammable

Xn: Harmful

R11: Highly Flammable

R38: Irritating to skin.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R63: Possible risk of harm to the unborn child.

R65: Harmful: may cause lung damage if swallowed.

R67: Vapours may cause drowsiness and dizziness.

S: Safety

T: Toxic

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

BOD: Biological Oxygen Demand

KoC: Soil Organic Carbon Partition Coefficient

For further Information email: msdstechnical@berryplastics.com

Prepared By: EnviroNet LLC.

The information and recommendations presented in this MSDS are based on sources believed to be accurate. Berry Plastics Corporation, Tapes and Coatings Division assumes no liability for the accuracy or completeness of this information. It is the user's responsibility to determine the suitability of the **material** for their particular purposes. In particular, we make NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, with respect to such information, and we assume no liability resulting from its use. Users should ensure that any use **or disposal** of the material is in accordance with applicable Federal, State, and local laws and regulations.

Revision Date: June 11, 2010 Page 5 of 5