GP1-40BL ADHESIVE

SECTION 1: IDENTIFICATION

PRODUCT NAME: GP1-40BL ADHESIVE / DIV01001

CAS NUMBER: MIXTURE

DESCRIPTION: CHLORINATED PRESSURE SENSITIVE ADHESIVE, HIGH SOLIDS (aerosol)

MANUFACTURER FOR: DIVERSITECH

6650 SUGARLOAF PARKWAY

SUITE 100

DULUTH, GA 30097 United States of America

Information Phone Number: 1-678-542-3600

Emergency Phone Number: 800-424-9300 (Chemtrec)

SDS Date of Preparation: 4/15/2015

Product Use: Adhesive – consumer product

Restriction on Use: None identified

SECTION 2: HAZARDS IDENTIFICATION

GHS Classification (Hazcom 2012):

For Aerosols:

Flammable Aerosol Category 1

Gas Under Pressure: Compressed Gas

Skin Irritation Category 2 Eye Irritation Category 2 Carcinogen Category 1

Specific Target Organ Toxicity – Single Exposure Category 3 (narcotic effects)
Specific Target Organ Toxicity – Repeat Exposure Category 2 (CNS, blood, liver)

Label Elements:



Contains Methylene Chloride

DANGER!

Extremely Flammable Aerosol.

Contains gas under pressure; may explode if heated.

Causes skin irritation.

Causes serious eye irritation.

May cause cancer.

May cause respiratory irritation.

May cause drowsiness or dizziness.

May cause damage to the central nervous system through prolonged or repeated exposure by inhalation.

May cause damage to blood and liver through prolonged or repeated exposure by ingestion.

Obtain special instructions before use.

GP1-40BL ADHESIVE

Do not handle until all safety precautions have been read and understood.

Keep out of reach of children.

Keep away from heat, sparks, open flames, and hot surfaces – No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe mist, vapors, or spray.

Use only outdoors or in a well-ventilated area.

Wash thoroughly after handling.

Wear protective gloves, protective clothing, and eye and face protection.

If exposed or concerned: Get medical advice or attention.

Get medical advice or attention if you feel unwell.

IF ON SKIN: Wash with plenty of water.

If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice or attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor if you feel unwell.

Store in a well-ventilated place. Keep container tightly closed.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Store locked up.

Dispose of contents and container in accordance with local, state, and national regulations.

For Cylinders:

Flammable Gas Category 1

Gas Under Pressure: Compressed Gas

Skin Irritation Category 2 Eye Irritation Category 2

Carcinogen Category 1

Specific Target Organ Toxicity – Single Exposure Category 3 (narcotic effects) Specific Target Organ Toxicity – Repeat Exposure Category 2 (CNS, blood, liver)

Label Elements:



DANGER!

Extremely flammable gas

Contains gas under pressure; may explode if heated.

Causes skin irritation.

Causes serious eye irritation.

May cause cancer.

May cause respiratory irritation.

GP1-40BL ADHESIVE

May cause drowsiness or dizziness.

May cause damage to the central nervous system through prolonged or repeated exposure by inhalation.

May cause damage to blood and liver through prolonged or repeated exposure by ingestion.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep out of reach of children.

Keep away from heat, sparks, open flames, and hot surfaces – No smoking.

Do not breathe mist, vapors, or spray.

Use only outdoors or in a well-ventilated area.

Wash thoroughly after handling.

Wear protective gloves, protective clothing, and eye and face protection.

If exposed or concerned: Get medical advice or attention.

Get medical advice or attention if you feel unwell.

IF ON SKIN: Wash with plenty of water.

If skin irritation occurs: Get medical advice or attention.

Take off contaminated clothing and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice or attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor if you feel unwell.

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

Eliminate all ignition sources if safe to do so.

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store locked up.

Dispose of contents and container in accordance with local, state, and national regulations.

Other Hazards: None

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	%	GHS Classification
Methylene Chloride	75-09-2	45-55	Skin Irritation Category 2
			Eye Irritation Category 2
			Carcinogen Category 1
			Specific Target Organ Toxicity Single Exposure Category 3 (narcotic)
			Specific Target Organ Toxicity Repeat Exposure Category 2 (CNS, blood, liver)
Propane	74-98-6	10-20	Flammable Gas Category 1
- 1			Compressed Gas
n-Butane	106-97-8	10-20	Flammable Gas Category 1
			Compressed Gas

SECTION 4: FIRST AID MEASURES

GP1-40BL ADHESIVE

Eye: Rinse thoroughly with water, holding the eye lids open to be sure the material is washed out. Remove contacts if it is safe and easy to do so. Continue rinsing. Get medical attention if irritation persists.

Skin: Remove contaminated clothing. Wash exposed area thoroughly with soap and water. Get medical attention if irritation or symptoms of exposure develop. Launder clothing before re-use.

Inhalation: Remove victim to fresh air. Give artificial respiration if needed. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

Ingestion: Ingestion is an unlikely route of exposure for aerosol products. If ingestion occurs rinse mouth with a small amount of water. Immediately call local poison control center or go to an emergency department. Never give anything by mouth to an unconscious or drowsy person.

Most Important symptoms and effects, both acute and delayed: Symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting), irritation (throat, nose, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), irregular heartbeat, and death. Methylene chloride is converted to carbon monoxide in the body which may worsen heart disease. Methylene chloride is a suspected carcinogen.

Indication of any immediate medical attention and special treatment needed: Medical attention may be required for skin and eye exposure. Get immediate medical attention for ingestion or inhalation.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable and Unsuitable Extinguishing Media: Use dry chemical, carbon dioxide, or foam. Use water to cool fire-exposed containers and to protect personnel. Do not direct a solid stream of water or foam into hot, burning pools this may results in frothing and increase fire intensity.

Special Hazards Arising from the Chemical:

Unusual Fire Hazards: Contents under pressure. Keep away from heat and open flames. Container may rupture or explode in the heat of a fire. Prolonged exposure to temperatures above 120°F may cause cans to burst. Empty containers may retain product residue including Flammable or Explosive vapors. DO NOT cut, drill, grind, or weld near full, partially full, or empty product containers.

Hazardous Decomposition Products: Carbon dioxide, carbon monoxide, chlorine, hydrochloric acid, and phosgene.

Special Equipment and Precautions for Fire-Fighters: Wear NIOSH approved, positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water. Protect against bursting cans.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: Evacuate the

GP1-40BL ADHESIVE

area promptly and keep upwind of the spilled material. Isolate the spill area to prevent people from entering. Wear appropriate personal protective equipment and clothing during clean-up. Eliminate all sources of ignition. Ventilate area.

Methods and Material for Containment and Cleaning Up: Stop discharge if safe to do so. Stop material from contaminating soil or from entering seers or water streams. Cover spills with inert absorbent and place in closed chemical waste containers.

SECTION 7: HANDLING AND STORAGE

FOR COMMERCIAL USE ONLY – NOT PACKAGED OR LABELED FOR HOME USE!

Precautions for Safe Handling: Keep product away from heat, sparks or open flame. Avoid contact with eyes and skin. Avoid breathing vapors, mists, or aerosols. Use with adequate ventilation. Wash exposed skin thoroughly with soap and water after use. Do not handle or store near an open flame, heat, or other sources of ignition. Contents under pressure. Do not puncture or incinerate container. Do not reuse the empty container.

Please read and follow the directions on the product label; they are your best guide to using this product in the most effective way, and give the necessary safety precautions to protect your health.

Refer to OSHA 1910.1052 for requirements for handling and use of methylene chloride.

Empty Container Precautions: Attention! Follow label warnings even after container is emptied since empty containers may retain product residues. Do not reuse empty container without professional cleaning for food, clothing, or products for human or animal consumption, or where skin contact can occur.

Conditions for Safe Storage, Including any Incompatibilities: Store in a cool, well-ventilated area at temperatures below 120°F. Do not store in direct sunlight.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	Exposure Limits
Methylene Chloride	50 ppm ACGIH TLV-TWA 25 ppm OSHA PEL-TWA, 125 ppm OSHA PEL-STEL
Propane	1000 ppm ACGIH TLV-TWA (as aliphatic hydrocarbon gas)
n-Butane	1000 ppm ACGIH TLV-TWA (as aliphatic hydrocarbon gas)

Appropriate Engineering Controls: General ventilation should be adequate for normal use. For operations where the occupational exposure limit may be exceeded, mechanical ventilation such as local exhaust may be needed to maintain exposure levels below applicable limits.

Individual Protection Measures:

See OSHA 1910.1052 for requirements for handling and use of methylene chloride.

Respiratory Protection: For operations where the occupational exposure limit may be exceeded, a NIOSH approved supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration, select in accordance with good industrial hygiene practice.

GP1-40BL ADHESIVE

For firefighting, use self-contained breathing apparatus.

Skin Protection: Impervious gloves are recommended for operations which may result in prolonged / repeated skin contact.

Eye Protection: Wear chemical safety glasses with side shields or goggles to prevent eye contact.

Other Protective Equipment: Protective clothing if needed to avoid prolonged / repeated skin contact. Suitable washing and eye flushing facilities should be available in the work area. Contaminated clothing should be removed and laundered before re-use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Natural liquid	Vapor Density: Not determined
Odor: Sweet pungent	Specific Gravity: 1.18 +/- 0.02
Odor Threshold: Not established	Water Solubility: Soluble
pH: Not determined	Octanol/Water Partition Coefficient: Not available
Melting Point/Freezing Point: Not available	Autoignition Temperature: Not available
Boiling Point: Not available	Decomposition Temperature: Not available
Flash Point: Less than -104.4°C (-156°F) (propellant)	Viscosity: Not available
Not applicable (concentrate) Evaporation Rate: Not available	Explosion Properties: None
Flammable Limits: LEL: 1.8% UEL: 9.5%	Oxidizing Properties: Not oxidizing
Vapor Pressure: Not available	Aerosol Fire Protection Level: Level 1 Aerosol (NFPA 30B)
Aerosol Flame Extension: Not available	Flashback: None
VOC: 47.4% by weight (554.6 g/L)	

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions of use

Chemical Stability: Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions: None known

Conditions to Avoid: Keep away from heat, sparks, flames and other sources of ignition.

Dropping containers may cause bursting.

Incompatible Materials: Avoid strong oxidizers, reducers, acids, and alkalis.

Hazardous Decomposition Products: Combustion will produce carbon dioxide, carbon monoxide, chlorine, hydrochloric acid, phosgene.

SECTION 11: TOXICOLOGICAL INFORMATION

GP1-40BL ADHESIVE

Potential Health Effects:

Eye: Liquid or vapours may irritate the eyes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Eye contact may lead to permanent damage if not treated promptly.

Skin: This product may cause irritation to the skin. Prolonged or repeated contact with this product may dry and/or defat the skin. This product may be harmful if it is absorbed through the skin.

Inhalation: This product may cause dizziness, nausea, upper respiratory irritation, drowsiness, mental depression or narcosis, difficulty in breathing, irregular heartbeats. Overexposure may cause cardiac sensitization and increased risk of cardiac arrest, blurred vision, adverse effects on the lungs, liver, kidney, nervous system, and other internal organs, coma or death. Carboxyhemoglobin levels can be elevated in persons exposed to methylene chloride causing stress on the cardiovascular system.

Ingestion: This product is harmful if swallowed. Ingestion can cause gastrointestinal irritation, nausea, and diarrhea.

Chronic Hazards: Prolonged overexposure may cause central nervous system effects, liver and blood damage. Methylene chloride has been shown to cause reproductive toxicity and/or birth defects only at doses that produce significant toxicity in the parent animal.

Carcinogen Status: Methylene chloride has been shown to cause liver and lung cancer in laboratory mice. Methylene chloride has not been shown to be carcinogenic in humans. It is listed as carcinogenic by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), and the Occupational Safety and Health Administration (OSHA). None of the components of this product are listed as carcinogens by IARC or the EU Directive.

Numerical Measures of Toxicity:

Methylene Chloride: Oral Rat LD50 – 1600 mg/kg, Inhalation rat LC50 – 52 g/m3

Propane: Inhalation rat LC50 – 658 mg/L/4 hr Butane: Inhalation rat LC50 – 658 mg/L/4 hr

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: Methylene Chloride: LC50/96-hour Fathead Minnow - >190 mg/l,

LC50/96-hour Bluegill - 220 mg/l

Persistence and Degradability: No data available

Bioaccumulative Potential: No data available

Mobility in Soil: No data available

Other Adverse Effects: None known

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose in accordance with all local, regional and national regulations. Do not puncture or

GP1-40BL ADHESIVE

incinerate containers. When contents are depleted, continue to depress button until all gas is expelled.

SECTION 14: TRANSPORT INFORMATION

Aerosols:

DOT Proper Shipping Name: Limited Quantity

DOT Technical Name: None DOT Hazard Class: 2.1 UN Number: UN1950

DOT Labels Required (49CFR172.101): Limited Quantity

Hazardous Substance (49CFR172.101): Methylene Chloride (RQ 1,000 lbs)

Reportable Quantity: 1,818 lbs.

IMDG Shipping Description: UN1950, Aerosols, 2.1, FP -104.4°C, Limited Quantity

ID Number: UN1950 Hazard Class: 2.1 Packing Group: None Labels Required: None Marking Required: LTD QTY

Placards Required: Limited Quantity Mark

Cylinders:

DOT Proper Shipping Name: Chemicals Under Pressure, Flammable, N.O.S.

DOT Technical Name: Methylene Chloride

DOT Hazard Class: 2.1 **UN Number:** UN3501

DOT Labels Required (49CFR172.101): Flammable 2.1

Hazardous Substance (49CFR172.101): Methylene Chloride (RQ 1.000 lbs)

Reportable Quantity: 1,818 lbs.

IMDG Shipping Description: UN3501, Chemicals Under Pressure, Flammable, N.O.S.

Methylene Chloride, (FP -104.4°C), 2.1

ID Number: UN3501 Hazard Class: 2.1 Packing Group: None

Labels Required: Flammable 2.1

Marking Required: None

Placards Required: Flammable 2.1

This product cannot be shipped by air unless it is repackaged by an authorized packing

company.

SECTION 15: REGULATORY INFORMATION

CERCLA 103 Reportable Quantity: Releases of this product in excess of the reportable quantity of 1,818 lbs (based on methylene chloride of 1000 lbs) are reportable to the National Response Center. Many states have more stringent reporting requirements. Report spills and other releases as required under federal, state and local regulations.

SARA TITLE III:

GP1-40BL ADHESIVE

Hazard Category for Section 311/312: Acute Health, Chronic Health, Fire Hazard, Sudden Release of Pressure

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA

Title III Section 313 Reporting requirements:

Methylene Chloride

75-09-2

45-55%

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.

STATE REGULATIONS:

California Proposition 65: This product contains the following substances known to the State of California to cause cancer: Methylene Chloride 45-55%.

SECTION 16: OTHER INFORMATION

Revision Summary: Updated Section 2, 14, and 15.

SDS Date of Preparation/Revision: September 16, 2014

While the information set forth herein is believed to be accurate as of the date hereof, the Company makes no warranty or guarantee, express or implied, and disclaims all liability arising out of the use of this information.