

SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION

Manufacturer's name and address:



K-FLEX USA
100 Nomaco Dr
Youngsville, NC 27596
USA

Supplier's name and address:

Refer to Manufacturer

Telephone No. : (800) 765-6475
Website Address : www.kflexusa.com
Product Identifier : FlexTherm®, FlexTherm® Seam Seal, FlexTherm® Sheet S2S,
FlexTherm® White; Elastomeric Tape
Chemical Name : NBR/PVC Elastomeric Foam
Recommended Use : This product is classified as an "article" according to Title 29 of
the Code of Federal Regulations, OSHA Part 1910.1200C.

SECTION 2 – HAZARD(S) IDENTIFICATION

Hazardous Ingredient : None

SECTION 3 – COMPOSITION/INFORMATION OF INGREDIENTS

Description : Elastomeric closed-cell foam comprised of nitrile butadiene
rubber/polyvinyl chloride (NBR/PVC). Available in rolls and
sheets of various dimensions.

SECTION 4 – FIRST-AID MEASURES

Inhalation : Unlikely route of exposure. No measures established.
Skin Contact : If rash or irritation develops, wash with soap and water. If rash
or irritation persists, consult a physician.
Eye Contact : Small particles may cause irritation. Flush with water. If
irritation persists, consult a physician.
Ingestion : Unlikely route of exposure. No adverse effects anticipated.

SECTION 5 – FIRE-FIGHTING MEASURES

Extinguishing Media : Water, CO₂, Dry Chemical, Foam
Special Firefighting Procedures : Recommend NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing be worn.
Decomposition Products : Upon combustion, HCl, HCN, and other hazardous gases may be evolved.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions : Recommend light to medium duty cloth or leather gloves and approved safety glasses.
Emergency Procedures : None.

SECTION 7 – HANDLING AND STORAGE

Hints for Safe Handling : None.
Hints for Fire and Explosion Protection : None.
Hints for Separation of Incompatible Materials : None.
Storage Recommendations : Avoid storage in confined areas where temperatures may exceed 51°C (125°F).

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Medical Conditions Aggravated by Exposure : Not established.
Codes Used : N/A
General Health Measures : N/A
Engineering Controls : Local exhaust ventilation is recommended for control of airborne dust, fumes, and vapors in confined areas.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Sheets, rolls, and tubes; some with self-adhesive
Color : Black, white, or gray.
Odor : Negligible to no odor.
Melting Point : N/A
Boiling Point : N/A
Lower Explosion Limit : N/A
Upper Explosion Limit : N/A
Vapor Pressure @ 20°C : 0.1
Vapor Density (Air = 1) : N/A
Solubility : Insoluble
Specific Gravity (H₂O = 1) : N/A

Flash Point : N/A

SECTION 10 – STABILITY AND REACTIVITY

Stability : Stable.
Incompatibility : N/A
Decomposition Products : Upon combustion, HCl, HCN, and other hazardous gases may be evolved.

SECTION 11 – TOXICOLOGICAL INFORMATION

Effects on short- and long-term Exposure : When used and handled according to specification, the product does not have any harmful effect to the best of our knowledge.

SECTION 12 – ECOLOGICAL INFORMATION

Classified as non-hazardous to waters.

SECTION 13 – DISPOSAL CONSIDERATIONS

Disposal : Not a RCRA hazardous waste. Dispose of in accordance with local, state, and federal regulations.

SECTION 14 – TRANSPORT INFORMATION

No hazardous materials.

SECTION 15 – REGULATORY INFORMATION

N/A

SECTION 16 – OTHER INFORMATION

Revised January, 2015. The information and recommendations contained herein are based upon data that is accurate and reliable, to the best of K-FLEX USA, LLC knowledge and belief. With respect to information and recommendations, K-FLEX USA, LLC makes no representations or warranties of any kind or nature, expressed or implied.