

SAFETY DATA SHEET

1. Identification

11 Identification	
Product identifier	Hercules Staput
Other means of identification	
Product code	1618E
Synonyms	Part Numbers: 25101, 25103, 25105, 25110, 25120, 25122
Recommended use	Plumbing Mastic
Recommended restrictions	Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.
Manufacturer/Importer/Supplier/	Distributor information
Company Name	HCC Holdings, Inc. an Oatey Affiliate
Address	4700 West 160th Street
	Cleveland, OH 44135
Talanhana	21/ 2/7 7100
Telephone E-mail	216-267-7100
Transport Emergency	info@oatey.com Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)
Emergency First Aid	1-877-740-5015
Contact person	MSDS Coordinator
-	
2. Hazard(s) identification	
Physical hazards	Not classified.
Health hazards	Not classified.
OSHA defined hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	The mixture does not meet the criteria for classification.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	Wash hands after handling.
Storage	Store away from incompatible materials.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Calcium carbonate	1317-65-3	60-100
Kaolin	1332-58-7	5-10
Mineral Wool	65997-17-3	1-5
Petroleum-based Lubricating Oil	64741-88-4	1-5

Crystalline silica (Quartz)		14808-60-7	<1
Other components below repo	ortable levels		16.5
*Designates that a specific chemic	cal identity and/or percentage of composition	has been withheld as a trade see	cret.
4. First-aid measures			
Inhalation	Move to fresh air. Call a physician if sympt	toms develop or persist.	
Skin contact	Wash off with soap and water. Get medica	al attention if irritation develops ar	nd persists.
Eye contact	Rinse with water. Get medical attention if i	rritation develops and persists.	
Ingestion	Rinse mouth. Get medical attention if symp	ptoms occur.	
Most important symptoms/effects, acute and delayed	Coughing.		
Indication of immediate medical attention and special treatment needed	Treat symptomatically.		
General information	Ensure that medical personnel are aware or protect themselves.	of the material(s) involved, and ta	ke precautions
5. Fire-fighting measures			
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. C	arbon dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as	s this will spread the fire.	
Specific hazards arising from the chemical	During fire, gases hazardous to health may	y be formed.	
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and fu	Il protective clothing must be wor	n in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can o	do so without risk.	
Specific methods	Use standard firefighting procedures and c	consider the hazards of other invo	lved materials.
	No unusual fire or explosion hazards noted	1	

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure.

Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Calcium carbonate (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Kaolin (CAS 1332-58-7)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

to

US. OSHA Table Z-3 (29 CFR 1910.1000)

TWA Type TWA	0.3 mg/m3 0.1 mg/m3 Value 0.025 mg/m3 2 mg/m3 5 mg/m3 Value Value 5 mg/m3 10 mg/m3 0.05 mg/m3 10 mg/m3 3 fibers/cm3 3 fibers/cm3 5 mg/m3 5 mg/m3	Total dust. Respirable. Form Respirable fraction. Respirable fraction. Inhalable fraction. Inhalable fraction. Sespirable dust. Total Respirable dust. Respirable. Total Dust. Fiber. Fiber. Fiber, total
TWA TWA TWA TWA Sal Hazards Type TWA TWA TWA TWA	Value 0.025 mg/m3 2 mg/m3 5 mg/m3 Value 5 mg/m3 10 mg/m3 0.05 mg/m3 5 mg/m3 3 fibers/cm3 3 fibers/cm3 5 mg/m3	Form Respirable fraction. Inhalable fraction. Inhalable fraction. Form Respirable. Total Respirable dust. Respirable. Total Dust. Fiber.
TWA TWA TWA TWA Sal Hazards Type TWA TWA TWA TWA	0.025 mg/m3 2 mg/m3 5 mg/m3 Value 5 mg/m3 10 mg/m3 0.05 mg/m3 10 mg/m3 3 fibers/cm3 3 fibers/cm3 5 mg/m3	Respirable fraction. Respirable fraction. Inhalable fraction. Form Respirable. Total Respirable dust. Respirable. Total Dust. Fiber.
TWA TWA TWA TWA Sal Hazards Type TWA TWA TWA TWA	0.025 mg/m3 2 mg/m3 5 mg/m3 Value 5 mg/m3 10 mg/m3 0.05 mg/m3 10 mg/m3 3 fibers/cm3 3 fibers/cm3 5 mg/m3	Respirable fraction. Respirable fraction. Inhalable fraction. Form Respirable. Total Respirable dust. Respirable. Total Dust. Fiber.
TWA TWA cal Hazards Type TWA TWA TWA TWA	2 mg/m3 5 mg/m3 Value 5 mg/m3 10 mg/m3 0.05 mg/m3 10 mg/m3 3 fibers/cm3 3 fibers/cm3 5 mg/m3	Respirable fraction. Inhalable fraction. Form Respirable. Total Respirable dust. Respirable. Total Dust. Fiber.
TWA cal Hazards Type TWA TWA TWA TWA	5 mg/m3 5 mg/m3 5 mg/m3 10 mg/m3 0.05 mg/m3 10 mg/m3 3 fibers/cm3 3 fibers/cm3 5 mg/m3	Inhalable fraction. Form Respirable. Total Respirable dust. Respirable. Total Dust. Fiber.
TWA cal Hazards Type TWA TWA TWA TWA	5 mg/m3 5 mg/m3 5 mg/m3 10 mg/m3 0.05 mg/m3 10 mg/m3 3 fibers/cm3 3 fibers/cm3 5 mg/m3	Inhalable fraction. Form Respirable. Total Respirable dust. Respirable. Total Dust. Fiber.
TWA TWA TWA TWA	5 mg/m3 10 mg/m3 0.05 mg/m3 5 mg/m3 10 mg/m3 3 fibers/cm3 3 fibers/cm3 5 mg/m3	Respirable. Total Respirable dust. Respirable. Total Dust. Fiber.
TWA TWA TWA TWA	5 mg/m3 10 mg/m3 0.05 mg/m3 5 mg/m3 10 mg/m3 3 fibers/cm3 3 fibers/cm3 5 mg/m3	Respirable. Total Respirable dust. Respirable. Total Dust. Fiber.
TWA TWA TWA	10 mg/m3 0.05 mg/m3 5 mg/m3 10 mg/m3 3 fibers/cm3 3 fibers/cm3 5 mg/m3	Total Respirable dust. Respirable. Total Dust. Fiber.
TWA TWA	10 mg/m3 0.05 mg/m3 5 mg/m3 10 mg/m3 3 fibers/cm3 3 fibers/cm3 5 mg/m3	Total Respirable dust. Respirable. Total Dust. Fiber.
TWA TWA	0.05 mg/m3 5 mg/m3 10 mg/m3 3 fibers/cm3 3 fibers/cm3 5 mg/m3	Respirable dust. Respirable. Total Dust. Fiber.
TWA TWA	5 mg/m3 10 mg/m3 3 fibers/cm3 3 fibers/cm3 5 mg/m3	Respirable. Total Dust. Fiber.
TWA	10 mg/m3 3 fibers/cm3 3 fibers/cm3 5 mg/m3	Total Dust. Fiber.
TWA	10 mg/m3 3 fibers/cm3 3 fibers/cm3 5 mg/m3	Total Dust. Fiber.
	3 fibers/cm3 3 fibers/cm3 5 mg/m3	Fiber.
	5 mg/m3	
	0	Fiber, total
	E	
	5 mg/m3	fibers, total dust
Ceiling	1800 mg/m3	
STEL	10 mg/m3	Mist.
TWA	5 mg/m3	Mist.
logical exposure limits noted fo	r the ingredient(s).	
Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.		
Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
personal protective equipm	ent	
afety glasses with side shields	o (or goggles).	
appropriate chemical resistant	gloves.	
suitable protective clothing.		
	articulate concentrations excee	eding the Occupational
	clothing, when necessary.	
s observe good personal hygier	ne measures, such as washing	
	be monitored and controlled. general ventilation (typically 10 be matched to conditions. If ap r engineering controls to main ure limits have not been establi personal protective equipm tafety glasses with side shields appropriate chemical resistant of suitable protective clothing. Darticulate filter respirator for p ure Limit. appropriate thermal protective of s observe good personal hygien fore eating, drinking, and/or sn nent to remove contaminants.	be monitored and controlled. general ventilation (typically 10 air changes per hour) should be be matched to conditions. If applicable, use process enclosur r engineering controls to maintain airborne levels below recor- irre limits have not been established, maintain airborne levels personal protective equipment tafety glasses with side shields (or goggles). appropriate chemical resistant gloves. suitable protective clothing. barticulate filter respirator for particulate concentrations exceed ure Limit. appropriate thermal protective clothing, when necessary. to observe good personal hygiene measures, such as washing fore eating, drinking, and/or smoking. Routinely wash work clo

Appearance		
Physical state	Solid.	
Form	Putty.	
Hercules Staput		SDS US

Hercules Staput

Color	Off-white.
Odor	Slight.
Odor threshold	Not available.
рН	Not applicable
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not determined
Flash point	> 212.0 °F (> 100.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	1.8
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	> 5000000 cP
Other information	
VOC (Weight %)	6 g/l

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Acids. Fluorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.		
Skin contact	No adverse effects due to skin contact are expected.	
Eye contact	Direct contact with eyes may cause temporary irritation.	
Ingestion	Expected to be a low ingestion hazard.	
Symptoms related to the physical, chemical and toxicological characteristics	Coughing.	
Information on toxicological effects		
Acute toxicity Not available.		
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	

Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.		
Respiratory or skin sensitization	1		
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected t	o cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) Risk of cancer cannot be excluded with prolonged exposure.		
	Evaluation of Carcinogenicity		
Crystalline silica (Quartz) Petroleum-based Lubrica NTP Report on Carcinogens	ting Oil (CAS 64741-88-4)	 Carcinogenic to humans. Not classifiable as to carcinogenicity to humans. 	
Crystalline silica (Quartz) OSHA Specifically Regulate Not listed.	(CAS 14808-60-7) d Substances (29 CFR 1910.1	Known To Be Human Carcinogen. 001-1050)	
Reproductive toxicity	This product is not expected t	o cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not an aspiration hazard.		
Chronic effects	Prolonged inhalation may be l	harmful. Prolonged exposure may cause chronic effects.	
Further information	This product has no known ac	lverse effect on human health.	
12. Ecological information	I		
Ecotoxicity		is environmentally hazardous. However, this does not exclude the nt spills can have a harmful or damaging effect on the environment.	
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential	No data available.		
Mobility in soil	No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		
13. Disposal consideration	าร		
Disposal instructions	Collect and reclaim or dispose	e in sealed containers at licensed waste disposal site.	
Local disposal regulations	Dispose in accordance with a	Il applicable regulations.	
Hazardous waste code	The waste code should be as disposal company.	signed in discussion between the user, the producer and the waste	
Waste from residues / unused products		local regulations. Empty containers or liners may retain some al and its container must be disposed of in a safe manner (see:	
Contaminated packaging		aken to an approved waste handling site for recycling or disposal. / retain product residue, follow label warnings even after container is	
14. Transport information			
DOT			

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

10.100	gulatory intormation	
US fede	eral regulations	This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. One or more components are not listed on TSCA.
TS	CA Section 12(b) Export N	lotification (40 CFR 707, Subpt. D)
OS	Not regulated. HA Specifically Regulated Not listed.	I Substances (29 CFR 1910.1001-1050)
CE	RCLA Hazardous Substan Not listed.	ice List (40 CFR 302.4)
Superfu	und Amendments and Rea	authorization Act of 1986 (SARA)
-	zard categories	Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No
SA	RA 302 Extremely hazard	ous substance
	Not listed.	
	RA 311/312 Hazardous emical	No
SA	RA 313 (TRI reporting) Not regulated.	
Other fe	ederal regulations	
Cle	an Air Act (CAA) Section	112 Hazardous Air Pollutants (HAPs) List
Cle	Not regulated. an Air Act (CAA) Section	112(r) Accidental Release Prevention (40 CFR 68.130)
	Not regulated.	
	ie Drinking Water Act DWA)	Not regulated.
US stat	e regulations	
US	. Massachusetts RTK - Su	bstance List
	Calcium carbonate (CAS 1 Crystalline silica (Quartz) (Kaolin (CAS 1332-58-7) Petroleum-based Lubricati	(CAS 14808-60-7)
US.	•	Community Right-to-Know Act
	Calcium carbonate (CAS 1 Crystalline silica (Quartz) (Kaolin (CAS 1332-58-7) Mineral Wool (CAS 65997	(CAS 14808-60-7) -17-3)
03	Calcium carbonate (CAS 1	d Community Right-to-Know Law
US	Crystalline silica (Quartz) (Kaolin (CAS 1332-58-7) . Rhode Island RTK	
	Not regulated.	
US	. California Proposition 65	s contains a chemical known to the State of California to cause cancer.
	•	on 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Crystalline silica (Quartz) (CAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	22-April-2015
Revision date	-
Version #	01
HMIS® ratings	Health: 0 Flammability: 0 Physical hazard: 0
NFPA ratings	

Disclaimer

HCC Holdings Inc. an Oatey Affiliate cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.