



MATERIAL SAFETY DATA SHEET

24-HOUR EMERGENCY ASSISTANCE
CHEMTREC: 800-424-9300

GENERAL MSDS ASSISTANCE
Nu-Calgon: 800-554-5499

For hazard identification, acute and chronic health effects refer to the discussion in Section 3

SECTION 1	NAME
PRODUCT	AC Re-New + Propane 4057-50
CHEMICAL NAME	Lubricant Additive
Use/Applications	Performance Improvement

SECTION 2	PRODUCT/INGREDIENT
-----------	--------------------

THIS PRODUCT IS CONSIDERED AS NON-HAZARDOUS (SEE SECTION 14).

COMPONENT	CHEMICAL NAME	%BY WEIGHT
Refrigerant (R-290)	Propane	25 – 45%
Additive package*	Lubricant additives	55 – 75%

* Composition/specific chemical identities are withheld as a trade secret under the provisions of OSHA hazard communication standard 29 CFR 1910.1200

SECTION 3	HAZARD IDENTIFICATION
-----------	-----------------------

EMERGENCY OVERVIEW

Appearance: A viscous oily appearance with clear yellow to golden colored liquid

Hazardous Material Information System (United States)	Health	1	National Fire Protection
	Fire	2	Association NFPA
	Reactivity	0	(United States)
	Personal protection		

POTENTIAL HEALTH EFFECTS

Primary Route of Exposure: Skin

EFFECTS OF OVEREXPOSURE

EYES: Expected to cause no more than minor eye irritation. Application of a similar product into the eyes of rabbits produced very slight membrane irritation without corneal injury. Avoid eye contact as good industrial practice.

SKIN: Not a primary skin irritant but may cause skin irritation on repeated or prolonged contact. Application of a similar product onto the skin of rabbits produced slight erythmia and edema.

INHALATION: Avoid breathing vapor or mist. Under normal use conditions, this product is not an inhalation hazard. Prolonged exposure to vapors may cause dizziness and headaches.

INGESTION: May cause nausea. Not expected to be acutely toxic by ingestion.

There is no evidence that this product aggravates an existing medical condition.

OTHER REMARKS: None.

SECTION 4 FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes while holding the eyelids open. If irritation persists, see a physician.

SKIN: Remove contaminated clothing. Wash skin thoroughly with soap and water. Launder contaminated clothing. See a doctor if irritation persists.

INGESTION: If swallowed, call a physician immediately. ONLY induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person. If medical advice cannot be obtained, take the person, product container and MSDS to the nearest medical emergency center.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration and seek medical attention immediately. Remove material from eyes, skin and clothing.

SECTION 5 FIRE-FIGHTING MEASURES

Flash Point (degrees C), Cleveland Open Cup for oil additive product.
>200C

Caution: gas is flammable

Flash Point of Propane
-104C

Flash Point of Mixture has not been determined.

Flammable Limits % (Lower-Upper):
Lower: Not determined
Upper: Not determined.

Recommended Fire Extinguishing Agents and Special Procedures:

Use water spray, dry chemical, foam, or carbon dioxide to extinguish flames. Use water spray to cool fire-exposed containers. Water or foam may cause frothing.

Unusual or Explosive Hazards: None.

Special Protective Equipment for Firefighters:

Wear full protective clothing and positive pressure breathing apparatus.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Procedures in Case of Accidental Release, Breakage or Leakage:

Ventilate area. Avoid breathing vapor. Wear appropriate personal protective equipment, including appropriate respiratory protection. Contain spill if possible. Wipe up or absorb on suitable material and shovel up. Prevent entry into sewers and waterways. Avoid contact with skin, eyes or clothing.

SECTION 7 HANDLING AND STORAGE

Precautions to be Taken in:

Handling: Minimum feasible handling temperatures should be maintained.

Storage: Periods of exposure to high temperatures should be minimized. Water contamination should be avoided.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective Equipment (Type)

Eye/Face Protection:

Safety glasses, chemical type goggles, or face shield recommended to prevent eye contact.

Skin Protection:

Protective clothing such as coveralls or lab coats should be worn. Launder or dry-clean when soiled. Gloves and boots resistant to chemicals and petroleum distillates required. Exposed workers should wash exposed skin several times daily with soap and water.

Remove and dry-clean or launder clothing soaked or soiled with this material before reuse. Dry cleaning of contaminated clothing may be more effective than normal laundering. Inform individuals responsible for cleaning of potential hazards associated with handling contaminated clothing.

Respiratory Protection:

Airborne concentrations should be kept to lowest levels possible. If vapor, dust or mist is generated and the occupational exposure limit of the product, or any component of the product, is exceeded, use appropriate NIOSH or MSHA approved air purifying or air-supplied respirator after determining the airborne concentration of the contaminant.

Air supplied respirators should always be worn when airborne concentration of the contaminant or oxygen content is unknown.

Ventilation:

Local exhaust ventilation recommended if generating vapor, dust, or mist. If exhaust ventilation is not available or inadequate, use MSHA or NIOSH approved respirator as appropriate.

Exposure Limit for the Total Product: None established for product

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Ordinary oily odor, clear liquid (lubricant additive)
Boiling point (deg C):	> 300C(>572F) at atmospheric pressure (lubricant additive) <-43F(42C) (gas only)
Melting/Freezing Point (deg C):	Not determined
Specific Gravity (water=1):	1.05 (lubricant additive) 1.6 (liquefied gas)
pH:	Not applicable
Vapor Pressure:	Not determined
Vapor Density (Air=1):	Not determined
Solubility in Water (%):	Negligible
Other:	None

SECTION 10 STABILITY AND REACTIVITY

Stability:	Stable (thermal, light).
Incompatibility:	May react with strong oxidizing materials.
Hazardous Decomposition Products:	Normal combustion forms carbon dioxide and water vapor. Incomplete combustion can form carbon monoxide.
Hazardous Polymerization:	Will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION (ANIMAL TOXICITY DATA), (lubricant only)

Oral:	LD50 believed to be > 5 g/kg (rat) practically non-toxic
Inhalation:	Not determined
Dermal:	LD50 believed to be > 10 g/kg (rabbit) practically non-toxic

IRRITATION INDEX, ESTIMATION OF IRRITATION (SPECIES)

Skin: (Draize) believed to be between 3-5 (rabbit) moderately irritating (maximum 8)
Eyes: (Draize) believed to be < 15 (rabbit) no appreciable effect (maximum 110)
Sensitization: Not determined
Other: This product, or a component of this product, has been shown to damage red blood cells or blood forming organs, and has caused anemia in laboratory animals.

SECTION 12 DISPOSAL CONSIDERATIONS

Waste Disposal Methods:

This product has been evaluated for RCRA characteristics and does not meet the criteria of a hazardous waste if discarded in its purchased form. Under RCRA, it is the responsibility of the user of the product to determine at the time of disposal, whether the product meets RCRA criteria for hazardous waste. This is because product uses, transformations, mixtures, processes, etc. may render the resulting materials hazardous.

Remarks: None.

SECTION 13 TRANSPORT INFORMATION

Transportation

DOT/IMO IMO regulated product component: Propane, see also Petroleum Gases, liquefied
ICAO/IATA: Hazard Class: 2.1
U. N. No.: 1978
DOT/IMO label: Flammable gas

SECTION 14 REGULATORY INFORMATION

FEDERAL REGULATIONS

This product and/or its components are considered non-hazardous by the following standards:

OSHA Hazard Comm. Standard Classification

SARA Title III Section 311 Hazardous Categorization

No chemicals subject to reporting per the following standards:

SARA Title III Section 302/304 Extremely Hazardous Substances.

SARA Title III Section 313 Toxic Chemical.

CERCLA 102(a)/DOT Hazardous Substances.

California Prop. 65

States Right-to-Know Regulations.

State list: CT (Connecticut), FL (Florida), IL (Illinois), MI (Michigan),
LA (Louisiana), MA (Massachusetts), NJ (New Jersey),
PA (Pennsylvania), RI (Rhode Island)

INTERNATIONAL REGULATIONS

TSCA Inventory Status: This product, or its components, are listed on, or are exempt from the Toxic Substance Control Act (TSCA) Chemical Substance Inventory.

Canadian Inventory Status: This product, or its components, are listed on or are exempt from the Canadian Domestic Substance List (DSL).

EINECS Inventory Status: This product, or its components, are listed on or are exempt from the European Inventory of Existing Chemical Substances (EINECS) or the European List of Notified Chemical Substances (ELINCS).

Australian Inventory Status: Not determined.

Japan Inventory Status: Not determined.

SECTION 15**ENVIRONMENTAL INFORMATION**

Lubricant Biodegradability: Estimated to be less than 40% degradation over a test period of more than 28 days.

Potential to Bioaccumulation: This product is estimated to have a very slow rate of bioaccumulation.

Remarks: None

SECTION 16**OTHER INFORMATION**

None

Date of Revision: October 29, 2010,
Supersedes: May, 2010 and older versions

Nu-Calgon
2008 Altom Ct
St. Louis, MO 63146

The information contained herein is based on the data available to us and is believed to be correct. However, Nu-Calgon makes no warranty, expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Nu-Calgon assumes no responsibility for injury from the use of the product described herein.