Product Name: Spacer (Corrugated Fiber)

MSDS No.: 013205

Part Numbers Covered:

013205 013206 013305 013306 013307								
I. Basic In	formation:							
Manufacturer: WILLIAM H. HARVEY COMPANY						NFPA Fire		
Address: 433	34 SOUTH 67TH ST	REET			ı	المالم ا	Reastivity	
City, ST Zip: OMAHA, NE 68117-1019								
Emergency C	contact: CHEMTRE	С						
Emergency Telephone Number: (800)424-9300								
Contact: Ray	y Rael / Jason Hertz					~		
Information Telephone Number: (800)228-9681								
Last Update:	07/08/2002	Expiration Date:				0 Flamm	ability	
Chemical State: Liquid Gas X Solid Peactivity								
Chemical Typ	De: Pure	X Mixture				Pers. F	Protection	
II. Ingredi	ents:							
Trade Se	cret							
_			E	HS IA	RC SAF		400	0.11
CAS No.	Chemical Name		% Range	NTP	SUB Z	3 OSHA PEL	ACGIH TLV	Other Limits
NA	THIS ITEM IS NOT AS HAZARDOU ACCORDANCE 1910.1200.		NI	1		NI	NI	NI
III. Hazar	dous Identificati	on:						
Hazard Category:								
Acute Chronic		Fire		Pressure		Reactive		
Hazardous Id NI	lentification Inform	ation:						
IV. First A	Aid Measures:							
IV. First A								

Product Name: Spacer (Corrugated Fiber)

MSDS No.: 013205
Signs and Symptoms:

NI

Medical Conditions Generally Aggravated by Exposure:

NI

Emergency and First Aid Procedures:

EMERGENCY FIRST AID CALL: 1-303-623-5716 COLLECT

NONE

Other Health Warnings:

NI

V. Fire Fighting Measures:

Flash Point: NI Lower Explosive Limit: NI Upper Explosive Limit:

F.P. Method:

Fire Extinguishing Media: WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE

Special Fire Fighting Procedures:

WEAR NIOSH APPROVED RESPIRATOR WHEN LARGE VOLUMES ARE BURNING; WILL MELT AT TEMPERATURES GREATER THAN 250 C DEG.

Unusual Fire and Explosion:

DOES NOT BURN UNDER ORDINARY USE.

VI. Accidental Release Measures:

Steps to be Taken in Case Material is Released or Spilled:

NI

VII. Handling and Storage:

Precautions to be Taken:

NI

Other Precautions:

NI

VIII. Exposure Controls/Personal Protection:

Ventilation Requirements:

NI

Personal Protective Equipment:

EYE PROTECTION RECOMMENDED

Product Name: Spacer (Corrugated Fiber)

MSDS No.: 013205

IX. Physical and Chemical Properties:

Boiling Point: NI Melting Point: NI

Evaporation Rate (Butyl Acetate = 1): NI Vapor Pressure (mm Hg.): NI Specific Gravity (H20 = 1): 0.00000 Vapor Density (AIR = 1): NI

Solubility In Water: NI Appearance and Odor: CORRUGATED BROWN FIBER

Other Information:

X. Stability and Reactivity:

Stability:

STABLE

Incompatibility (Materials to Avoid):

ACIDS, MATERIALS WILL BREAK DOWN ON CONTACT

Decomposition/By Products:

CO, CO2, HYDROCARBONS AT HIGH TEMPERATURE (250 C DEG)

Hazardous Polymerization:

WILL NOT OCCUR

XI. Toxicological Information:

NDA

XII. Ecological Information:

NDA

XIII. Disposal Considerations:

STANDARD LANDFILL CONSISTENT WITH APPLICABLE FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.

XIV. Transport Information:

TRANSPORATION INFORMATION:

DOT PROPER SHIPPING NAME: N/A

DOT LABEL: N/A DOT NUMBER: N/A UN NUMBER: N/A MCO CLASS: N/A

DOT HAZARD CLASSIFICATION: N/A

XV. Regulatory Information:

NDA

Product Name: Spacer (Corrugated Fiber)

MSDS No.: 013205

XVI. Other Information:

ABBREVIATIONS:

N/A = NOT APPLICABLE N/I = NONE INDICATED NDA = NO DATA AVAILABLE N/E = NOT ESTABLISHED C = CELSIUS DEGREES F = FAHRENHEIT DEGREES

DISCLAIMER:

THE INFORMATION HEREIN HAS BEEN COMPILED FROM SOURCES BELIEVED TO BE RELIABLE, UP-TO-DATE, AND IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, WILLIAM H. HARVEY COMPANY CANNOT GIVE ANY GUARANTEES REGARDING INFORMATION FROM OTHER SOURCES, AND EXPRESSLY DOES NOT MAKE WARRANTIES, NOR ASSUMES ANY LIABILITY FOR ITS USES.