

EMT and Rigid Combination Conduit Bodies with Covers and Gaskets

LB Type

Features

- Combination LB type with cover and gasket
- NPT tapered hubs
- Suitable for use in concrete
- NEMA FB 1 rated for wet locations use with threaded rigid metal conduit only

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die cast
- Cover - Stamped steel
- Gasket - Neoprene rubber


Standard Finish

- Powder coat



E195124

UL Standard: 514A
Fed. Spec. W-C-586D
NEMA FB 1



Catalog Number	UPC	Size	Max. Number	Max. Size	Unit Carton	Ship Case	Weight/Case	A	Inches B	C
LB1SSCG	83768	1/2"	1	6 AWG	10	100	34	4.56	2.06	1.31
LB2SSCG	83769	3/4"	2	6 AWG	10	50	23	5.31	2.37	1.48
LB3SSCG	83770	1"	3	6 AWG	5	25	19	6.25	2.63	1.75
LB4SSCG	83771	1-1/4"	3	2 AWG	2	10	14	8.22	3.50	2.40
LB5SSCG	83772	1-1/2"	3	2 AWG	2	10	15	8.22	3.75	2.40
LB6SSCG	83773	2"	3	2/0 AWG	---	5	14	10.13	4.28	3.10