

# Flexible Liquidtight Conduit

## Metallic - Coil

### Features

- Crush and corrosion resistant steel core for lasting mechanical protection
- EF PVC jacket is oil and sunlight resistant
- Smooth interior for easy wire pull through

### Applications

- For use in damp or wet locations, suitable for commercial and industrial use
- Non UL

### Standard Material

- EF PVC jacketed steel core coil wrapped in clear plastic shrink wrap



Catalog Number	UPC	Size	Feet Coil	Ship Case	Weight/Case	Inside Diameter		Outside Diameter	
						Min.	Max.	Min.	Max.
<b>6100</b>	80414	<b>3/8"</b>	100'	100	16	.484	.504	.689	.709
<b>6101</b>	80415	<b>1/2"</b>	100'	100	26	.622	.642	.819	.839
<b>6102</b>	80417	<b>3/4"</b>	100'	100	31	.815	.835	1.032	1.051
<b>6103</b>	80419	<b>1"</b>	100'	100	44	1.032	1.055	1.287	1.315
<b>6104</b>	80421	<b>1-1/4"</b>	50'	50	46	1.37	1.394	1.63	1.661
<b>6105</b>	80423	<b>1-1/2"</b>	50'	50	35	1.579	1.598	1.866	1.902
<b>6106</b>	80425	<b>2"</b>	25'	25	22	2.02	2.043	2.339	2.374
<b>6106C50</b>	86340	<b>2"</b>	50'	50	49	2.02	2.043	2.339	2.374
<b>6107</b>	80427	<b>2-1/2"</b>	25'	25	42	2.48	2.504	2.839	2.874
<b>6108</b>	80429	<b>3"</b>	25'	25	53	3.071	3.102	3.461	3.50
<b>6109</b>	80430	<b>3-1/2"</b>	25'	25	55	3.50	3.54	3.96	4
<b>6110</b>	80431	<b>4"</b>	25'	25	57	4	4.039	4.457	4.50