

# Rigid Watertight Hubs

## Insulated Throat - Zinc Die Cast

### Features

- Flame-retardant insulated throat
- Rain, oil, and dust tight
- Oversized locknut protects against damage from vibrations and promotes positive grounding

### Applications

- Indoor or outdoor use
- Use to connect Rigid or IMC conduit to a load center or other metal enclosure where a watertight joint is required at knockouts or slip-fit holes

### Standard Material


- Zinc die cast

### Applicable Third Party Standards

- UL Standard: UL 514B
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB 1-2014



NEMA 2 3R, 4, 4X, 5, 12, 13



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	Inches	
						A	B
201	11550	1/2"	25	250	49	1.31	1.54
202	11560	3/4"	10	100	29	1.37	1.73
203	11570	1"	10	100	42	1.59	2.04
204	11580	1-1/4"	2	20	12	1.59	2.42
205	11590	1-1/2"	2	20	15	1.59	2.79
206	11600	2"	2	10	9	1.59	3.30
207	11610	2-1/2"	---	5	8	2.44	3.70
208	11620	3"	---	5	9	2.44	4.39
209	11630	3-1/2"	---	5	11	2.44	4.88
210	11640	4"	---	1	3	2.44	5.50