

EMT Connectors

Compression Type - Steel



Features

- Compression type connectors
- Concrete tight
- Assembled with a steel locknut
- Also available with insulated throat

Applications

- Use to join EMT to box or enclosure

Standard Material

- Steel

Standard Finish


- Zinc plated

Applicable Third Party Standards

- UL Standard: UL 514B
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB1-2014



1/2"-2" E18472
2-1/2"-4" E148716



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	Inches		
						A	B	C
651S	16790	1/2"	25	250	30	1.75	1.25	.406
652S	16800	3/4"	25	250	43	1.813	1.563	.406
653S	16810	1"	10	100	25	2	1.813	.406
654S	16820	1-1/4"	---	25	12	2.75	2.188	.50
655S	16830	1-1/2"	---	20	12	3	2.438	.50
656S	16840	2"	---	15	15	3.188	2.938	.688
657S	16841	2-1/2"	---	12	19	3.875	3.688	.75
658S	16842	3"	---	6	15	4.375	4.313	.938
659S	16843	3-1/2"	---	6	16	4.50	4.875	.938
660S	16844	4"	---	6	21	4.75	5.375	.938