

## Vinyl Electrical Tapes

## 3M™ Temflex™ Vinyl Electrical Tape 1700

3M™ Temflex™ Electrical Tape 1700 is a good quality, economical general purpose vinyl insulating tape. It has excellent resistance to abrasion, moisture, alkalies, acid, copper corrosion and varying weather conditions. It is a polyvinyl chloride (PVC) tape that is flame-retardant and conformable. Temflex Tape 1700 provides excellent mechanical protection with minimum bulk. It is a UL Listed and CSA Certified "Insulating Tape."




Adhesive Material	Rubber Resin
Backing Material	Polyvinyl Chloride
Tape Grade	General Use
Tape Type	Vinyl
Operating Temperature	32–176°F (0–80°C)
RoHS 2011/65/EU	Yes
Specifications	ASTM D 2301 type 1, MSHA (1700P only)
Agency Approvals	UL  CSA 
Country of Origin	 and Taiwan



Order No.	UPC	Color	Length	Width	Thickness	Breaking Strength	Rolls per Case
1700-1X66FT	054007-43962	Black	66'	1.00"	7 mil	17 lbs/in	99
1700-3/4X36YD-1.5CORE	054007-49700	Black	36 yd	0.75"	7 mil	17 lbs/in	100
1700-3/4X60FT	054007-69764	Black	60'	0.75"	7 mil	17 lbs/in	100
1700P-PRINTED-3/4X66FT	054007-08175	Black	67'	0.75"	7 mil	17 lbs/in	100
1700P-PRINTED-1-1/2X44FT	054007-08408	Black	44'	1.50"	7 mil	17 lbs/in	100
1700P-PRINTED-1-1/2X66FT	054007-50750	Black	66'	1.50"	7 mil	17 lbs/in	100

## 3M™ Temflex™ Vinyl Electrical Tape 1776

3M™ Temflex™ Vinyl Electrical Tape 1776 is a good quality, economical general-purpose vinyl insulating tape, manufactured in the U.S.A. It has excellent resistance to abrasion, moisture, alkalies, acid, copper, corrosion and varying weather conditions. It is a polyvinyl chloride (PVC) tape that is flame-retardant and conformable. Temflex Tape 1776 provides excellent mechanical protection with minimum bulk. It is a UL Listed and CSA Certified "Insulating Tape."

Tape Grade	General Use
Tape Type	Vinyl
Maximum Operating Temperature	176°F (80°C)
RoHS 2011/65/EU	Yes
Agency Approvals	UL  CSA 
Country of Origin	



Order No.	UPC	Color	Length	Width	Thickness	Elongation	Breaking Strength	Adhesion to Steel	Rolls per Carton	Rolls per Case
1776-3/4"x60'	051128-58442	Black	60'	0.75"	7 mil	200%	17 lbs/in	24 oz/in	10	100