




### **TYPE "A" END CAP**

The Type "A" End Cap is supplied on all Concrete Inserts longer than 12". End Caps may be ordered separately.




Catalog No.		Use With Anvil-Strut	A	Std. Pkg.	Wt./100 Pcs.
🗆 AS 902	🗆 PG	AS 100	<b>3</b> <sup>7</sup> /32"	100	19
🗆 AS 2580	🗆 PG	AS 150	2 <sup>3</sup> ⁄8"	100	16
🗅 AS 655	🗆 PG	AS 200	<b>1</b> 5⁄8"	100	7
🗆 AS 656	🗆 PG	AS 300	<b>1</b> ³⁄8"	100	6
🗆 AS 901	🗆 PG	AS 400	1"	100	4
🗆 AS 930	🗆 PG	AS 500	<b>1</b> <sup>13</sup> ⁄16"	200	4

Std Pkg & Wt/100 pcs: See chart above.

#### **TYPE "B" END CAP**


The Type "B" End Cap is furnished on all Inserts up to 12" in length and provides nail lugs at each end of the Insert. End Caps may be ordered separately.



Catalog No.		Use With Anvil-Strut	C	D	Wt./100 Pcs.
🗆 AS 652	🗆 PG	AS 200	1.42	3 <sup>1</sup> ⁄8"	19
🗆 AS 653	🗆 PG	AS 300	1.17	27⁄8"	16
🗆 AS 654	🗆 PG	AS 400	0.79	<b>2</b> <sup>1</sup> /2"	7

Std Pkg 50 - Wt/100 pcs: See chart above.

## END CAP WITH KNOCK OUT (CONDUIT END CAP)




□ AS 2511 3 🗆 EG AS 300 1/2" When ordering AS 2511 2, please specify conduit size.

**AS 6153** 

Std Pkg 50 - Wt/100 pcs: See chart above.

# □ Red, □ White PLASTIC RED & WHITE SAFETY END CAP



Size	Std. Pkg.	Wt./100 Pcs.	Use With Channel
1	100	5.0	AS 100
2	100	2.8	AS 200 & AS 210
3	100	2.5	AS 300
5	100	2.0	AS 500
5		-	

Std Pkg & Wt/100 pcs: See chart above.

#### LEGEND:

GR: Powder Coated Supr-Green EG: Electro-Galvanized PG: Pre-Galvanized AL: Aluminum HG: Hot Dipped Galvanized PL: Plain SS: Stainless Steel ZTC: Zinc Trivalent Chromium Stainless Steel (SS), Zinc Trivalent Chromium (ZTC) and Hot Dipped Galvanized (HG) are specialty finishes. Pricing is located in the Specialty Strut Section of the Anvil-Strut price book.

	PROJECT INFORMATION	APPROVAL STAMP
Project:		Approved
Address:		Approved as noted
Contractor:		Not approved
Engineer:		Remarks:
Submittal Date:		
Notes 1:		
Notes 2:		
10 10 15		