

CLINIC SERVICE SINK

- Vitreous china
- Floor mount
- Flushing rim
- Siphon jet flushing action with bolt caps
- White Only

❑ 9504.999.020 Floor Service sink

Available Components:


- ❑ 710098-201.081 Pedestal base, black on white finish
- ❑ 7832504.075 Rim guard, service sink, floor

Nominal Dimensions:

743 x 508 x 457mm
(29-1/4" x 20" x 18")

NOTES:

- ❑ Fixture conforms to ANSI/ASME A112.19.2M standards
- ❑ Optional one, two or three rim guards available when specified and ordered accordingly (not shown)
- ❑ Optional pedestal base (approximately 28" x 14" x 10") available when specified and ordered accordingly (as shown)
- ❑ For efficient operation of the sink, a minimum flowing water pressure of 25 PSI is required at the valve.
- ❑ Valve specifications: Flush valve with vacuum breaker, 1" angle screwdriver stop and flush connection. Suggested (6.5 gpf/24.6 lpf) flush valves include:
 - ❑ Sloan "Royal" #117
 - ❑ Delany "Flushboy" #F418
 - ❑ Zurn "Aquaflush" #Z-6017XL-H



NOTES:

- * CUSTOMER SHOULD CHECK WITH GENERAL CONTRACTOR TO DETERMINE IF BASE IS BEING PROVIDED BEFORE PROCEEDING WITH ROUGHING-IN MEASUREMENTS.
- ** VARIABLE-CHECK WITH MANUFACTURER OF FLUSHVALVE FOR PROPER ROUGHING-IN DIMENSIONS.
- *** VARIABLE-CHECK WITH MANUFACTURER OF SERVICE SINK FAUCET FOR PROPER ROUGHING-IN DIMENSIONS.

IMPORTANT: Roughing-in dimensions may vary 1/2" and are subject to change or cancellation without prior notice. No responsibility is assumed for use of superseded or voided leaflets.

Available in White Only