

Catalog Number
Notes
Type

## FEATURES & SPECIFICATIONS

### INTENDED USE

For use with housings LC6, LI6, L7X, L7XR, LI6F, L7XF, L7XFR.

### CONSTRUCTION

All finishes are one-piece aluminum open reflectors with integral flange.

### INSTALLATION

Socket to trim interface.

Trim retention is achieved by utilizing two side-mounted torsion springs on the trim and two receiving brackets in the can, ensuring a consistently tight fit with the ceiling.

Maximum ceiling thickness 1/2".

### LISTINGS

UL Listed to U.S. and Canadian safety standards.

Damp location listed.

Note: Specifications subject to change without notice.

6" Full Reflector Trim

# 6B1

PREMIUM BAFFLE

Wide Flange




### Specifications

Height: 6-1/2 (16.5)

Lamp opening: 4-5/8 (11.7)

Diameter: 7-5/8 (19.4)

Trim height when used with Non-IC incandescent rough-in.  
All dimensions are inches (centimeters) unless otherwise indicated.



### ORDERING INFORMATION

For shortest lead times, configure product using **standard options (shown in bold)**.

**Example: 6B1**

6B1		
Series	Finish	
6B1	<b>(blank)</b>	White reflector with black baffle <sup>1</sup>
	<b>W</b>	White baffle

### Housing Compatibility: Housing and trim ordered separately.

Application	Source	Maximum wattage	Housing
IC	Incandescent	75 PAR30	LC6, LI6, L7X, L7XR
		65 BR30	LC6, LI6, L7X, L7XR
		40 A19	LC6, LI6, L7X, L7XR
	Fluorescent	13DTT	L7XF, L7XFR
		18DTT	L7XF, LI6F, L7XFR
		26TRT	LI6F, L7XF
	32TRT	LI6F	

### Notes

1 Flange matches trim finish.

