

FEATURES & SPECIFICATIONS

INTENDED USE

For use with frame-in LP6 and LP6F, and housings LC6, LI6, L7X, L7XR, LI6F, L7XF and L7XFR.

CONSTRUCTION

- Aluminum white reflector.
- Polyester powder coat paint.
- Opal or prismatic polycarbonate diffuser.
- Drop or flush lens.
- White integral flange or white plastic flange.

INSTALLATION

- Socket to trim interface.
- Rough-ins with clips retain trim.
- Retaining clips riveted to top of trim to hold trim inside housing.

LISTINGS

- UL Listed to US and Canadian safety standards.
- Wet location listed.
- Pull on clip Patent # (US) 5707143, (Canada) 2193902.

WARRANTY

- 1-year limited warranty. Complete warranty terms located at www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx
- Actual performance may differ as a result of end-user environment and application.
- Note: Specifications subject to change without notice.

Catalog Number
Notes
Type

6" Full Reflector Trim


6L1/2

LENS

Wet Location
Narrow Flange




Drop opal lens



Flush prismatic lens

Specifications

- Height: 5-3/4" (14.6)
- Lamp opening: 5-5/8" (14.3)
- Diameter: 7-5/8" (19.4)
- Trim height when used with Non-IC incandescent rough-in



All dimensions are in inches (centimeters) unless otherwise indicated.

ORDERING INFORMATION

For shortest lead times, configure product using **bolded options**.

Example: 6LD1

Series	Options
6LD1 Drop opal lens	PF Integral white plastic flange ¹
6LD2 Drop prismatic lens	
6LF1 Flush opal lens	
6LF2 Flush prismatic lens	

Housing Compatibility: Housing and trim ordered separately.			
Application	Source	Maximum wattage	Housing
IC	Incandescent	40 A19	LI6
	Fluorescent	13DTT	L7XF, L7XFR
		26TRT	LI6F, L7XF, L7XFR
Non-IC	Incandescent	60 A19	LC6, LP6, L7X, L7XR
	Fluorescent	18TRT*	L7XF, L7XFR
		13DTT	LP6F
		18DTT*	
		26TRT	

* Drop lens only

Notes

- Flush lens (6LF1, 6LF2) with plastic flange option is not compatible with CFL housings.

