

WSL1F

SERIES

LAMPS

9DTT¹
13DTTE^{1,2}

VOLTAGE

120
277

FACEPLATE³

FPL White Louvered
FPLBL Black Louvered
FPS White Slotted
FPSBL Black Slotted
FPO White Opal
FPOBL Black Opal




Slotted
9DTT
13DTTE (4-pin only)



Opal
9DTT
13DTTE (4-pin only)



Louvered
Faceplates
9DTT
13DTTE (4-pin only)



NOTES:

- 1 Must specify voltage (9DTT120V only).
- 2 Electronic ballast standard.
- 3 Must be ordered as separate line item, faceplate shipped separately.

REMODELER CLIPS



ARC 144
Box of 144 loose clips.

ARC 12
12 packs of 12 clips (144).
Used to secure frame-ins in ceiling in remodel applications.

T-BAR MOUNTING CLIPS



LSMC
Designed to lock bar hangers to T-bar. Set of 4 clips.

CHANNEL BAR MOUNTING BRACKETS



LCMB
Used when commercial channel bars are desired to mount fixture. Channel bars not included. Set of two brackets. For use with 4", 5" and 6" frame-ins only.

COLOR FILTERS/SPECIALTY LENSES



- F200DB Dark Blue
- F200MA Medium Amber
- F200MB Medium Blue
- F200MG Medium Green
- F200MP Medium Pink
- F200RR Ruby Red
- F200UV Ultra Violet
- F200SL Spread Lens
- F200EG Elongating Lens
- F200ST Softening Lens

For use on 6" low voltage trims using a MR16 lamp. Not for use on 4" low voltage trims.

LBH - BAR HANGERS



LBH
Extended bar hangers used for extreme off-center mounting in a 24" space. Set of two 22" bar hangers. For use with 4", 5" or 6" frame-ins only.

OVERSIZE TRIM RINGS



CTR5
7-1/8" (19.9 cm) O.D.
Use with J Series trims only.

CTR6
8-3/4" (22.2 cm) O.D. Use with 6, 7, C and F6 Series trims. Compatible with all 7-5/8" flanged trims only.

CEILING THICKNESS EXTENDER



CTE
Use when ceiling thickness is greater than 1-1/2". Maximum thickness 2" (5.1cm). For use with 6" reflectors only. Not compatible with VPE2, VMB4, F6-Series and 7-Series reflectors.

CTE8
Use when ceiling thickness is greater than 1-1/2". Maximum thickness 2" (5.1cm). For use with 8" reflectors only.

SLOPE CEILING ADAPTER



SCA
Sloped ceiling adapter. Compatible with 8 inch and 6 inch commercial fixtures. Available in 5-degree increments, 10 degrees through 30 degrees. White only. See chart for fixture compatibility. Ex: SCA6 15D

OPTIONS

ELECTRONIC BALLAST

GEB10
Generic electronic ballast. <10% THD (Total Harmonic Distortion). Requires four-pin lamp.

MVOLT
Electronic multi-volt ballast capable of operating any line voltage from 120-277V, 50 or 60 Hz.

HEB
Electronic HID ballast. 120V or 277V, 50 or 60 HZ. THD <15%. PF>0.90.

MAGNETIC BALLAST

HPF
High power factor magnetic ballast, 90% power factor.

ELECTRONIC DIMMING BALLAST

ADEZ
Advance Mark 10™ electronic ballast, 120V or 277V. Requires four-pin lamp (18DTT, 26DTT, 18TRT, 26TRT, 32TRT, 42TRT or 57TRT only). Minimum dimming level 5%.

DMHL
Lutron Compact SE™ electronic dimming ballast, 120V or 277V. Requires four-pin lamp (18DTT, 26DTT, 18TRT, 26TRT, 32TRT or 42TRT only.) Minimum dimming level 5%.

FUSING

GMF
Single slow-blow fuse. For use with fluorescent fixtures only.

SF
Single fuse (120V, 277V or 347V only).

STEPDOWN TRANSFORMER

SDT
277V stepdown transformer (277V to 120V). For use with incandescent fixtures (maximum 300 watts).

EMERGENCY

EL
Emergency battery pack with integral test switch. Operates one four-pin lamp in emergency mode with battery back-up in case of power disruption. Not available with a magnetic ballast. Consult factory.

ELR
Emergency battery pack with remote test switch. Operates one four-pin lamp in emergency mode with battery back-up in case of power disruption. Not available with a magnetic ballast.

TRIM

TRW
White flange.

RELOC

LRC
Provides compatibility with Lithonia Reloc® System. Lithonia Reloc System can be installed less this option with connectors provided by others. Not required on electronic CFL units.

MISCELLANEOUS

ENCL
Standard medium-base socket. For use when 50, 70, 100 and 150 metal halide frame-in is used with PAR38 metal halide or CMH lamps.

AT
Sealed airtight housing to minimize air flow through rough-in. Complies with WSEC and certified per ASTM E283.

WLP
35K Lamp (shipped separately).

ACCESSORIES

FRAME-IN COMPATIBILITY

Accessories are ordered separately.

	ARC144	ARC12	LSMC	LCMB	LBH	CTE	SCA6	SCA8
LF8 1/TRT	■	■	■	■	■			■
LF8 2/TRT	■	■	■	■	■			■
LF8 2/DTT	■	■	■	■	■			■
LP8F	■	■	■	■	■			■
LF6 1/TRT	■	■	■	■	■			■
LF6 2/DTT	■	■	■	■	■			■
LIF6			■	■	■			■
LP6F	■	■	■	■	■			■
LI6F			■	■	■			■
LQJ	■	■	■	■	■			■
LP8	■	■	■	■	■			■
LP6	■	■	■	■	■			■
LPJ	■	■	■	■	■			■
LP8H	■	■	■	■	■			■
LP6H	■	■	■	■	■			■
LV	■	■	■	■	■			■
LP3V			■	■	■			■

■ Option available
(blank) Option not available

OPTIONS

FRAME-IN COMPATIBILITY

	GEB10	MVOLT	HPF	HEB	ADEZ	DMHL	SDT	GMF	SF	EL	ELR	LRC	ENCL	AT	WLP
LF8 1/TRT	■	■			■	■		■		■	■				■
LF8 2/TRT	■	■			■	■		■		■	■				■
LF8 2/DTT	■	■	▲		■	■		■		■	■				■
LP8F	■	■	▲		■	■		■		■	■				■
LF6 1/TRT	■	■			■	■		■		■	■				■
LF6 2/DTT	■	■	▲		■	■		■		■	■				■
LIF6						■		■		■	■				■
LP6F	■	■	▲		■	■		■		■	■				■
LI6F		▲				■		■		■	■				■
LQJ	■	■	■			■		■		■	■				■
LP8	■	■	■			■		■		■	■				■
LP6	■	■	■			■		■		■	■				■
LPJ	■	■	■			■		■		■	■				■
LP8H				■				■		■	■				■
LP6H				■				■		■	■				■
LV								■		■	■				■
LP3V								■		■	■				■

■ Option available
▲ Standard
(blank) Option not available