

**For Residential and Commercial Applications**

Job Name		Engineer / Architect	
Job Location		Wholesaler	
Submittal Date		Contractor	

## BL12-\*\*WA Speedi Plumb® PLUS Braided Washing Machine Connector – Female Hose Thread

**Use:** For use in potable water distribution systems in accessible locations only.

**Design Features:**


- **Engineered polymer braided** fibers bend freely without kinking or crimping
- **Reinforced PVC inner hose** ensures durability
- **Rubber washers** provide a large pliable sealing surface and ensure a long lasting water-tight connection
- **8-sided pneumatic crimp** provides greater dependability for reliable nut-to-hose connections
- **No Lead**

**Operating Specifications:**

**Temperature:** 40°- 140° F, intermittent to 180° F

**Pressure:** 125 PSI maximum

**Tubing Diameter:** 0.450" ID (0.660" OD)



MATERIAL SPECIFICATIONS	
<b>Inner Hose</b>	<i>EPDM or reinforced PVC</i>
<b>Braiding</b>	<i>PVC coated polyester yarn</i>
<b>Barb</b>	<i>Brass</i>
<b>Ferrule</b>	<i>Zinc-plated steel</i>
<b>Nut</b>	<i>Brass, chrome plated</i>
<b>Washer</b>	<i>Rubber</i>

**Part Listing:**

- |                          |             |  |
|--------------------------|-------------|--|
| <input type="checkbox"/> | BL12-48WA   | 3/4" female hose thread x 3/4" female hose thread x 48" length, sleeve       |
| <input type="checkbox"/> | BL12-48WA B | 3/4" female hose thread x 3/4" female hose thread x 48" length, bulk         |
| <input type="checkbox"/> | BL12-48WA F | 3/4" female hose thread x 3/4" female hose thread x 48" length, flag labeled |
| <input type="checkbox"/> | BL12-48WA P | 3/4" female hose thread x 3/4" female hose thread x 48" length, bagged       |
| <input type="checkbox"/> | BL12-60WA   | 3/4" female hose thread x 3/4" female hose thread x 60" length, sleeve       |
| <input type="checkbox"/> | BL12-60WA B | 3/4" female hose thread x 3/4" female hose thread x 60" length, bulk         |
| <input type="checkbox"/> | BL12-60WA F | 3/4" female hose thread x 3/4" female hose thread x 60" length, flag labeled |
| <input type="checkbox"/> | BL12-60WA P | 3/4" female hose thread x 3/4" female hose thread x 60" length, bagged       |


This specification and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft Mfg. This specification must be returned to BrassCraft Mfg. if requested.



# BL12-\*\*WA Speedi Plumb® PLUS Braided Washing Machine Connector – Female Hose Thread

**Part Listing (con't):**

- BL12-60WA PX2 3/4" female hose thread x 3/4" female hose thread x 60" length, 2 per bag, cutcase of 5
- BL12-72WA 3/4" female hose thread x 3/4" female hose thread x 72" length, sleeve
- BL12-72WA B 3/4" female hose thread x 3/4" female hose thread x 72" length, bulk
- BL12-72WA F 3/4" female hose thread x 3/4" female hose thread x 72" length, flag labeled
- BL12-72WA P 3/4" female hose thread x 3/4" female hose thread x 72" length, bagged



<b>PART DIMENSIONS (Inches)</b>	
<b>Model</b>	<b>DIM. A</b>
BL12-48WA	48.0 / 49.0
BL12-60WA	60.0 / 61.0
BL12-72WA	72.0 / 73.0

**Listings & Certifications:**

- IAPMO listed to ASME A112.18.6 and CSA B125.6 (File # 0452)
- CSA listed to ASME A112.18.6 and CSA B125.6 (File #204593)
- No-Lead product CSA listed to Low-Lead Content Certification Program – Plumbing Products Class 6853-01



*This specification and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft Mfg. This specification must be returned to BrassCraft Mfg. if requested.*

**BrassCraft®**