

## For Residential and Commercial Applications


Job Name		Engineer / Architect	
Job Location		Wholesaler	
Submittal Date		Contractor	

### CSSL 1/4" ID (3/8" OD) Coated Gas Appliance Connectors

**Use:** For use with indoor and outdoor connections of gas appliances to gas piping system. May be used with natural, manufactured, mixed and liquefied petroleum (LP or propane) gases and LP gas-air mixtures

**Design Features:**

- **Superior corrosion resistance** to harsh chemicals found in common household cleaning, plumbing repair and masonry products
- **UV rays & salt resistant**, ProCoat connectors are certified for indoor & outdoor use
- **Greater strength & flexibility** with greater depth & number of corrugations to withstand greater torque & bend cycles
- **Outperforms industry standards for torsion** (1.5X) without compromising the integrity of the coating or connector
- **Outperforms industry standard for repeated bending** (2X) without compromising the integrity of the coating or connector
- **One-piece construction** has no soldered or brazed joints
- **Smoother, burnished flare** on connector ends seal with less torque
- **Uniform coat over entire length of connector** for complete corrosion resistance of the stainless steel core
- **100% leak tested**



**Operating Specifications:**

**Temperature:** -40° to 150° F

**Pressure:** standard line pressures up to 1/2 psi maximum

#### CONNECTOR FLOW CAPACITY (Straight Length)

	12"	18"	24"	30"	36"	48"	60"	72"
BTU per Hour (NG)	48,000	43,800	40,000	36,400	33,400	28,300	24,900	23,100
BTU per Hour (LPG)	76,800	70,080	64,000	58,240	53,440	45,280	39,840	36,960
Watts per Hour (NG)	14,067	12,837	11,723	10,668	9,789	8,294	7,297	6,770


#### MATERIAL SPECIFICATIONS

Tubing	304L stainless steel
Coating	Polymer blend
Nuts	12L14 OR 1010 steel
Fittings	12L14 OR 1010 steel

*This specification and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This specification must be returned to BrassCraft if requested.*



# CSSL 1/4" ID (3/8" OD) Coated Gas Appliance Connectors



PART DIMENSIONS ( Inches )									
Connector Length – Nut by Nut									
Model	DIM.	12"	18"	24"	30"	36"	48"	60"	72"
CSSL	A	10.50 / 11.25	16.50 / 17.25	22.50 / 23.25	28.50 / 29.75	34.50 / 35.75	46.50 / 48.75	58.50 / 60.25	70.50 / 72.25

PART DIMENSIONS ( Inches )									
Connector Lengths – with Fittings									
Model	DIM.	12"	18"	24"	30"	36"	48"	60"	72"
CSSL44	B	13.00 / 13.75	19.00 / 19.75	25.00 / 25.75	30.00 / 32.25	37.00 / 38.25	49.00 / 51.25	61.00 / 62.75	73.00 / 74.75
CSSL47	B	12.75 / 13.50	18.75 / 19.50	24.75 / 25.50	29.75 / 32.00	36.75 / 38.00	48.75 / 51.00	60.75 / 62.50	72.75 / 74.50
CSSL77	B	12.50 / 13.25	18.50 / 19.25	24.50 / 25.25	30.50 / 31.75	36.50 / 37.75	48.50 / 50.75	60.50 / 62.25	72.50 / 74.25
CSSL48	B	12.60 / 13.35	18.60 / 19.35	24.60 / 25.35	30.60 / 31.85	36.60 / 37.85	48.60 / 50.85	60.60 / 62.35	72.60 / 74.35
CSSL55	B	12.34 / 13.09	18.34 / 19.09	24.34 / 25.09	30.34 / 31.59	36.34 / 37.59	48.34 / 50.59	60.34 / 62.09	72.34 / 74.09
CSSL88	B	12.20 / 12.95	18.20 / 18.95	24.20 / 24.95	30.20 / 31.45	36.20 / 37.45	48.20 / 50.45	60.20 / 61.95	72.20 / 73.95
CSSL54	B	12.67 / 13.42	18.67 / 19.42	24.67 / 25.42	30.67 / 31.92	36.67 / 37.92	48.67 / 50.92	60.67 / 62.42	72.67 / 74.42
CSSL87	B	12.35 / 13.10	18.35 / 19.10	24.35 / 25.10	30.35 / 31.60	36.35 / 37.60	48.35 / 50.60	60.35 / 62.10	72.35 / 74.10
Connector Lengths – with Fitting & Gas Ball Valves									
CSSL4M	B	13.63 / 14.38	19.63 / 20.38	25.63 / 26.38	31.63 / 32.88	37.63 / 38.88	49.63 / 51.88	61.63 / 63.38	73.63 / 75.38
CSSL7M	B	13.38 / 14.13	19.38 / 20.13	25.38 / 26.13	30.38 / 32.63	37.38 / 38.63	49.38 / 51.63	61.38 / 63.13	73.38 / 75.13
CSSL8M	B	13.23 / 13.98	19.23 / 19.98	25.23 / 25.98	30.23 / 32.48	37.23 / 38.48	49.23 / 51.48	61.23 / 62.98	73.23 / 74.98

**Part Listing:**

**Connectors with Fittings**

- CSSL44-12      1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 12" length

*This specification and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This specification must be returned to BrassCraft if requested.*



# CSSL 1/4" ID (3/8" OD) Coated Gas Appliance Connectors

## Connectors with Fittings (con't)

<input type="checkbox"/>	CSSL11-12	1/4" ID (3/8" OD) with 3/4" MIP x 3/4" MIP fittings x 12" length
<input type="checkbox"/>	CSSL11-18	1/4" ID (3/8" OD) with 3/4" MIP x 3/4" MIP fittings x 18" length
<input type="checkbox"/>	CSSL11-24	1/4" ID (3/8" OD) with 3/4" MIP x 3/4" MIP fittings x 24" length
<input type="checkbox"/>	CSSL11-30	1/4" ID (3/8" OD) with 3/4" MIP x 3/4" MIP fittings x 30" length
<input type="checkbox"/>	CSSL11-36	1/4" ID (3/8" OD) with 3/4" MIP x 3/4" MIP fittings x 36" length
<input type="checkbox"/>	CSSL11-48	1/4" ID (3/8" OD) with 3/4" MIP x 3/4" MIP fittings x 48" length
<input type="checkbox"/>	CSSL11-60	1/4" ID (3/8" OD) with 3/4" MIP x 3/4" MIP fittings x 60" length
<input type="checkbox"/>	CSSL11-72	1/4" ID (3/8" OD) with 3/4" MIP x 3/4" MIP fittings x 72" length
<input type="checkbox"/>	CSSL44-18	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 18" length
<input type="checkbox"/>	CSSL44-24	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 24" length
<input type="checkbox"/>	CSSL44-30	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 30" length
<input type="checkbox"/>	CSSL44-36	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 36" length
<input type="checkbox"/>	CSSL44-36 P	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 36" length, bagged
<input type="checkbox"/>	CSSL44-48	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 48" length
<input type="checkbox"/>	CSSL44-48 P	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 48" length, bagged
<input type="checkbox"/>	CSSL44-60	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 60" length
<input type="checkbox"/>	CSSL44-60 P	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 60" length, bagged
<input type="checkbox"/>	CSSL44-72	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 72" length
<input type="checkbox"/>	CSSL44-72 P	1/4" ID (3/8" OD) with 1/2" MIP x 1/2" MIP fittings x 72" length, bagged
<input type="checkbox"/>	CSSL47-18	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" MIP fittings x 18" length
<input type="checkbox"/>	CSSL47-24	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" MIP fittings x 24" length
<input type="checkbox"/>	CSSL47-30	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" MIP fittings x 30" length
<input type="checkbox"/>	CSSL47-36	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" MIP fittings x 36" length
<input type="checkbox"/>	CSSL77-12	1/4" ID (3/8" OD) with 3/8" MIP x 3/8" MIP fittings x 12" length
<input type="checkbox"/>	CSSL77-18	1/4" ID (3/8" OD) with 3/8" MIP x 3/8" MIP fittings x 18" length
<input type="checkbox"/>	CSSL77-24	1/4" ID (3/8" OD) with 3/8" MIP x 3/8" MIP fittings x 24" length
<input type="checkbox"/>	CSSL77-30	1/4" ID (3/8" OD) with 3/8" MIP x 3/8" MIP fittings x 30" length
<input type="checkbox"/>	CSSL77-36	1/4" ID (3/8" OD) with 3/8" MIP x 3/8" MIP fittings x 36" length
<input type="checkbox"/>	CSSL77-48	1/4" ID (3/8" OD) with 3/8" MIP x 3/8" MIP fittings x 48" length
<input type="checkbox"/>	CSSL48-12	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" FIP fittings x 12" length
<input type="checkbox"/>	CSSL48-18	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" FIP fittings x 18" length
<input type="checkbox"/>	CSSL48-24	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" FIP fittings x 24" length
<input type="checkbox"/>	CSSL48-30	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" FIP fittings x 30" length
<input type="checkbox"/>	CSSL48-36	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" FIP fittings x 36" length
<input type="checkbox"/>	CSSL48-48	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" FIP fittings x 48" length
<input type="checkbox"/>	CSSL48-60	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" FIP fittings x 60" length
<input type="checkbox"/>	CSSL48-72	1/4" ID (3/8" OD) with 1/2" MIP x 3/8" FIP fittings x 72" length
<input type="checkbox"/>	CSSL55-12	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" FIP fittings x 12" length
<input type="checkbox"/>	CSSL55-18	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" FIP fittings x 18" length
<input type="checkbox"/>	CSSL55-24	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" FIP fittings x 24" length
<input type="checkbox"/>	CSSL55-30	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" FIP fittings x 30" length
<input type="checkbox"/>	CSSL55-36	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" FIP fittings x 36" length
<input type="checkbox"/>	CSSL55-48	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" FIP fittings x 48" length
<input type="checkbox"/>	CSSL58-48	1/4" ID (3/8" OD) with 1/2" FIP x 3/8" FIP fittings x 48" length
<input type="checkbox"/>	CSSL58-48 P	1/4" ID (3/8" OD) with 1/2" FIP x 3/8" FIP fittings x 48" length, bagged
<input type="checkbox"/>	CSSL88-12	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" FIP fittings x 12" length
<input type="checkbox"/>	CSSL88-12 X	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" FIP fittings x 12" length, bagged, cut case
<input type="checkbox"/>	CSSL88-18	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" FIP fittings x 18" length

*This specification and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This specification must be returned to BrassCraft if requested.*



# CSSL 1/4" ID (3/8" OD) Coated Gas Appliance Connectors

## Connectors with Fittings (con't)

<input type="checkbox"/>	CSSL88-24	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" FIP fittings x 24" length
<input type="checkbox"/>	CSSL88-24 K12	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" FIP fittings x 24" length, 12 per carton
<input type="checkbox"/>	CSSL88-30 K12	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" FIP fittings x 30" length, 12 per carton
<input type="checkbox"/>	CSSL88-36	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" FIP fittings x 36" length
<input type="checkbox"/>	CSSL88-48	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" FIP fittings x 48" length
<input type="checkbox"/>	CSSL88-60	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" FIP fittings x 60" length
<input type="checkbox"/>	CSSL54-12	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 12" length
<input type="checkbox"/>	CSSL54-12 P	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 12" length, bagged
<input type="checkbox"/>	CSSL54-18	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 18" length
<input type="checkbox"/>	CSSL54-18 P	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 18" length, bagged
<input type="checkbox"/>	CSSL54-18 X	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 18" length, bagged, cut case
<input type="checkbox"/>	CSSL54-24	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 24" length
<input type="checkbox"/>	CSSL54-24 P	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 24" length, bagged
<input type="checkbox"/>	CSSL54-24 X	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 24" length, bagged, cut case
<input type="checkbox"/>	CSSL54-24 X10	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 24" length, bagged, carton of 10
<input type="checkbox"/>	CSSL54-30	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 30" length
<input type="checkbox"/>	CSSL54-30 P	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 30" length, bagged
<input type="checkbox"/>	CSSL54-30 X	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 30" length, bagged, cut case
<input type="checkbox"/>	CSSL54-36	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 36" length
<input type="checkbox"/>	CSSL54-36 P	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 36" length, bagged
<input type="checkbox"/>	CSSL54-36 X	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 36" length, bagged, cut case
<input type="checkbox"/>	CSSL54-48	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 48" length
<input type="checkbox"/>	CSSL54-48 P	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 48" length, bagged
<input type="checkbox"/>	CSSL54-48 X	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 48" length, bagged, cut case
<input type="checkbox"/>	CSSL54-60	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 60" length
<input type="checkbox"/>	CSSL54-60 P	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 60" length, bagged
<input type="checkbox"/>	CSSL54-72	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 72" length
<input type="checkbox"/>	CSSL54-72 P	1/4" ID (3/8" OD) with 1/2" FIP x 1/2" MIP fittings x 72" length, bagged
<input type="checkbox"/>	CSSL57-12	1/4" ID (3/8" OD) with 1/2" FIP x 3/8" MIP fittings x 12" length
<input type="checkbox"/>	CSSL57-18	1/4" ID (3/8" OD) with 1/2" FIP x 3/8" MIP fittings x 18" length
<input type="checkbox"/>	CSSL57-24	1/4" ID (3/8" OD) with 1/2" FIP x 3/8" MIP fittings x 24" length
<input type="checkbox"/>	CSSL57-30	1/4" ID (3/8" OD) with 1/2" FIP x 3/8" MIP fittings x 30" length
<input type="checkbox"/>	CSSL57-36	1/4" ID (3/8" OD) with 1/2" FIP x 3/8" MIP fittings x 36" length
<input type="checkbox"/>	CSSL57-36 P	1/4" ID (3/8" OD) with 1/2" FIP x 3/8" MIP fittings x 36" length, bagged
<input type="checkbox"/>	CSSL57-48	1/4" ID (3/8" OD) with 1/2" FIP x 3/8" MIP fittings x 48" length
<input type="checkbox"/>	CSSL57-60	1/4" ID (3/8" OD) with 1/2" FIP x 3/8" MIP fittings x 60" length
<input type="checkbox"/>	CSSL87-12	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 12" length
<input type="checkbox"/>	CSSL87-18	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 18" length
<input type="checkbox"/>	CSSL87-18 P	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 18" length, bagged
<input type="checkbox"/>	CSSL87-24	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 24" length
<input type="checkbox"/>	CSSL87-24 P	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 24" length, bagged
<input type="checkbox"/>	CSSL87-24 X10	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 24" length, bagged, cut case of 10
<input type="checkbox"/>	CSSL87-30	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 30" length
<input type="checkbox"/>	CSSL87-36	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 36" length
<input type="checkbox"/>	CSSL87-36 P	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 36" length, bagged
<input type="checkbox"/>	CSSL87-36 X	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 48" length, bagged, cut case
<input type="checkbox"/>	CSSL87-48	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 48" length
<input type="checkbox"/>	CSSL87-48 P	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 48" length, bagged
<input type="checkbox"/>	CSSL87-60	1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 60" length

*This specification and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This specification must be returned to BrassCraft if requested.*



# CSSL 1/4" ID (3/8" OD) Coated Gas Appliance Connectors

## Connectors with Fittings (con't)

- CSSL87-60 P 1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 60" length, bagged
- CSSL87-72 P 1/4" ID (3/8" OD) with 3/8" FIP x 3/8" MIP fittings x 72" length, bagged

## Connectors with Fitting & Gas Ball Valve

- CSSL4M-12 1/4" ID (3/8" OD) with 1/2" MIP fitting x 1/2" FIP ball valve x 12" length
- CSSL4M-18 1/4" ID (3/8" OD) with 1/2" MIP fitting x 1/2" FIP ball valve x 18" length
- CSSL4M-24 1/4" ID (3/8" OD) with 1/2" MIP fitting x 1/2" FIP ball valve x 24" length
- CSSL4M-30 1/4" ID (3/8" OD) with 1/2" MIP fitting x 1/2" FIP ball valve x 30" length
- CSSL4M-36 1/4" ID (3/8" OD) with 1/2" MIP fitting x 1/2" FIP ball valve x 36" length
- CSSL4M-48 1/4" ID (3/8" OD) with 1/2" MIP fitting x 1/2" FIP ball valve x 48" length
- CSSL4M-60 1/4" ID (3/8" OD) with 1/2" MIP fitting x 1/2" FIP ball valve x 60" length
- CSSL4M-72 1/4" ID (3/8" OD) with 1/2" MIP fitting x 1/2" FIP ball valve x 72" length
- CSSL7M-12 1/4" ID (3/8" OD) with 3/8" MIP fitting x 1/2" FIP ball valve x 12" length
- CSSL7M-18 1/4" ID (3/8" OD) with 3/8" MIP fitting x 1/2" FIP ball valve x 18" length
- CSSL7M-24 1/4" ID (3/8" OD) with 3/8" MIP fitting x 1/2" FIP ball valve x 24" length
- CSSL7M-30 1/4" ID (3/8" OD) with 3/8" MIP fitting x 1/2" FIP ball valve x 30" length
- CSSL7M-36 1/4" ID (3/8" OD) with 3/8" MIP fitting x 1/2" FIP ball valve x 36" length
- CSSL7M-48 1/4" ID (3/8" OD) with 3/8" MIP fitting x 1/2" FIP ball valve x 48" length
- CSSL5M-36 1/4" ID (3/8" OD) with 1/2" FIP fitting x 1/2" FIP ball valve x 36" length
- CSSL8M-12 1/4" ID (3/8" OD) with 3/8" FIP fitting x 1/2" FIP ball valve x 12" length
- CSSL8M-18 1/4" ID (3/8" OD) with 3/8" FIP fitting x 1/2" FIP ball valve x 18" length
- CSSL8M-24 1/4" ID (3/8" OD) with 3/8" FIP fitting x 1/2" FIP ball valve x 24" length
- CSSL8M-36 1/4" ID (3/8" OD) with 3/8" FIP fitting x 1/2" FIP ball valve x 36" length
- CSSL8M-48 1/4" ID (3/8" OD) with 3/8" FIP fitting x 1/2" FIP ball valve x 48" length
- CSSL8M-48 P 1/4" ID (3/8" OD) with 3/8" FIP fitting x 1/2" FIP ball valve x 48" length, bagged

## Connectors Less Fittings (Connectors without fittings are NOT CSA design-certified)

- CSSLNN-10N 1/4" ID (3/8" OD) x 10" length, no fittings
- CSSLNN-16N 1/4" ID (3/8" OD) x 16" length, no fittings
- CSSLNN-22N 1/4" ID (3/8" OD) x 22" length, no fittings
- CSSLNN-28N 1/4" ID (3/8" OD) x 28" length, no fittings
- CSSLNN-34N 1/4" ID (3/8" OD) x 34" length, no fittings
- CSSLNN-46N 1/4" ID (3/8" OD) x 46" length, no fittings
- CSSLNN-58N 1/4" ID (3/8" OD) x 58" length, no fittings
- CSSLNN-70N 1/4" ID (3/8" OD) x 70" length, no fittings

## Listings & Certifications:

- CSA listed to ANSI Z21.24 / CSA 6.10 standard "Connectors for Gas Appliances" (file #204593)
- CSA listed to ANSI Z21.75 / CSA 6.27 standard "Connectors for Outdoor Gas Appliances & Manufactured Homes" (file #204593)
- The Commonwealth of Massachusetts



*This specification and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This specification must be returned to BrassCraft if requested.*

