


For Residential and Commercial Applications

Job Name		Engineer / Architect	
Job Location		Wholesaler	
Submittal Date		Contractor	

TK30RB21 Tankless Water Heater Service Valve Kit

Use: For use in potable water distribution systems for water flow control. Valves connect directly to cold water inlet and hot water outlet of the tankless water heater. Use for appliance maintenance and emergency shut-off.

Design Features:

- **Compact design** ideal for recessed and cover box installations
- **Captive coupling nut & washer** reduces opportunity for component loss making installation easier
- **Captive washer** won't kink or tear during installation
- **Forged, one-piece construction** reduces the potential for pinhole leaks
- **Integrated drain valve** with independent, 1/4 turn operation allows quick system diagnostic testing and maintenance
- **Built-in side port** for the pressure relief valve reduces the number of connections & simplifies the installation
- **Right-sized handles**, color-coded for immediate system identification. Perfect for tight installations
-  **No Lead**

Operating Specifications:

Temperature: 40° - 180° F

Pressure: 125 PSI maximum

No-Lead Product

MATERIAL SPECIFICATIONS	
Valve Body	No-Lead forged brass
Stem	No-Lead brass
Handle	Aluminum, coated
Handle Screw	Zinc-plated steel
Flat Seal	Rubber
Coupling Nut	Forged brass
Drain Cap	Forged brass
Cap Gasket	Rubber
Seat	PTFE
Ball	No-Lead brass, chrome plated

No-Lead Part Listing:

- ☐ TK30RB21-18G3X 3/4" IPS x 3/4" IPS hot/cold service valve kit, 18" gas connector, 3/4" full-port gas ball valve, and PR valve
- ☐ TK30RB21-24G3X 3/4" IPS x 3/4" IPS hot/cold service valve kit, 24" gas connector, 3/4" full-port gas ball valve, and PR valve

Listings and Certifications:

- CSA verified to WOG 600 rating
- IAPMO listed to NSF/ANSI 61 (File # N-5427) and IGC 157 (File # 5427)
- No-Lead product manufactured in compliance with section 116875 of the California Health & Safety Code. IAPMO file #6242



This specification and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft Mfg. This specification must be returned to BrassCraft Mfg. if requested.

