For Residential and Commercial Applications

Job Name	Engineer / Architect	
Job Location	Wholesaler	
Submittal Date	Contractor	

V1-**KC Speedi Plumb® Vinyl Faucet Connectors - Compression Inlet x KC Nosepiece Outlet

Use: For use in potable water distribution systems in accessible locations only

Design Features:

- No kink hose. The specially engineered reinforced PVC hose provides unique flexibility to prevent kinking and crimping
- Greater strength and durability with a tighter weave and two-layer bonded construction, outperforms conventional vinyl connectors
- Longer wing nuts ease installation for speedier connections
- Rubber washers provide a large pliable sealing surface and ensures a long lasting water tight connection
- 8-sided pneumatic crimp provides greater dependability for reliable nut-to-hose connections



Operating Specifications:

Temperature: 40°- 140° F, intermittent to 180° F

Pressure: 125 PSI maximum


Tubing Diameter: 0.300" I.D. (0.500" O.D.)

AACHINED AND		
IEO, MARINE STATE OF THE STATE		
SIGNE		
W THE USA		
A LHE OS.		

MATERIAL SPECIFICATIONS			
Hose	PVC with polyester braid reinforcement		
Barb	Compliant brass		
Ferrule	Zinc plated 1008 steel		
Nut	C36000 brass, chrome plated		
Washer	Rubber		
Compression Nut & Ring	C36000 brass, (nut) chrome plated		


Part Listing:

Ш	V1-12KC F	3/8 compression x 3/8 compression x 12 length
	V1-20KC F	3/8" compression x 3/8" compression x 20" length



BrassCro

V1-**KC Speedi Plumb® Vinyl Faucet Connectors - Compression Inlet x KC Nosepiece Outlet



PART DIMENSIONS (Inches)			
Model	DIM. A		
V1-12KC	12.0 / 13.0		
V1-20KC	20.0 / 21.0		

Listings & Certifications:

- IAPMO listed to ASME A112.18.6-2003 (File # 0452)
- CSA listed to ASME A112.18.6-2003 / CSA B125 (File # 204593)
- CSA approved to California Health & Safety Code and Vermont Bill S.152 (Project # 2174785)





