



## PRODUCT SPECIFICATIONS

Pipe Type	PVC, Schedule 40 & 80
Cement Uses:	For PVC pipe and fitting applications; potable water, pressure, non-pressure, conduit, drain, DWV, and sewer
Maximum Diameter	For PVC pipe sizes thru 6" (150mm) all schedules and classes. Schedule 80 thru 4" (100mm)
Color	Deep Blue
Relative Set Time	Very Fast Set
Body	Medium Body
Performance Specification	ASTM D-2564, NSF/ANSI 14, NSF/ANSI 61, NSF/ANSI 372
Brookfield Viscosity	Minimum 500 cP @73°F +/- 2°F 23°C +/- 1°C
Specific Gravity	Typical 0.955 +/- 0.04
Industry Listing	
Max VOC Emissions	600 g/l per SCAQMD Rule 1168 Method 316A
Shelf Life	3 Years

## RED HOT BLUE GLUE®

### The "Hottest" solvent formula on the market

Christy's Red Hot Blue Glue® is a very aggressive, deep blue, medium bodied, very fast setting PVC solvent cement. Christy's Red Hot Blue Glue® is the industry's highest quality Blue Glue, from the leading producer of high performance solvent cements. For use in plumbing, industrial, irrigation, agricultural, municipal, or pool and spa applications including PVC foam core.

- **Contractor Preferred... "The Original" Blue Glue that quickly bonds PVC pipe & fittings for fast pressurization and maximum productivity**
- **The industry's highest quality "Blue Glue" - Premium formulation designed to bond in wet, dry, and humid conditions**
- **Industry's fastest acting solvent cement with the most active ingredients**
- **Can be used without a primer for non-pressure system up to 6" (150mm) and pressure systems below 4" (100mm), if local codes permit**
- **For PVC pipe and fitting applications; potable water, pressure, non-pressure, conduit, drain, duct, DWV and sewer**

## CASE PACK CONFIGURATIONS

Item #	Can Size	Cans/Cs	Can UPC
RH-RHBG-QP-48	¼ Pint, 4 oz (118 ml)	48	044752100045
RH-RHBG-HP-36	½ Pint, 8 oz (237 ml)	36	044752100083
RH-RHBG-PT-24	Pint, 16 oz (473 ml)	24	044752100168
RH-RHBG-QT-12	Quart, 32 oz (946 ml)	12	044752100328
RH-RHBG-GL-6	Gallon, 128 oz (3.785 l)	6	044752101288

**SPECIAL CONSIDERATIONS:** Consult the SDS for health and safety specifics. Always use in a well-ventilated environment. Wear safety glasses and gloves at all times. **DO NOT USE** a dry granular calcium hypochlorite as a disinfecting material for water purification in potable water piping systems. The introduction of granules or pellets of calcium hypochlorite with PVC and CPVC solvent cements and primers (including their vapors) may result in a violent chemical reaction if a water solution is not used. It is advisable to purify lines by pumping chlorinated water into the piping system - this solution will be non-volatile. Furthermore, dry granular calcium hypochlorite should not be stored or used near solvent cements and primers.

**THIS PRODUCT IS NOT FOR USE IN A SYSTEM USING OR  
BEING TESTED WITH COMPRESSED AIR OR GASSES.**

T. Christy Enterprises, Inc.



655 E. Ball Rd. • Anaheim, CA 92805

Tel: (714) 507-3300 • Fax: (714) 507-3310

www.TChristy.com • 800-BLU-GLUE