

GASKET JOINT PSM SEWER PIPE SDR-35 ASTM D3034	SIZE	O.D.	MIN. WALL	WEIGHT PER 100'	FEET PER PALLET	PALLETS PER T.L.	LGTH.	PART NO.
	4"	4.215	.120	109.04	1260	18	14'	53726
			108.05	1200	16	20	53735	
	6	6.275	.180	244.06	490	18	14	53786
			241.84	700	12	20	53795	
	8	8.400	.240	438.52	280	18	14	53806
			433.62	400	12	20	53815	
	10	10.500	.300	685.91	168	18	14	53826
	12	12.500	.360	980.09	112	24	14	53836

GASKET JOINT PSM SEWER PIPE SDR-26 ASTM D3034	4"	4.215	.162	145.64	1260	18	14'	53506
	6	6.275	.241	323.01	490	18	14	53526
	8	8.400	.323	583.79	280	18	14	53550
	10	10.500	.404	913.21	168	18	14	53531
	12	12.500	.481	1290.43	112	24	14	53541

14' & 20' LAYING LENGTHS. INSERTION DEPTH RING IS MARKED ON THE SPIGOT END OF PIPE.  
GASKET JOINT PIPE IS PRODUCED WITH AN INTEGRAL BELL END WITH A REINFORCED GASKET CONFORMING TO ASTM F477.

SOLVENT WELD PSM SEWER PIPE SDR-35 ASTM D3034	4"	4.215	.120	105.74	900	24	10'	53115
					1200	16	20	53118
	6	6.275	.180	236.66	350	24	10	53180
					700	12	20	53183
8	8.400	.240	422.19	200	16	10	53250	

SOLVENT WELD PSM SEWER PIPE SDR-26 ASTM D3034	4"	4.215	.162	141.23	900	24	10'	53416
					1200	16	20	53425
	6	6.275	.241	313.22	350	18	10	53455

PERFORATED SOLVENT WELD PSM SEWER PIPE IS AVAILABLE.



CRESLINE PLASTIC PIPE CO., INC.

[www.cresline.com](http://www.cresline.com)

600 Cross Pointe Blvd.  
264 Silver Spring Rd.  
2100 South 35th St.  
3801 East Hwy. 31

Evansville, IN 47715  
Mechanicsburg, PA 17050  
Council Bluffs, IA 51501  
Corsicana, TX 75109

812-428-9350  
717-766-2566  
712-322-2294  
903-872-8475

Fax 812-428-9353  
Fax 717-697-2371  
Fax 712-322-6673  
Fax 903-872-7732