

ACCESS FITTINGS

A convenient low-cost port for refrigeration servicing. May be installed in any position on either high or low side for charging, purging, quick testing or pressure checking. DiversiTech's access fittings have 1/4" SAE male flare access ports and include a quick seal cap and a stainless and brass special refrigerant valve core.

| CATALOG NO. | DESCRIPTION | CONNECTION | QTY PER PACK | UOM | ORDER MULT. |
|-----------------|---|--|--------------|-----|-------------|
| VA-3-346 | 3 Way Solder Type, pack of 6 | For 3/16" O.D. tube or 1/4" and 3/8" solder fitting | 6 | PK | 1 |
| VA-34 | Straight Solder Type, pack of 6 | 3/16" O.D.S. x 1/4" O.D.F. | 6 | PK | 1 |
| VA-46 | Straight Solder Type, pack of 6 | 1/4" O.D.S. x 3/8" O.D.F. | 6 | PK | 1 |
| VA-68 | Straight Solder Type, pack of 6 | 3/8" O.D.S. x 1/2" O.D.F. | 6 | PK | 1 |
| VAU-24 | Half Union, pack of 6 | 1/8" MPT | 6 | PK | 1 |
| VAU-45 | Half Union, pack of 6 | 1/4" MPT | 6 | PK | 1 |
| VAX-2 | Extended Copper Tube | 1/8" O.D. tube | 6 | PK | 1 |
| VAX-3 | Extended Copper Tube | 3/16" O.D. x 1/8" I.D. | 6 | PK | 1 |
| VAX-4 | Extended Copper Tube | 1/4" O.D. x 3/16" I.D. | 6 | PK | 1 |
| VAX-5 | Extended Copper Tube | 5/16" O.D. x 1/4" I.D. | 3 | PK | 1 |
| VAX-6 | Extended Copper Tube | 3/8" O.D. x 5/16" I.D. | 3 | PK | 1 |
| VAX-8 | Extended Copper Tube | 1/2" O.D. | 3 | PK | 1 |
| VS-4 | Swivel Nut w/Depressor, pack of 6 | 1/4" female flare forged swivel nut | 6 | PK | 1 |
| VST-4 | Swivel Tee w/Permanent Depressor, pack of 3 | 1/4" Access on run x 1/4" female flare w/depressor on female swivel branch end | 3 | PK | 1 |
| VST-44 | Swivel Tee w/Perm. Depressor, pack of 3 | 1/4" Access on run x 1/4" access on "T" - female swivel on run | 3 | PK | 1 |
| VTR-24 | Threaded Tee, pack of 3 | 1/8" MPT x 1/4" male flare on run x access on branch | 3 | PK | 1 |
| VTS-10 | Solder Tee Type | 5/8" O.D. tube | 1 | EA | 1 |
| VTS-12 | Solder Tee Type | 3/4" O.D. tube | 1 | EA | 1 |
| VTS-14 | Solder Tee Type | 7/8" O.D. tube | 1 | EA | 1 |
| VTS-46 | Solder Tee Type, pack of 3 | 1/4" O.D.S. x 5/16" O.D.F. | 3 | PK | 1 |
| VTS-56 | Solder Tee Type, pack of 3 | 5/16" O.D.S. x 3/8" O.D.F. | 3 | PK | 1 |
| VTS-68 | Solder Tee Type, pack of 3 | 3/8" O.D.S. | 3 | PK | 1 |
| VTS-810 | Solder Tee Type, pack of 3 | 1/2" O.D.S. | 3 | PK | 1 |
| VTS-3-12 | Solder Tube Elbow | 3/4" O.D.S. | 1 | EA | 1 |
| VTS-3-14 | Solder Tube Elbow | 7/8" O.D.S. | 1 | EA | 1 |
| VC-4 | Flare Cap, pack of 12 | 1/4" | 12 | PK | 1 |
| VC-4R | Flare Cap w/Core Remover, pack of 12 | 1/4" | 12 | PK | 1 |
| VVC-1 | Valve Core, pack of 6 | | 6 | PK | 1 |



Brass Adapters

The MSA-45 is used on the new R410 Mini Split systems that have the larger unique fitting on the service valve. The description of that fitting is 1/2" acme Male-20 UN. This adapter will screw onto the 1/2" Acme Male-20 UN fitting and allow you to connect a standard 1/4 service hose to it.



| CATALOG NO. | DESCRIPTION | UOM | ORDER MULTIPLE |
|---------------|---|-----|----------------|
| MSA-45 | 1/4" Male flare x 1/2" - 20 UNF Female | EA | 1 |
| MSA-44 | 1/4" Female flare swivel w/depressor tip and seal x 1/4" MPT, pack of 2 | PK | 1 |

Cop-Cap™ Locking Valve Cover

An effective way to discourage and prevent the removal of refrigerant. COP-CAP™ fits this standard service valve on all central AC units and mini-splits. It helps prevent access by unauthorized persons and can only be removed with the included special tool. Simply thread COP-CAP™ assembly onto existing 1/4" flare connection on system and lock set screw in place with hex wrench provided.



- Seals service valve to prevent leaks
- Prevents illegal venting or theft of refrigerant
- Stops unauthorized access in unsecured areas

| CATALOG NO. | DESCRIPTION | UOM | ORDER MULTIPLE |
|---------------|-----------------------------|-----|----------------|
| VCC-4 | Cop-Cap™, Pack of 2 | PK | 1 |
| VCC-4B | Cop-Cap™ bulk, 100 per case | EA | 100 |