


Range & dryer power receptacles

Product description

3-pole, 4-wire grounding
 30A, 125/250V/AC
 50A, 125/250V/AC



1212



58

Surface power receptacles



| Rating A | V/AC | NEMA | Description | Color | Catalog no. | | |
|-------------|---------|--------|---------------------------------------------------------|-------|-------------|---|---|
| 30 | 125/250 | 14-30R | Surface mount dryer power receptacle, matching plug S21 | BK | □ 1225 | • | • |
| 50 | 125/250 | 14-50R | Surface mount range power receptacle, matching plug S21 | BK | □ 1212 | • | • |

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

Panel power receptacles



| Rating A | V/AC | NEMA | Description | Color | Catalog no. | | |
|-------------|---------|--------|-------------------------------------------------------|-------|-------------|---|---|
| 50 | 125/250 | 14-50R | Panel mount range power receptacle, matching plug S21 | BK | □ 58 | • | • |

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

Compatible wallplates / standard size for flush power receptacles



| Description | Color suffix | Catalog no. | | |
|-----------------------------------------------------------|-----------------|-------------|---|---|
| Thermoset 1-Gang wallplate for one power receptacle | A, B, V, W | □ 2068__ | • | • |
| Thermoset 2-Gang wallplate for one power receptacle | A, B, LA, V, W | □ 2168__ | • | • |
| Nylon 1-Gang wallplate for one power receptacle | V | □ 5068 | • | • |
| Polycarbonate 1-Gang wallplate of one power receptacle | B, BK, V, W | □ PJ724__ | • | • |
| Polycarbonate 2-Gang wallplate for one power receptacle | B, V, W | □ PJ703__ | • | • |
| Stainless steel 1-Gang wallplate for one power receptacle | Stainless Steel | □ 93221* | • | • |
| Stainless steel 2-Gang wallplate for one power receptacle | Stainless Steel | □ 93227* | • | • |

Listed to UL498, file no. E15058; *CSA certified to C22.2, no. 42

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), LA (Light Almond), V (Ivory), Stainless Steel, W (White)



Dimensional information: B-70 **Specification information:** Please visit www.eaton.com/wiringdevices

Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page G-21

RoHS compliant - Page G-21