Plugs & connectors



Heavy duty grade armored vinyl plugs & connectors

Product description

2-pole, 3-wire grounding 15A, 125V/AC 20A, 125V/AC



Design features

- Armored housing resists abuse and is automatically grounded
- · Solid brass plug blades are firmly embedded
- · Terminals in individual chambers to positively insulate conductors



- Terminal screw clamps are designed to contain wire and prevent binding
- Combination Slot/Phillips head mounting and terminal screws for installation flexibility (Slot/ Robertson screws in Canada where available)



2867



Armored vinyl plugs & connectors






| Ra | ting | | | | Plug | Connector | |
|----|------|--------------------------|-------------------------|-------|-------------|-------------|------------|
| Α | V/AC | Description | Cord diameter | Color | catalog no. | catalog no. | 4 2 |
| 15 | 125 | NEMA 5-15, straight body | 0.25-0.63" (6.4-16.0mm) | Υ | □ 2867 | □ 2887 | • • |
| 20 | 125 | NEMA 5-20, straight body | 0.25-0.63" (6.4-16.0mm) | Υ | □ 2809 | □ 2228 | • • |

Listed to UL498, file no. E15012; CSA certified to C22.2, no. 42; NOM certified

Heavy duty grade armored vinyl plugs & connectors

Product description

2-pole, 3-wire grounding 15A, 250V/AC 20A, 250V/AC



Design features

- Armored housing resists abuse and is automatically grounded
- · Solid brass plug blades are firmly embedded in body
- Terminals in individual chambers to positively insulate conductors
- Terminal screws backed out and ready for wiring
- Terminal screw clamps are designed to contain wire and prevent binding
- Combination Slot/Phillips-head mounting and terminal screws for installation flexibility (Slot/ Robertson screws in Canada where available)

Armored vinyl plugs & connectors





| Ra A | ting V/AC | Description | Cord diameter | Color | Plug catalog no. | Connector catalog no. | A Rosis |
|---------|--------------|--------------------------|-------------------------|-------|---------------------|-----------------------|---------|
| 15 | 250 | NEMA 6-15, straight body | 0.25-0.63" (6.4-16.0mm) | Υ | □ 2866 | □ 2227 | • • |
| 20 | 250 | NEMA 6-20, straight body | 0.25-0.63" (6.4-16.0mm) | Υ | □ 3809 | □ 2229 | • • |

Listed to UL498, file no. E15012; CSA certified to C22.2, no. 42; NOM certified

Color ordering information:

Y (Yellow)



Dimensional information: B-70 Specification information: Please visit www.eaton.com/wiringdevices Compliances, specifications and availability are subject to change without notice.



Indicates NAFTA compliant - Page G-21



RoHS compliant - Page G-21