

806 Small Diameter Series

APOLLOXPRESS® Press End Copper Elbow 45° CxC (1/2" through 2")



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO Number:	
Representative:	
Wholesale Distributor:	







DESCRIPTION

The APOLLOXPRESS® 806 Small Diameter Press Elbow features a Lead-Free dezincification resistant copper body and an EPDM O-Ring. Our Small Diameter APOLLOXPRESS® products are manufactured utilizing proven ASTM materials and standards. Proudly Made In The USA.

FEATURES

- Lead-Free Construction
- Leak-Before-Press Technology
- Compatible with Pro-Press™ Pressing Tools
- Approved for underground installation (per local installation code)
- Use with hard/soft ASTM B88 K, L & M Copper Tube
- Made in USA
- cUPC® Compliant
- ARRA Compliant

PERFORMANCE RATING

- Maximum Pressure: 200 psi
- Temperature Range: o°F to 250°F depending on application. Hot Water up to 250°F, Chilled Water down to 33°F

APPROVALS

- NSF/ANSI NSF 61 ~ Water Quality
- NSF/ANSI NSF-372 ~ Lead Free (LF)
- IAPMO File Listings: 4861, 6174 & N-4951

APOLLOXPRESS

- Small Diameter Sizes 1/2" through 2"
- Model 806, 45° Elbow C x C

STANDARD MATERIALS

Part Name	Material					
Body	UNS C12200 Copper					
O-Ring	EPDM					
Lubrication	Silicone, ANSI/NSF-61 Listed					


DIMENSIONS


		Dimension (in.)									(lb.)
Item No.	Description	Α	В	C*	D**	E*	F**	Height	Width	Depth	Weight
10075060	806 ½ CxC	2.14	1.52	0.78	0.32	0.78	0.32	1.52	2.01	0.95	0.10
10075062	806 ¾ CxC	2.62	1.91	0.92	0.41	0.92	0.41	1.91	2.62	1.24	0.16
10075064	806 1 CxC	3.10	2.28	0.97	0.59	0.97	0.59	2.28	3.10	1.49	0.24
10075090	806 1¼ CxC	3.62	2.69	1.09	0.72	1.09	0.72	2.69	3.62	1.75	0.34
10075092	806 1½ CxC	4.20	3.16	1.31	0.78	1.31	0.78	3.16	4.20	2.09	0.59
10075094	806 2 CxC	5.12	3.88	1.51	1.02	1.51	1.02	3.88	5.12	2.60	0.83

^{*} Tolerance +/- .045"

Elkhart Products Corporation

1255 Oak Street, Elkhart, IN 46514 www.elkhartproducts.com | (574) 264-3181







^{**} Tolerance +.09 / -.03