

SUBMITTAL SHEET

818 Small Diameter Series

APOLLOXPRESS® Press End Copper Reducer
FTGxC (3/4" x 1/2" through 2" x 1 1/2")



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO Number:	
Representative:	
Wholesale Distributor:	



DESCRIPTION

The APOLLOXPRESS® 818 Small Diameter Press Reducer features a Lead-Free dezincification resistant copper body and an EPDM O-Ring. Our Small Diameter APOLLOXPRESS® products are manufactured utilizing proven ASTM materials and standards. Proudly Made In The USA.

FEATURES

- Lead-Free Construction
- Leak-Before-Press Technology
- Compatible with Pro-Press™ Pressing Tools
- Approved for underground installation (per local installation code)
- Use with hard/soft ASTM B88 K, L & M Copper Tube
- Made in USA
- cUPC® Compliant
- ARRA Compliant

PERFORMANCE RATING

- Maximum Pressure: 200 psi
- Temperature Range: 0°F to 250°F depending on application. Hot Water up to 250°F, Chilled Water down to 33°F

APPROVALS

- NSF/ANSI NSF 61 – Water Quality
- NSF/ANSI NSF-372 – Lead Free (LF)
- IAPMO File Listings: 4861, 6174 & N-4951

APOLLOXPRESS


- Small Diameter Sizes 3/4" x 1/2" through 2" x 1 1/2"

STANDARD MATERIALS

Part Name	Material
Body	UNS C12200 Copper
O-Ring	EPDM
Lubrication	Silicone, ANSI/NSF-61 Listed

DIMENSIONS

Item No.	Description	Dimension (in.)								(lb.)
		A	B	C*	D**	E***	Height	Width	Depth	
10075146	818 3/4x1/2 FTGxC	2.07	0.95	0.86	1.22	0.98	0.95	2.03	0.95	0.08
10075150	818 1x1/2 FTGxC	2.37	1.25	0.81	1.56	1.10	1.25	2.37	1.25	0.10
10075148	818 1x3/4 FTGxC	2.22	1.25	0.85	1.37	1.10	1.25	2.22	1.25	0.12
10075336	818 1 1/4x1/2 FTGxC	2.83	1.38	0.85	1.98	1.27	1.38	2.83	1.38	0.18
10075154	818 1 1/4x3/4 FTGxC	2.69	1.38	0.85	1.84	1.34	1.38	2.69	1.38	0.16
10075156	818 1 1/4x1 FTGxC	2.40	1.50	0.91	1.48	1.23	1.50	2.40	1.50	0.20
10075332	818 1 1/2x1/2 FTGxC	3.19	1.63	0.81	2.38	1.43	1.63	3.19	1.63	0.31
10075334	818 1 1/2x3/4 FTGxC	3.22	1.63	0.89	2.33	1.55	1.63	3.22	1.63	0.25
10075158	818 1 1/2x1 FTGxC	2.93	1.63	0.93	2.00	1.53	1.63	2.93	1.63	0.28
10075160	818 1 1/2x1 1/4 FTGxC	2.69	1.75	1.04	1.65	1.31	1.75	2.69	1.75	0.26
10075338	818 2x1/2 FTGxC	4.04	2.13	0.85	3.19	1.83	2.13	4.04	2.13	0.34
10075162	818 2x1 FTGxC	3.66	2.13	0.97	2.69	1.83	2.13	3.66	2.13	0.49
10075152	818 2x1 1/4 FTGxC	3.34	2.13	1.04	2.30	1.60	2.13	3.34	2.13	0.41
10075164	818 2x1 1/2 FTGxC	3.51	2.13	1.31	2.20	1.77	2.13	3.51	2.13	0.53



Elkhart Products Corporation
1255 Oak Street, Elkhart, IN 46514
www.elkhartproducts.com | (574) 264-3181

* Tolerance +/- .045"
** Tolerance +.09 / -.03
*** Tolerance +.09 / -.00

This specification is provided for reference only. Elkhart Products Corporation reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Elkhart products previously or subsequently sold.

