



Power Vents

Available in both roof and gable mount, power vents may cost more to install than other types of attic vents, but they exhaust the greatest volume of hot and/or humid air from the attic—which in turn can help save more on energy costs.

Power Attic Vents – Roof Mount

All Master Flow® Roof-Mounted Power Attic Vents are factory-tested before shipment and include a heavy-duty insect/animal screen for maximum performance and protection.

- **Energy Efficient...** PSC (permanent split capacitor) motor provides maximum operating efficiency
- **Available In Popular Colors...** To blend in with the finished roof (see color chart on page 11)
- **Adjustable Thermostat...** Included on all models for superior operation
- **Adjustable Humidistat/Thermostat Available...** On PR2DHT and PR3DHT models only
- **Extra-Long Conduit Available...** For easier electrical hook-up (PR3 model only)



PR3DSMWWHT with adjustable humidistat/thermostat shown



Texas Department of Insurance Product Evaluation RV-37 & 38

Florida Building Code FL5027

Power Attic Vents–Gable Mount

Master Flow® Gable-Mounted Power Attic Vents are the easiest power ventilators to install and won't detract from the look of the finished roof. They're factory-tested prior to shipment and are manufactured with 100% rust-resistant metal construction.

- **Energy Efficient...** PSC (permanent split capacitor) motor provides maximum operating efficiency
- **Adjustable Thermostat Included On All Models...** For superior operation
- **Extra-Long Conduit...** For easier electrical hook-up (on PG3 model only)



Power Attic Vent Accessories

Power Attic Vent Automatic Shutter – Gable Mount SGM 20

- **Versatile...** Use with all power gable vents
- **Automatic...** Moving air opens the louvers only when the power vent is operating
- **Weather-Resistant...** When vent is off, shutter helps prevent infiltration of rain, snow, insects, etc.
- **Maintenance-Free...** White aluminum construction can be painted if desired



Opening Dimensions
16 1/2" x 16 1/2"

Overall Dimensions
19 1/4" x 19 1/4"

Humidistat (Model H1)

- Fully adjustable for all climate conditions
- Can be used with all Master Flow® & previous LL Building Products Inc. Power Vents
- Helps power ventilator reduce damaging attic moisture



Humidistat/Thermostat (Model HT1)

- Fully adjustable for all climate conditions
- Can be used with all Master Flow® & previous LL Building Products Inc. Power Vents
- Helps power vents reduce damaging attic heat & moisture



Replacement Thermostat (Model PT6)

- Automatic and adjustable
- Compatible with all single-speed Master Flow® & previous LL Building Products Inc. Power Vents
- UL listed



Replacement Motors (not shown)

- **Model PVM105** – Replaces motor for the following models: PG1, CPG2 (available in Canada only), PG2, PR1, CPR1D, PR1D, CPR2D, PR2D & PR2DHT
- **Model PVM115** – Replacement motor for the following models: PSG3, PSG3HT, PG3X, PSR10D, PSR10DHT, PR3XD & PRX3DH

PRODUCT SPECIFICATIONS

Choose The Right Master Flow® Power Attic Vent–Roof Mount

	PR - Roof Mount Series			ERV - Roof Mount Series		
	PR1D, CPR1D ¹	PR2D, CPR2D ¹ , PR2DHT ¹	PR3XD, PR3DHT ¹	CERV4 ¹ , ERV4	CERV5 ¹ , ERV5	ERV6
For Maximum Attic Size (sq. ft. @ 4:12 roof pitch)	1,600	2,400	3,200	1,600	2,200	2,800
Air Flow (cubic feet per minute)	1,000	1,250	1,600	1,000	1,250	1,500
Minimum Intake Ventilation Needed at Soffits/Undereave or Fascia (net free area in sq. in.)	480	600	768	480	600	720
Adjustable Thermostat Included	Yes	Yes	Yes	Yes	Yes	Yes
Optional Adjustable Humidistat/Thermostat Available	–	Yes	Yes	–	–	–
Length of Ltd. Warranty**	5	5	10	5	5	10
Length of Labor Protection Plus plan**	2	3	5	2	3	5

Power Attic Vent–Roof Mount Color Availability

Mill	Black	Brown	Weathered Wood	Shingle Match™ Weathered Wood
PR1D, ERV4	PR1DBL, ERV4BL	PR1DBR, ERV4BR	PR1DWW, CPR1DWW ¹ , ERV4WW, CERV4WW ¹	–
PR2D, ERV5	PR2DBL, ERV5BL	PR2DBR, ERV5BR	PR2DWW, CPR2DWW ¹ , ERV5WW, CERV5WW ¹	–
PR2DHT ¹	PR2DBLHT ¹	PR2DBRHT ¹	PR2DWWHT ¹	–
–	–	–	–	PR3XDSMWW, ERV6SMWW
–	–	–	–	PR3DSMWWHT ¹

Choose The Right Master Flow® Power Attic Vent–Gable Mount

	PG - Gable Mount Series		EGV - Gable Mount Series	
	CPG2 ¹ , PG2	PG3	CEGV5 ¹ , EGV5	EGV6
For Maximum Attic Size (sq. ft. @ 4:12 roof pitch)	2,400	3,200	2,300	3,000
Air Flow (cubic feet per minute)	1,540	1,600	1,450	1,600
Minimum Intake Ventilation Needed at Soffits/Undereave or Fascia (net free area in sq. in.)	740	768	696	768
Adjustable Thermostat Included	Yes	Yes	Yes	Yes
Length of Ltd. Warranty**	5	10	5	10
Length of Labor Protection Plus plan**	3 Yrs.	5 Yrs.	3 Yrs.	5 Yrs.

¹Adjustable humidistat/thermostat included

²See Master Flow® Powered Ventilation Products Ltd. Warranty for complete coverage and restrictions.

³Available in Canada only

Note: Always have a balanced attic ventilation system. The amount of exhaust ventilation should NEVER exceed the amount of intake ventilation.