



STEP DOWN RUBBER WASHER FOR LAVATORY SUPPLY

- Step Down Slip Joint Washer molded from very high quality rubber that is not affected by oil, steam, etc.
- 3/4" O.D.
- 3/8" I.D.
- 3/8" Height
- Use with #R35 friction rings
- Usage: Lavatory Supply Nuts
- Packed 100 per box
- Full cartons only

| Item No | Std. Pkg | Price / 100 |
|---------|----------|-------------|
| W443 | 100 Ea | |



STEP DOWN RUBBER WASHER FOR CLOSET SUPPLY

- Step Down Slip Joint Washer molded from very high quality rubber that is not affected by oil, steam, etc.
- 13/16" O.D.
- 3/8" I.D.
- 7/16" Height
- Use with #R34 friction rings
- Usage: Ballcock Supply Nuts
- Packed 100 per box
- Full cartons only

| Item No | Std. Pkg | Price / 100 |
|---------|----------|-------------|
| W442 | 100 Ea | |

BRAIDED STAINLESS STEEL CLOSET SUPPLIES W / PLASTIC BALLCOCK NUT



- UPC Approved and Certified to ANSI / NSF 61
- Specially formulated FDA approved PVC compound
- Reinforced with tightly knit external stainless steel braiding
- A quality alternative to inner braided PVC water supplies
- Improved reliability and flexibility that resists kinking
- Brass coupling at the stop
- Plastic Nut at ballcock connection
- Solid brass inserts
- Operating temperature range: 30° F - 180° F
- Maximum pressure range: 1,800 psi @ 70° F
1,250 psi @ 180° F

| Item No | Length | Description | Std. Pkg | Price / Ea |
|---------|--------|-----------------|----------|------------|
| 653SH | 12" | 1/2ips x 7/8 BC | 6 Ea | |
| 653SM | 9" | 3/8cmp x 7/8 BC | 6 Ea | |
| 653SR | 12" | 3/8cmp x 7/8 BC | 6 Ea | |
| 653SS | 20" | 3/8cmp x 7/8 BC | 6 Ea | |
| 653SX | 20" | 1/2cmp x 7/8 BC | 6 Ea | |

BRAIDED STAINLESS STEEL CLOSET SUPPLIES W / BRASS BALLCOCK NUT



- UPC Approved and Certified to ANSI / NSF 61
- Specially formulated FDA approved PVC compound
- Reinforced with tightly knit external stainless steel braiding
- A quality alternative to inner braided PVC water supplies
- Improved reliability and flexibility that resists kinking
- All Brass Nuts, Couplings and Inserts
- Operating temperature range: 30° F - 180° F
- Maximum pressure range: 1,800 psi @ 70° F
1,250 psi @ 180° F

| Item No | Length | Description | Std. Pkg | Price / Ea |
|-----------|--------|--------------------|----------|------------|
| 653SHB | 12" | 1/2ip x 7/8 BR BC | 6 Ea | |
| 653SRB | 12" | 3/8cmp x 7/8 BR BC | 6 Ea | |
| 653SRB-16 | 16" | 3/8cmp x 7/8 BR BC | 6 Ea | |
| 653SSB | 20" | 3/8cmp x 7/8 BR BC | 6 Ea | |
| 653SWB | 12" | 1/2cmp x 7/8 BR BC | 6 Ea | |
| 653SXB | 20" | 1/2cmp x 7/8 BR BC | 6 Ea | |

FLARE ADAPTORS LF



- Adapt Fittings: Compression to Flare

| Item No | Description | Std. Pkg | Price / Ea |
|---------|----------------------------|----------|------------|
| 654A-LF | 3/8 Comp x 3/8 Flare | 12 Ea | |
| 654A-W | Plastic Washer for 654A-LF | 12 Ea | |
| 654B-LF | 3/8 Comp x 1/2 Flare | 12 Ea | |
| 654B-W | Plastic Washer for 654B-LF | 12 Ea | |

PEX CLOSET SUPPLY TUBES



- Cross linked polyethylene (PEX)
- ASTM F876/877, NSF 61, IAPMO listed
- Rated for 100 psi at 180° F

| Item No | Length | Diameter | Std. Pkg | Price / Ea |
|----------|--------|----------|----------|------------|
| 653PX-12 | 12" | 3/8" | 12 Ea | |
| 653PX-20 | 20" | 3/8" | 1 Ea | |



PRODUCTS MEET THE STRICT LEAD-FREE STANDARDS OF THE SAFE DRINKING WATER ACT.