

Accessories

Snake Oil™

Protects your cables better than common lubricants. Its special rust inhibitor cuts through moisture and replaces it with a rust-resistant coating. In addition, Snake-Oil gives your equipment a fresh, clean smell.



Catalog Number	Description
SQO	1 Quart Snake Oil
SQO-12	12 Quarts Snake Oil
SOG	1 Gallon Snake Oil
SOG-4	4 Gallons Snake Oil

GT Cable Guide Tube

Adds safety when you can't get machine close to drain opening. 30" long x 1-1/4" diameter spring.



GTE Guide Tube Extension

Five foot extension attaches to the Cable Guide Tube. Made of 40" conduit with 24" spring end.



MGT Manhole Guide Tube

Supports drain cables in man-holes. Adjusts from 6'2" to 9'4". 4'4" extensions available.



Cables

Flexicore® Cable Wire Rope Center Construction

Heavy-gauge wire coiled tightly around 49-strand aircraft-type wire rope and heat treated. Has unequalled strength and the

right amount of flexibility. So tough it carries a one-year warranty against defect or breakage.

Flexicore Patent Nos. 2,244,735 and 2,849,870



General Flexicore® Cable with Male and Female Connector

Sectional Cables

Sections for Model 88 and Rodrunner come in the all-purpose Flexichain which has a chain center, a stiffer Proflex which has a spring center, and a hollow style. Choose from three coupling styles. They snap together in a second and are taken apart quickly with a spanner wrench or uncoupling key. With the more recently developed "G" connector, no torque is put on the locking pin when running in reverse, making it a durable coupling.



Flexichain® Section



Proflex® Cable



"G" Connector Pat. No. 3094011



"L" Connector



15R10-P Proflex® Cable



SIG

Splash/Impact Goggles

Can be worn over glasses.

QF "Quick Fix" Repair Coupler



Just screw on tightly and it won't come off. For 1/2", 9/16", 5/8", and 3/4" sizes.

FC Butt-Weld Connector



Passes through automatic feeds. No need to adjust feed. For 5/8", and 3/4" sizes.

FC-O Cup Type Connector



Sheath fits over cable for easier repairs. For 5/16", 3/8", 1/2", 5/8" and 3/4" sizes.

RS Repair Sleeve



In 3/8", 1/2", 5/8", and 3/4" sizes.