

Genesis® Series Cable Part Numbers, Packaging and Color Codes

All Genesis® Series Cable products come with an eight digit part number:

- The first four digits represent the product
- The next two digits represent the packaging
- The last two digits represent the color code

For Example:

This is a 500' Pull Box of Black

RG6U 60% AL

5003 = RG6U 60% AL

55 = 500' Pull Box

08 = Black



COLORS

Color Code	Color
00	Clear
01	White
02	Yellow
03	Orange
04	Red
05	Green
06	Blue
07	Brown
08	Black
09	Gray
10	Purple
11	Pink
12	Natural
13	Beige
40	Violet
41	Fluorescent Pink
45	Neon Green
99	Unjacketed
1G	White w/ Green Stripe
1A	White w/ Orange Stripe
1R	White w/Red Stripe
4B	Red w/Blue stripe
4G	Red w/Green Stripe
4K	Red w/Black Stripe
4P	Red w/Purple Stripe
4W	Red w/White Stripe
4Y	Red w/Yellow Stripe
6R	Blue w/Red Stripe
6Y	Blue w/Yellow Stripe

PACKAGING

Packaging Code	Put up
01	250' Reel
03	4 x 250' Reel
05	250' SPEED BOX® Pull Box
09	250' Speed Bag®
10	1000' Reel
11	1000' SPEED BOX® Pull Box
18	1000' Speed Bag®
21	1000' SPEED BOX® Reel-In-A-Box
25	2500' Reel
39	5 x 50' Coil
43	100' Reel
46	125' Speed Bag®
48	4 x 500' Reel
54	500' Reel (1 of 4-pack)
55	500' SPEED BOX® Pull Box
58	500' Speed Bag®
61	500' SPEED BOX® Reel-In-A-Box
86	1000' REACT™ Packaging
87	500' REACT™ Packaging

* See Selection Guide on www.honeywellcable.com for complete list of product options.

Security Cables - Plenum Rated



Construction	
Conductors	Bare Copper
Insulation	Plenum PVC
Shielding	100% Aluminum Foil + Drain
Jacket	Plenum PVC
Ratings/Listings	
Listings	CMP/CL2P/FT6
Voltage (max.)	300V
Temperature (max.)	75° C max

SHIELDED

AWG	Number of Conductors	Stranding	Shield	DC Resistance (Ohms/1000')	Nominal Capacitance (pF/ft.)	Nominal Outer Diameter (Inches)	Average Weight (Pounds/1000')	Product Code
22	2	Solid	Shielded	18	29.9	0.108	9.9	3201
22	2	7 Strand	Shielded	16.9	44.0	0.120	11.0	3202
22	3	7 Strand	Shielded	16.9	39.2	0.134	13.9	3227
22	4	Solid	Shielded	18	26.5	0.124	14.9	3203
22	4	7 Strand	Shielded	16.9	39.2	0.137	17.0	3204
22	6	7 Strand	Shielded	16.9	26.0	0.162	23.3	3206
22	8	7 Strand	Shielded	16.9	26.0	0.192	28.9	3207
22	10	7 Strand	Shielded	16.9	26.0	0.216	35.2	3208
22	12	7 Strand	Shielded	16.9	26.0	0.219	41.4	3209
18	2	19 Strand	Shielded	6.66	59.3	0.156	19.3	3214
18	3	19 Strand	Shielded	6.66	50.8	0.166	25.8	3226
18	4	19 Strand	Shielded	6.66	50.8	0.182	32.2	3215
18	5	19 Strand	Shielded	6.66	50.8	0.197	38.3	3276
18	6	19 Strand	Shielded	6.66	32.2	0.216	40.2	3216
18	8	19 Strand	Shielded	6.66	32.2	0.236	58.2	3217
18	10	19 Strand	Shielded	6.66	32.2	0.276	72.3	3218
16	2	26 Strand	Shielded	4.19	65.9	0.180	28.0	3221
16	4	26 Strand	Shielded	4.19	55.6	0.210	49.1	3222
14	2	19 Strand	Shielded	2.62	70.2	0.212	38.8	3223
14	4	19 Strand	Shielded	2.62	58.6	0.238	69.1	3224