CATEGORY 1

Professional Plumbing-Grade PVC Cement

780[™] PVC Plumbing, Clear, Regular-Bodied, Fast-Setting

ELD×ON

CORPORAT



WELD:ON

WELD ON

PVC

- (NSF)
- Regular-bodied, fast-setting, low-VOC PVC cement for all classes and schedules with interference fit through 4"
 - Specialty formulated for plumbing applications, including PVC foam core pipe

Product Code	Product	Description	Model Number	UPC Barcode	Cubic ft./Case	Units/Case	Lbs/Case
14004	1⁄4 Pt.	Can with Applicator Cap	14004	012181-140048	0.220	24	8
14003	1⁄2 Pt.	Can with Applicator Cap	14003	012181-140031	0.370	24	15
14002	Pt.	Can with Applicator Cap	14002	012181-140024	0.360	12	14
14001	Qt.	Can with Applicator Cap	14001	012181-140017	0.670	12	27
14000	Gal.	Can with Screw-on Cap	14000	012181-140000	1.070	6	52

702[™] PVC Clear, Regular-Bodied, Fast-Setting

• Regular-bodied, fast-setting, low-VOC PVC cement for all (NSF) classes and schedules with interference fit through 4"

(110 mm) diameter (except Schedule 80)

Specialty formulated for plumbing applications, including PVC

· Can be used without primer on non-pressure systems if local

Specialty formulated for plumbing applications, including PVC

Excellent for DWV, irrigation, electrical conduit, pool & spa

(110 mm) diameter (except Schedule 80)				-	•				
Product	Code Pr	roduct D	Description	Model	Number	UPC Barcode	Cubic ft./Case	Units/Case	Lbs/Case
10978	3 1/4	á Pt.	Can with Applicator Cap	1070	20051	012181-109786	0.29	24	8
10977	' ½	2 Pt.	Can with Applicator Cap	1070	20041	012181-109779	0.41	24	15
10976	6 Pt	t.	Can with Applicator Cap	1070	20031	012181-109762	0.42	12	14
10975	i Q	t.	Can with Applicator Cap	1070	20021	012181-109755	0.78	12	27

and plumbing, including PVC foam core pipe

1 TOULOT OOUC			Wouch Wullinger	or o barcouc	00010 11./0030	01113/0030	LD3/0030
10978	1⁄4 Pt.	Can with Applicator Cap	107020051	012181-109786	0.29	24	8
10977	1⁄2 Pt.	Can with Applicator Cap	107020041	012181-109779	0.41	24	15
10976	Pt.	Can with Applicator Cap	107020031	012181-109762	0.42	12	14
10975	Qt.	Can with Applicator Cap	107020021	012181-109755	0.78	12	27
10974	Gal.	Can with Screw-on Cap	107020011	012181-109748	1.21	6	51

781[™] PVC Plumbing, Clear, Medium-Bodied, Fast-Setting

- •Medium-bodied, fast-setting, low-VOC PVC cement for all
- classes and schedules with interference fit through 6" (NSF) (160 mm) diameter, Schedule 80 through 4" (110 mm) diameter

alamotor	codes permit						
Product Code	Product Description		Model Number	UPC Barcode	Cubic ft./Case	Units/Case	Lbs/Case
14009	1⁄4 Pt.	Can with Applicator Cap	14009	012181-140093	0.220	24	8
14008	½ Pt.	Can with Applicator Cap	14008	012181-140086	0.370	24	15
14007	Pt.	Can with Applicator Cap	14007	012181-140079	0.360	12	14
14006	Qt.	Can with Applicator Cap	14006	012181-140062	0.670	12	27
14005	Gal.	Can with Screw-on Cap	14005	012181-140055	1.070	6	52

foam core pipe

foam core pipe

781[™] PVC Plumbing, Gray, Medium-Bodied, Fast-Setting



- E. • Medium-bodied, fast-setting, low-VOC PVC cement for all classes and schedules with interference fit through 6" (NSF) (160 mm) diameter, Schedule 80 through 4" (110 mm)
 - · Can be used without primer on non-pressure systems if local diameter codes permit Product Code Product Description Model Number UPC Barcode Cubic ft./Case Units/Case Lbs/Case 14014 1⁄4 Pt. Can with Applicator Cap 14014 012181-140147 0.220 24 8 14013 1/2 Pt. Can with Applicator Cap 14013 012181-140130 0.370 24 15 14012 Pt. Can with Applicator Cap 14012 012181-140123 0.360 12 14 14011 Can with Applicator Cap 012181-140116 12 Qt. 14011 0.670 27 14010 Can with Screw-on Cap 14010 012181-140109 1.070 52 Gal. 6



GRAY

GUY







STUDOR IPS CORPORATION