

Specification:

Furnish and install Water-Tite's Wax Gasket which is 100% pure wax gasket for setting all floor outlet toilet bowls. The gasket will form a water tight, gas tight and odor tight seal. Fits 3" and 4" waste lines. Available with plastic horn which extends the discharge opening to create a more positive seal and assure proper bowl alignment.


Certifications:

Meets federal specification TT-P-1536A
 Buy American Act

Instructions:

1. Be sure the wax ring is at room temperature (about 70°F). If wax ring is too cold a good seal may not be made or the toilet bowl could crack while making the installation.
2. With the toilet bowl upside down on a protective pad or blanket, place the wax ring around the discharge opening, extending plastic flange away from the bowl. Press firmly to assure adhesion when the toilet is inverted.
3. Using IPS Corporation's Soft Putty make a putty ring about 1 inch high around the outside rim of the toilet. This will make a seal between the toilet rim and the floor.
4. Carefully set toilet down on bolts and twist bowl slightly to spread wax and putty to make a tight seal. Tighten bolts carefully to prevent breaking the bowl.

✓	Product Code #	Model #	Product Description	Units/Case
	82550	RWG1	Standard Wax Gasket	48
	82555	RWG2	Wax Gasket with Plastic Horn	24
	82556	RWG7	Std. Wax Gasket w/Double Nut Brass Closet Bolts	48
	82557	RWG8	Wax Gasket w/Plastic Horn w/Double Nut Brass Closet Bolts	24
	82565	RNWG1	Reinforced Wax Gasket with Plastic Horn	24
	87760	RWG3	Standard Wax Gasket w/Brass Closet Bolt Kit	48
	82552	RWG4	Wax Gasket with Plastic Horn w/Brass Closet Bolt Kit	24
	82553	RWG5	Jumbo Wax Gasket with 3.5" Brass Plated Bolt Kit	48
	82554	RWG6	Wax Gasket with Plastic Horn w/Brass Plated Closet Bolt Kit	24
	82559	RWG10	Jumbo Wax Gasket with Horn & Double Nut Bolt Kit	24
	82561	RWG2J	Jumbo Wax Gasket with Horn & Double Nut Bolt Kit	24
	82560	RWG1J	Jumbo Wax Gasket	48
	82562	RWG11	Wax Gasket with Horn & Double Nut Bolt Kit	24

Note: Items that include Brass Closet Bolt Kit contains: two 1/4" x 2-1/4" brass bolts, two brass plated washers, two brass plated nuts and two plastic stand-up washers.