

Stabilizer Systems

CATEGORY 14

PEX Bend Supports



- · Provides versatile, rigid, 90-degree support for PEX tubing
- When snapped into PEX Bend Support Bracket, offers a full 360-degree roration with positive locking at 45 degree intervals
- Reduces noise and vibration
- Plastic material eliminates cutting or scratching of tubing
- For residential or commercial applications

	Fite	3/,11	and	1/211	tubina
•	LII?	78	ann	72	11111111111

- Offers three installation options mounting directly to stud or overhead joist, through stabilizer bar, or snapped into PEX Bend Support Bracket
- When snapped into PEX Bend Support Bracket, offers a full 360-degree roration with positive locking at 45 degree intervals

Product Co	ode#	Product Description	Model Number	UPC Barcode	Cubic ft./Case	Units/Case	Lbs/Case
86673	3	½" PEX Bend Support, Ceiling/Stud Mount	PBS2	012181-866733	0.120	50	11.9
86672	₹.	½" PEX Bend Support, Bar Mount	PBS1	012181-866726	0.120	100	23.8
86652		18" PEX Support Bar	PS18	012181-866528	0.120	50	210
86653		26" PEX Support Bar	PS26	012181-866535	0.120	50	210

Horizontal Run Stabilizer Bar Kits



- Insulators are available for horizontal runs of 1/2" or 3/4" tube
- Supports all CTS tubing
- Kits include a 20" or 26" stabilizer bar, 2 tube insulators
- Horizontal insulators are available in CPVC
- Impact-resistant to 0°F (-18°C) Max temp: 160°F (71°C) continuous

	ode # Product Description	Model Number	r UPC Barcode	Cubic ft./Case	Units/Case	Lbs/Case
86694	20" Bar with Plastic Insulators for ½" CTS	S2012PH	012181-866948	0.390	50	15
86696	20" Bar with Plastic Insulators for ¾" CTS	S2034PH	012181-866962	0.390	50	15
86698	26" Bar with Plastic Insulators for ½" CTS	S2612PH	012181-866986	0.500	50	19
86699	26" Bar with Plastic Insulators for ¾" CTS	S2634PH	012181-866993	0.500	50	18

Vertical Run Stabilizer Bar Kits



- Insulators are available for vertical runs of 1/2" or 3/4" tube
- Supports all CTS tubing
- Kits include a 20" or 26" stabilizer bar, 2 tube insulators and 4 nails
- Vertical insulators are available in plastic only
- •Impact-resistant to 0°F (-18°C) Max temp: 160°F (71°C) continuous

Product Code #	Product Description	Model Number	r UPC Barcode	Cubic ft./Case	Units/Case	Lbs/Case
86701	20" Bar with Plastic Insulators for ½" CTS	S2012PV	012181-867013	0.390	50	15
86702	20" Bar with Plastic Insulators for ¾" CTS	S2034PV	012181-867020	0.390	50	15
86703	26" Bar with Plastic Insulators for ½" CTS	S2612PV	012181-867037	0.500	50	19
86704	26" Bar with Plastic Insulators for ¾" CTS	S2634PV	012181-867044	0.500	50	19

Stabilizer Bars



• Bars are available in 20" lengths for 16" stud bays & 26" lengths for 24" stud bays

F	roduct Co	de # Product Description	Model Number	UPC Barcode	Cubic ft./Case	Units/Case	Lbs/Case
8	36650	20" Stabilizer Bar for 16" Stud Bays	S20	012181-866504	0.120	100	24
8	36655	26" Stabilizer Bar for 24" Stud Bays	S26	012181-866559	0.120	100	29

