

SPARK-PROOF MOTOR

New Spark-Proof Motor has the same features as our other pumps with the addition of spark-free, dual-voltage operation.

For use with A2L refrigerant gases such as R32 and 1234YF.

Part No. DV-200N-250SP



PLATINUM® Pump Assembly

PLATINUM® PUMPS					
	DV-42N	DV-85N	DV-142N	DV-200N/ DV-200N-250SP	DV-285N
CFM	1.5 CFM (42 l/m)	3 CFM (85 l/m)	5 CFM (142 l/m)	7 CFM (200 l/m)	10 CFM (285 l/m)
MOTOR	1/2 HP, 1725 RPM	1/2 HP, 1725 RPM	1/2 HP, 1725 RPM	1/2 HP, 1725 RPM	1/2 HP, 1725 RPM
VOLTAGE	115v, 60Hz	115v, 60Hz	115v, 60Hz	115v, 60Hz	115v, 60Hz
PLUG	US 110v	US 110v	US 110v	US 110v	US 110v
INTAKE PORT	1/4"	1/4" x 3/8"	1/2" x 1/4" x 3/8"	1/2" x 1/4" x 3/8"	1/2" x 1/4" x 3/8"
OIL CAP	26 oz (798 cc)	26 oz (798 cc)	21 oz (680)	21 oz (680)	26 oz (798 cc)
SHIP DIMENSIONS	17-5/8" h 9-1/8" w 14" l	17-5/8" h 9-1/8" w 14" l	17-5/8" h 9-1/8" w 14" l	17-5/8" h 9-1/8" w 14" l	17-5/8" h 9-1/8" w 14" l
WEIGHT	29 lbs (13.2 kg)	30 lbs (13.6 kg)	32 lbs (14.5 kg)	32 lbs (14.5 kg)	34 lbs (15.4 kg)
EUROPEAN					-250EU
	DV-42N-250EU	DV-85N-250EU	DV-142N-250EU	DV-200N-250EU	DV-285N-250EU
MOTOR	1/2 HP, 1425 RPM	1/2 HP, 1425 RPM	1/2 HP, 1425 RPM	1/2 HP, 1425 RPM	1/2 HP, 1425 RPM
VOLTAGE	230v/50Hz	230v/50Hz	230v/50Hz	230v/50Hz	230v/50Hz
PLUG	European	European	European	European	European
DUAL VOLTAGE					-250
	DV-42N-250	DV-85N-250	DV-142N-250	DV-200N-250	DV-285N-250
MOTOR	1/2 HP, 1725 (1425) RPM	1/2 HP, 1725 (1425) RPM	1/2 HP, 1725 (1425) RPM	1/2 HP, 1725 (1425) RPM	1/2 HP, 1725 (1425) RPM
VOLTAGE	115v, 60Hz and 230v/50Hz	115v, 60Hz and 230v/50Hz	115v, 60Hz and 230v/50Hz	115v, 60Hz and 230v/50Hz	115v, 60Hz and 230v/50Hz
PLUG	US 220v	US 220v	US 220v	US 220v	US 220v
UNITED KINGDOM					-250UK
	DV-42N-250UK	DV-85N-250UK	DV-142N-250UK	DV-200N-250UK	DV-285N-250UK
MOTOR	1/2 HP, 1425 RPM	1/2 HP, 1425 RPM	1/2 HP, 1425 RPM	1/2 HP, 1425 RPM	1/2 HP, 1425 RPM
VOLTAGE	230v/50Hz	230v/50Hz	230v/50Hz	230v/50Hz	230v/50Hz
PLUG	UK	UK	UK	UK	UK