

## BRASS PIPE FITTINGS

JB's American made forged brass pipe fittings are manufactured from CA 377 alloy and are threaded to Dry seal Taper Pipe Standards to generally comply with SAE, ASA, ASME, and MS Standards. Forgings can be used on vacuums to pressures of 5,000 psi depending on size, material, and conditions.

### FEATURES

Good vibration resistance (improved by using long nuts)

Low cost

Easy assembly

American made quality

Wide selection

JB recommends the use of a compatible thread sealant and tightening 2-1/2 full turns past hand tight. Vacuum and pressures of 5,000 psi can be handled depending upon the size, material, and conditions.

**Caution:** Over-tightening and dirt can damage fittings

JB brass fittings are sold in box quantities only. For more information, please contact customer service.

#### NOMINAL PIPE SIZE THREADS

NOM. PIPE	THD. / IN.	NOM. PIPE	THD. / IN.
1/16"	27	2"	11.5
1/8"	27	2-1/2"	8
1/4"	18	3"	8
3/8"	18	3-1/2"	8
1/2"	14	4"	8
3/4"	14	5"	8
1"	11.5	6"	8
1-1/4"	11.5	8"	8
1-1/2"	11.5	---	---

### FEMALE FLARE X FEMALE FLARE CONNECTOR

Includes two copper gaskets



PART NO.	SIZE	QTY.
U4-4	1/4"	10
U4-6	3/8"	10
U4-8	1/2"	2
U4-10	5/8"	2
U4-12	3/4"	2

### FEMALE FLARE X FEMALE PIPE ADAPTER

Includes copper seal gasket



PART NO.	SIZE	QTY.
U5-4A	1/4" x 1/8"	5
U5-4B	1/4" x 1/4"	10
U5-6B	3/8" x 1/4"	5
U5-8C	1/2" x 3/8"	2
U5-8D	1/2" x 1/2"	2

### SWIVEL FEMALE FLARE CONNECTOR



PART NO.	SIZE	QTY.
US4-4	1/4"	10
US4-5	5/16"	5
US4-6	3/8"	10
US4-8	1/2"	10
US4-10	5/8"	5

### FEMALE FLARE X MALE PIPE ADAPTER



PART NO.	SIZE	QTY.
U6-4A	1/4" x 1/8"	2
U6-4B	1/4" x 1/4"	2

### SWIVEL FEMALE FLARE X SOLDER ADAPTER

A32700 series, see page 68



PART NO.	SIZE	QTY.
US5-44	1/4" x 1/4"	5
US5-66	3/8" x 3/8"	5
US5-88	1/2" x 1/2"	5
US5-1010	5/8" x 5/8"	5
US5-1212	3/4" x 3/4"	2

### EXTRA LONG FLARE X MALE PIPE ADAPTER



PART NO.	SIZE	QTY.
UX1-4A	1/4" x 1/8"	2
UX1-4B	1/4" x 1/4"	5

### EXTRA LONG FLARE UNION



PART NO.	SIZE	QTY.
UX2-4	1/4"	5