

Slic-tite® Paste with PTFE

Heavy-duty pipe
thread compound



Specially formulated with PTFE for added sealing power, Slic-tite® is the premium thread sealant paste. It has been successfully used for decades to seal water, air, steam, natural gas, and more. It removes easily from skin and clothing, reducing post-job cleanup time. Slic-tite thread sealant works in extremely high-pressure systems, and it comes with several approvals to ensure industry standards are met.

- Contains PTFE for greater sealing power
- Pressures: 3,000 PSI (204 BAR) for gas; 10,000 PSI (680 BAR) for liquid
- Sealing temperature: -50°F to 500°F (-46°C to 260°C)
- Can be used on a variety of metals and plastic, eliminating the need for any other thread sealant
- Washes off hands and clothes easily; quick and easy cleanup
- Safe, non-toxic, non-drying
- Made in U.S.A.

For Use On:

- Metal
- PVC
- CPVC
- ABS

Approvals/Certifications:

- USDA approved for use in federally inspected meat and poultry plants
- UL
- CSA
- NSF
- UPC
- FBC™ system compatible

RIGHT
FOR
THE
JOB.™

LA-CO®

laco.com

41209	1/4 pt. BIC	12 per case	42013	1 qt.	12 per case
42009	1/4 pt. BIC	24 per case	42049	1 qt. BIC	12 per case
41219	1/2 pt. BIC	12 per case	42014	1 gal.	4 per case
42019	1/2 pt. BIC	24 per case	42015	5 gal.	1 per case
42012	1 pt.	24 per case	42069	55 gal.	1 per case
42029	1 pt. BIC	24 per case	42002	1-1/2 oz.	24 per case

BIC=Brush-In-Cap

LA-CO Industries Inc.
1201 Pratt Boulevard
Elk Grove Village, IL 60007-5746 USA
(1) 800.621.4025
(1) 847.956.7600
Customer Service@laco.com
LP97R00010

LA-CO Industries Europe S.A.S.
ALLEE DES COMBES
PI DE LA PLAINE DE L'AIN
01150 BLYES
France
Tel: +33 (0) 4 74 46 23 23
info@eu.laco.com

