2.94 in (75 mm)



Shown actual size: Skylark dimmer and 1-gang Claro wallplate in White (WH).

Product family features

- Rocker switch returns light to your favorite light level
- Slide up to brighten, down to dim (adjust light to suit any activity)
- · eco-dim_® model available
- 1000W preset dimmers have voltage compensation which maintains stable light levels, despite line voltage variations
- · 100% factory tested
- Coordinating Claro® and Stainless Steel wallplates only available separately
- Custom engraving available for wallplates, see pg. 155

Control types

Single-pole (one location)

a-way or 4-way (two or more locations)

Direct load type compatibility

- ▼ Magnetic low-voltage lighting
- ☐ Electronic low-voltage lighting
- □ Fluorescent lighting
- LED lighting
- Dimmable compact fluorescent
- Ceiling fans
- ★ Ceiling fan/lights

Load type requiring load interface

Neon/cold cathode lighting

Lighting load interfaces may be applicable for some additional load type, voltage and capacity combinations.

For additional information, see pg. 174.

Dimmer model numbers

Dimmers with on/off switch

Single-pole	S-600P- <u>CC</u> ³
120V 600W	
Single-pole	S-10P- <u>CC</u> 3
120V 1000W	
3-way	S-603P- <u>CC</u> ³
120V 600W	
3-way	S-103P- <u>CC</u> 3
120V 1000W	

eco-dim@dimmer with on/off switch

3-way/single-pole	S-603PG- EE 2
120V 600W	

eco-dim model guarantees at least 15% energy savings compared to a standard switch.

Dimmers with on/off switch and locator light

Single-pole	S-600PNL- <u>CC</u> 3	
120V 600W		
Single-pole	S-10PNL- <u>CC</u> 3	
120V 1000W		
3-way	S-603PNL- <u>CC</u> 3	
120V 600W		
3-way	S-103PNL- <u>CC</u> 3	
120V 1000W		

Slide-to-off dimmers

Single-pole	S-600- <u>CC</u> 3
120V 600W	
Single-pole	S-1000- <u>CC</u> ³
120V 1000W	

For dual slide-to-off dimmers (two loads), see page 111.

▼ Magnetic low-voltage dimmers

Dimmers with on/off switch

Single-pole	SLV-600P- <u>CC</u> 3
120 V 600 VA (450 W)	
3-way	SLV-603P- CC ³
120 V 600 VA (450 W)	

The stated VA (Volt-Ampere) rating includes the magnetic transformer heat losses and the lamp load. The stated W (Watt) rating is the maximum lamp wattage based on assumed 20% transformer loss.

□ Electronic low-voltage dimmers*

Dimmers with on/off switch

Single-pole	SELV-300P- <u>CC</u> ³
120V 300W	
3-way	SELV-303P- CC ³
120V 300W	

Certain LED drivers are dimmable using an ELV dimmer, for more information, visit www.lutron.com/LED.

CC³: Gloss color codes, see pg. 105

EE²: Available in White (WH), Ivory (IV), Almond (AL) and Light Almond (LA) (Wallplates not included, order separately, see pg. 160)

All models must be derated if ganged unless otherwise noted, see pg. 170.

*Requires neutral wire connection.