

Compliance Label Model MTXXXX Made in USA Complies with ANSI 7124.1-1995 CSA Certified C/US 571/4 (1)12 1/2" 51/2 -261/2" Shown with Whirlpool Package 211/4 201/2"

MBOC6060

59.25" x 59.25" x 21.25"

Installation: Drop-in

cannot be undermounted

GENERAL SPECIFICATIONS:

Material Acrylic

Plumbed Weight 125 lbs / 57 kg Soaker Weight 100 lbs / 45 kg Average Fill 44 gal to above jet level

Maximum Fill 85 gal to overflow

NOTE: Filling this tub to the maximum may require an above average size or dedicated water heater

ELECTRICAL SPECIFICATIONS:

Required Electrical Service 110 Volt Air Bath or Whirlpool 1-15 amp GFCI Whirlpool with Inline Heater 1-15 amp GFCI Soaker with Inline Heater 1-15 amp GFCI Air Bath with Inline Heater 2-15 amp GFCI CSA Certified C/US; ANSI Z124.1 for plastic tubs and ANSI 112.19.7 for whirlpool components.

PACKAGES AND OPTIONS

Hydrotherapy Package	Package Contents	Part #
Soaker	soaking bath - no jets, textured bottom	MBSOC6060
Whirlpool	6 point-massage jets, 1-bhp pump, textured bottom	MBWOC6060
Air Bath	12 air jets, heated air blower, textured bottom, pre-leveled foam base (increases overall height 2-3")	MBAOC6060

OPTIONS

Standard Colors - White

Color Upgrade - Biscuit (MTISCOLOR) Quick Ship - reduces lead time - call for availability

Inline Heater - Whirlpool (HTRMTIS)

Inline Heater with Pump - Soaker or Air Bath (MBHTISOAK)

Lift & Turn Drain Kit -

Chrome (MBWOC); Brushed Nickel (MBWOBN), White (MBWOW)

Tile Flange - Factory-Installed - 2 sides (MBTFKC); Pre-Leveled Foam Base (MBPLFOAM) standard with Air Bath

Pre-Leveled Frame & Foam Base (MBPLF) Pre-Leveled Frame & Foam Base with Skirting -

Acrylic Euro-Style Skirt with Removable Panels (MBFSKAC5)

IMPORTANT INFORMATION

- Before ordering or installing, please consider future access to equipment.
- Add bedding compound to fully level and support bottom of tub.
- Tubs equipped with an air bath or a pre-leveled foam base are designed to rest on the floor without bedding compound, provided the floor is level.
- Overall tub height is increased by approx. 2-3" when tub is equipped with any air bath package or when pre-leveled foam base or framing system is ordered.
- Please measure tub on-site before building tub decking.

- · Jet, pump & blower locations are predetermined and cannot be changed.
- Suction and control locations may vary.
- Options listed cannot be combined with Designer Collection options.
- Specifications and configurations are subject to change without notice.
- Measurements are $\pm 1/2$ " and are subject to change without notice.
- Measurements herein supersede all others published prior to publication date shown below.

