ONE-INCH **NOTCHER**

The N2R Notcher punches a big 1-inch (25.4 mm) deep "V" notch in common 24- to 30-inch (0.71-0.41 mm) gauge galvanized sheet metal quickly and easily.

N2R - Throat Depth 1-inch (25.4 mm)



RATCHETING **HANDLE**

CONNEXT3TM

Forward or Reverse ratchet driving, as well as a locked driving position. Meets torque capacity standards (including ANSI) comparable to a 1/2-inch solid shaft driver! A quick-connect holder accepts most 1/4-inch hex shank driver or insert bits.



POCKET SIZED SHEET METAL SCRIBE



Scribe common place trim lines on galvanized sheet metal. Ten pre-set scribing depths from 1/8 to 1 inch (3 to 25 mm).

A40 - 1/8, 3/16, 1/4, 5/16, 3/8,1/2, 5/8, 3/4, 7/8, 1 inch (3.2, 4.8, 6.4, 9.5, 12.7, 15.9, 19.1, 22.2, 25.4 mm)

ADJUSTABLE SHEET METAL SCRIBE

Measure, mark and scribe trim lines on sheet metal in one easy operation. Adjustable from 1/4 to 12-1/2 inch (6.4 to 318 mm) depths. Rotate the scriber extension and knob end to end for depths larger than 6-1/2 inch (165 mm).



SHEET METAL DOUBLE ENDER DRILL BITS



Two points for twice the life, twice the convenience. DE18 - Polished Drill Bit - 1/8-inch (3.175 mm) Qty. 12

DE18B - Polished Drill Bit Bulk Pack - 1/8-inch (3.175 mm) Qty. 144



SLIP-ON SPRING TUBE BENDERS

TB1026 - 3/8-inch (9.5 mm) O.D. capacity

TB1028 - 1/2-inch (12.7 mm) O.D. capacity

TB1020 - 5/8-inch (15.9 mm) 0.D. capacity

TB1022 - 3/4-inch (19.1 mm) O.D. capacity

TB102K - Kit: 5-piece set including Tube Benders above plus

1/4-inch (6.4 mm) 0.D. size

Bend tubing including brake lines and more without collapsing walls.



Easy loading and lightweight for smooth, clean operation.

CG10 - 1/10 gal. cart. cap., 2-inch (51 mm) cart. dia.

CG12 - Puncture Wire, 1/10 gal. cart. cap., 2-inch (51 mm) cart. dia.

CG18 - Heavy-duty, Rotating barrel, 1/10 gal. cart. cap., 2-inch (51 mm) cart. dia.

CG20 - Heavy-duty, Puncture wire, 1/10 gal. cart. cap., 2-inch (51 mm) cart. dia.



SELF-PIERCING SHEET METAL SCREWS

The standard by which all others are judged. A unique thread design and quality controlled manufacture spell the Zip-in® difference.

PAINTED SHEET METAL / DRILL IN SCREWS

Drill-In screws, Type A, Single Thread (Shown in Bags)

HW8x3/4ZT - Zip-in® Tub, Head Zinc Plated, Size 1/4-inch, Quantity 1000 HW6x3/8ZRBT - Painted Drill-in Screws Tub. Color Royal Brown (RB), Size 1/4-inch, Qtv. 1000 HW6x3/8ZWT - Painted Drill-in Screws Tub, Color White (W), Size 1/4-inch, Quantity 1000



The TR42 expands to a big 42-inch (107 cm) radius (84-inch diameter). The compact TR18 expands to 18-inch (46 cm) and stores in most tool boxes.

TR18 - 18-inch (46 cm) • TR42 - 42-inch (107 cm) • TRP - Replacement Points





Cuts hose up to 1-inch (25.4 mm) I.D. **TC400** - Cutting applications include

fabric-reinforced hose.