



**RADS-121P 12,000 BTUH**  
Nominal

**FEATURES**



- Electronic controls with full feature remote and auto restart
- Four-way adjustable air direction
- Easy-access, slide-out, washable filter
- One degree temperature adjustment
- Energy saver mode, 24-hour on/off timer, dehumidification and auto modes

**SPECIFICATIONS**

|                                  |                                |
|----------------------------------|--------------------------------|
| Cooling Capacity BTUH            | 12,000                         |
| Approx. Sq. Ft. Cooling          | 450-550                        |
| EER/CEER                         | 12.0/12.0                      |
| Heating Capacity BTUH (electric) | N/A                            |
| Power Supply                     | 115V 60Hz                      |
| Humidity Removal Pts/Hr          | 2.54                           |
| Ventilation Control              | Yes                            |
| Fan Only                         | Yes                            |
| Fan Speeds Cool/Fan              | 3/3                            |
| Air Delivery Max. CFM            | 300                            |
| dB Level (hi/med/low)            | 61/57/54                       |
| Amps Cooling                     | 8.7                            |
| Amps Heating                     | N/A                            |
| Maximum Fuse Size                | 15A                            |
| Power Cord                       | 15A Parallel NEMA 5-15P        |
| Slide-Out Chassis                | No                             |
| Window Mounting Kit              | Yes                            |
| Remote Control                   | Yes                            |
| In-Home Service                  | Yes                            |
| Shipping Weight (lbs.)           | 78.5                           |
| Dimensions (in.) Height          | 14 <sup>5</sup> / <sub>8</sub> |
| Width                            | 19                             |
| Depth                            | 21 <sup>1</sup> / <sub>2</sub> |



**RADS-123M 12,000 BTUH**  
Nominal

**FEATURES**

- Electronic controls with full feature remote and auto restart
- Four-way adjustable air direction
- Easy-access, slide-out, washable filter
- One degree temperature adjustment
- Energy saver mode, 24-hour on/off timer, dehumidification and auto modes

**SPECIFICATIONS**

|                                  |                                |
|----------------------------------|--------------------------------|
| Cooling Capacity BTUH            | 11,700/12,000                  |
| Approx. Sq. Ft. Cooling          | 450-550                        |
| EER/CEER                         | 11.3/11.2                      |
| Heating Capacity BTUH (electric) | N/A                            |
| Power Supply                     | 208/230V 60Hz                  |
| Humidity Removal Pts/Hr          | 2.54                           |
| Ventilation Control              | Yes                            |
| Fan Only                         | Yes                            |
| Fan Speeds Cool/Fan              | 3/3                            |
| Air Delivery Max. CFM            | 288                            |
| dB Level (hi/med/low)            | 60/58/55                       |
| Amps Cooling                     | 5.1/4.7                        |
| Amps Heating                     | N/A                            |
| Maximum Fuse Size                | 15A                            |
| Power Cord                       | 15A Tandem NEMA 6-15P          |
| Slide-Out Chassis                | No                             |
| Window Mounting Kit              | Yes                            |
| Remote Control                   | Yes                            |
| In-Home Service                  | Yes                            |
| Shipping Weight (lbs.)           | 77                             |
| Dimensions (in.) Height          | 14 <sup>5</sup> / <sub>8</sub> |
| Width                            | 19                             |
| Depth                            | 21 <sup>1</sup> / <sub>2</sub> |



**RADS-151P 15,000 BTUH**  
Nominal

**FEATURES**



- Electronic controls with full feature remote and auto restart
- Four-way adjustable air direction
- Easy-access, slide-out, washable filter
- One degree temperature adjustment
- Energy saver mode, 24-hour on/off timer, dehumidification and auto modes

**SPECIFICATIONS**

|                                  |                                  |
|----------------------------------|----------------------------------|
| Cooling Capacity BTUH            | 15,100                           |
| Approx. Sq. Ft. Cooling          | 550-700                          |
| EER/CEER                         | 12.0/12.0                        |
| Heating Capacity BTUH (electric) | N/A                              |
| Power Supply                     | 115V 60Hz                        |
| Humidity Removal Pts/Hr          | 3.17                             |
| Ventilation Control              | Yes                              |
| Fan Only                         | Yes                              |
| Fan Speeds Cool/Fan              | 3/3                              |
| Air Delivery Max. CFM            | 353                              |
| dB Level (hi/med/low)            | 56/54/53                         |
| Amps Cooling                     | 11.5                             |
| Amps Heating                     | N/A                              |
| Maximum Fuse Size                | 15A                              |
| Power Cord                       | 15A Parallel NEMA 5-15P          |
| Slide-Out Chassis                | Yes                              |
| Window Mounting Kit              | Yes                              |
| Remote Control                   | Yes                              |
| In-Home Service                  | Yes                              |
| Shipping Weight (lbs.)           | 118                              |
| Dimensions (in.) Height          | 17 <sup>15</sup> / <sub>16</sub> |
| Width                            | 23 <sup>5</sup> / <sub>8</sub>   |
| Depth                            | 25 <sup>7</sup> / <sub>16</sub>  |

# Specifications

## POWER CORD Configurations



15 AMP 115V  
PARALLEL  
**A**  
5-15P



15 AMP 230V  
TANDEM  
**B**  
6-15P



20 AMP 230V  
TEE  
**C**  
6-20P



30 AMP 230V  
TANDEM  
**D**  
6-30P

## Sizing Guidelines

Use the chart below as a quick reference in determining which unit(s) will fit your needs

| Square Feet to be conditioned | Square Meters to be conditioned | Capacity Needed (BTUH) |
|-------------------------------|---------------------------------|------------------------|
| 100 - 150                     | 9.3 - 13.9                      | 5,000                  |
| 150 - 250                     | 13.9 - 23.2                     | 6,000                  |
| 250 - 300                     | 23.2 - 27.9                     | 7,000                  |
| 300 - 350                     | 27.9 - 32.5                     | 8,000                  |
| 350 - 400                     | 32.5 - 37.2                     | 9,000                  |
| 400 - 450                     | 37.2 - 41.8                     | 10,000                 |
| 450 - 550                     | 41.8 - 51.1                     | 12,000                 |
| 550 - 700                     | 51.1 - 65.1                     | 14,000                 |
| 700 - 1,000                   | 65.1 - 92.9                     | 18,000                 |
| 1,000 - 1,200                 | 92.9 - 111.5                    | 21,000                 |
| 1,200 - 1,400                 | 111.5 - 130.1                   | 23,000                 |
| 1,400 - 1,500                 | 130.1 - 139.4                   | 25,000                 |
| 1,500 - 2,000                 | 139.4 - 185.8                   | 30,000                 |

Guidelines from [www.energystar.gov](http://www.energystar.gov)

Energy Star recommends increasing capacity by 10% for a sunny room, decreasing by 10% for shaded room.

If used in a kitchen, add 4,000 BTUHs to the total.

If more than two people regularly use the room, add 600 BTUH for each additional person.

### IMPORTANT!

Always wait to cut an opening until the unit arrives and dimensions can be verified.



| Model                                | Cooling Capacity BTU/Hr | Approx. Sq. Ft. Cooling | EER/CEER  | Heating Capacity BTUH (electric) | Electric (Volts) | Humidity Removal Pints/Hr | Remote Control |
|--------------------------------------|-------------------------|-------------------------|-----------|----------------------------------|------------------|---------------------------|----------------|
| <b>COOLING 5,000 to 10,000 BTUH</b>  |                         |                         |           |                                  |                  |                           |                |
| RG-51M                               | 5,000                   | 100-150                 | 11.1/11.0 | N/A                              | 115              | 1.27                      | No             |
| RADS-51P*                            | 5,000                   | 100-150                 | 12.2/12.1 | N/A                              | 115              | 1.27                      | Yes            |
| RADS-61P*                            | 6,000                   | 150-250                 | 12.2/12.1 | N/A                              | 115              | 1.48                      | Yes            |
| RADS-81P*                            | 8,000                   | 300-350                 | 12.0/12.0 | N/A                              | 115              | 2.11                      | Yes            |
| RADS-101P*                           | 10,000                  | 400-450                 | 12.0/12.0 | N/A                              | 115              | 2.32                      | Yes            |
| <b>COOLING 12,000 to 36,600 BTUH</b> |                         |                         |           |                                  |                  |                           |                |
| RADS-121P*                           | 12,000                  | 450-550                 | 12.0/12.0 | N/A                              | 115              | 2.54                      | Yes            |
| RADS-123M                            | 11,700/12,000           | 450-550                 | 11.11.2   | N/A                              | 208/230          | 2.54                      | Yes            |
| RADS-151P*                           | 15,100                  | 550-700                 | 12.0/12.0 | N/A                              | 115              | 3.17                      | Yes            |
| RADS-183P*                           | 17,700/18,000           | 700-1000                | 11.8/11.8 | N/A                              | 208/230          | 3.80                      | Yes            |
| RADS-253P*                           | 24,700/25,000           | 1400-1500               | 10.3/10.3 | N/A                              | 208/230          | 5.71                      | Yes            |
| RAD-283M                             | 28,000/28,500           | 1500-2000               | 9.0       | N/A                              | 208/230          | 6.34                      | Yes            |
| <b>COOLING WITH ELECTRIC HEAT</b>    |                         |                         |           |                                  |                  |                           |                |
| REG-81M                              | 8,000                   | 300-350                 | 10.9/10.9 | 3,500                            | 115              | 1.48                      | Yes            |
| REG-123M                             | 11,600/12,000           | 450-550                 | 10.9/10.9 | 8,500/11,000                     | 208/230          | 2.54                      | Yes            |
| REG-183M                             | 18,200/18,500           | 700-1000                | 10.7/10.7 | 13,000/16,000                    | 208/230          | 3.80                      | Yes            |
| REG-253M                             | 24,700/25,000           | 1400-1500               | 9.4/9.4   | 13,000/16,000                    | 208/230          | 5.71                      | Yes            |
| <b>THRU-THE-WALL SERIES</b>          |                         |                         |           |                                  |                  |                           |                |
| BG-81P*                              | 8,000                   | 300-350                 | 10.6/10.6 | N/A                              | 115              | 2.11                      | Yes            |
| BG-101P*                             | 10,000                  | 400-450                 | 10.6/10.6 | N/A                              | 115              | 2.32                      | Yes            |
| BG-103P*                             | 9,800/10,000            | 400-450                 | 10.6/10.6 | N/A                              | 208/230          | 2.32                      | Yes            |
| BG-121P*                             | 12,000                  | 450-550                 | 10.5/10.5 | N/A                              | 115              | 2.54                      | Yes            |
| BG-123P*                             | 11,700/12,000           | 450-550                 | 10.5/10.5 | N/A                              | 208/230          | 2.54                      | Yes            |
| BG-143M                              | 13,600/14,000           | 550-700                 | 9.3/9.3   | N/A                              | 208/230          | 2.96                      | Yes            |
| BGE-103M                             | 9,800/10,000            | 400-450                 | 9.6/9.6   | 8,600/10,600                     | 208/230          | 2.32                      | Yes            |
| BGE-123M                             | 11,700/12,000           | 450-550                 | 9.5/9.5   | 8,600/10,600                     | 208/230          | 2.54                      | Yes            |
| BGE-143M                             | 13,600/14,000           | 550-700                 | 9.3       | 8,600/10,600                     | 208/230          | 2.96                      | Yes            |
| <b>HEAT PUMPS</b>                    |                         |                         |           |                                  |                  |                           |                |
| RAH-123M                             | 11,200/11,600           | 450-550                 | 9.9       | 9,900/10,200**                   | 208/230          | 3.17                      | Yes            |
| RAH-183M                             | 17,000/17,300           | 700-1000                | 9.9       | 14,000/14,300**                  | 208/230          | 4.65                      | Yes            |
| <b>CASEMENT SERIES</b>               |                         |                         |           |                                  |                  |                           |                |
| CD-81M                               | 8,000                   | 300-350                 | 10.9/10.8 | N/A                              | 115              | 1.9                       | Yes            |
| CD-101M                              | 10,000                  | 400-450                 | 10.4/10.4 | N/A                              | 115              | 2.32                      | Yes            |
| <b>PORTABLE A/C</b>                  |                         |                         |           |                                  |                  |                           |                |
| PS-81B                               | 8,000                   | 300-350                 | 8.9       | N/A                              | 115              | 2.32                      | Yes            |
| PS-101B                              | 10,000                  | 400-450                 | 9.0       | N/A                              | 115              | 2.74                      | Yes            |
| PS-121B                              | 12,000                  | 450-550                 | 8.9       | N/A                              | 115              | 3.38                      | Yes            |
| PSH-141A                             | 14,000                  | 550-700                 | 8.9       | N/A                              | 115              | 2.96                      | Yes            |

\*Energy Star® rated

\*\*Heat pump capacity

| Model Number                         | Ventilation Control | Fan Only Speeds | Air Delivery Max. CFM | Fan Motor Speeds | Amps Cooling | Amps Heating | dB Level (hi/med/low) | Maximum Fuse Size Amps | Slide-Out Chassis | Window Mounting Kit (Standard) | Power Cord Plug | Approx. Max-Wall Thickness (in.) | Ship Weight (lbs.) | Dimensions H x W x D (with base and front in inches)  |
|--------------------------------------|---------------------|-----------------|-----------------------|------------------|--------------|--------------|-----------------------|------------------------|-------------------|--------------------------------|-----------------|----------------------------------|--------------------|---|
| <b>COOLING 5,000 to 10,000 BTUH</b>  |                     |                 |                       |                  |              |              |                       |                        |                   |                                |                 |                                  |                    |   |
| RG-51M                               | No                  | 2               | 136                   | 2                | 4.0          | N/A          | 55/51                 | 15                     | No                | Yes                            | A               | 3 <sup>9</sup> / <sub>16</sub>   | 45                 | 12 x 16 x 15 <sup>7</sup> / <sub>16</sub>   |
| RADS-51P*                            | No                  | 3               | 140                   | 3                | 3.8          | N/A          | 56/53/51              | 15                     | No                | Yes                            | A               | 3 <sup>5</sup> / <sub>16</sub>   | 47                 | 12 x 16 x 15 <sup>7</sup> / <sub>16</sub>   |
| RADS-61P*                            | No                  | 3               | 147                   | 3                | 4.5          | N/A          | 56/54/52              | 15                     | No                | Yes                            | A               | 5                                | 52                 | 13 <sup>7</sup> / <sub>16</sub> x 18 <sup>1</sup> / <sub>2</sub> x 15 <sup>3</sup> / <sub>4</sub>   |
| RADS-81P*                            | No                  | 3               | 224                   | 3                | 5.9          | N/A          | 60/59/56              | 15                     | No                | Yes                            | A               | 5                                | 58                 | 13 <sup>7</sup> / <sub>16</sub> x 18 <sup>1</sup> / <sub>2</sub> x 15 <sup>3</sup> / <sub>4</sub>   |
| RADS-101P*                           | Yes                 | 3               | 285                   | 3                | 7.5          | N/A          | 60/58/51              | 15                     | No                | Yes                            | A               | 7 <sup>5</sup> / <sub>16</sub>   | 70.6               | 14 <sup>5</sup> / <sub>8</sub> x 19 x 21 <sup>1</sup> / <sub>2</sub>                                |
| <b>COOLING 12,000 to 36,600 BTUH</b> |                     |                 |                       |                  |              |              |                       |                        |                   |                                |                 |                                  |                    |   |
| RADS-121P*                           | Yes                 | 3               | 300                   | 3                | 8.7          | N/A          | 61/57/54              | 15                     | No                | Yes                            | A               | 7 <sup>5</sup> / <sub>16</sub>   | 78.5               | 14 <sup>5</sup> / <sub>8</sub> x 19 x 21 <sup>1</sup> / <sub>2</sub>                                |
| RADS-123M                            | Yes                 | 3               | 288                   | 3                | 5.1/4.7      | N/A          | 60/58/55              | 15                     | No                | Yes                            | B               | 7 <sup>5</sup> / <sub>16</sub>   | 77                 | 14 <sup>5</sup> / <sub>8</sub> x 19 x 21 <sup>1</sup> / <sub>2</sub>                                |
| RADS-151P*                           | Yes                 | 3               | 353                   | 3                | 11.5         | N/A          | 56/54/53              | 15                     | Yes               | Yes                            | A               | 8                                | 118                | 17 <sup>15</sup> / <sub>16</sub> x 23 <sup>5</sup> / <sub>8</sub> x 25 <sup>7</sup> / <sub>16</sub> |
| RADS-183P*                           | Yes                 | 3               | 360                   | 3                | 7.5/7.0      | N/A          | 60/57/54              | 15                     | Yes               | Yes                            | B               | 8                                | 129                | 17 <sup>15</sup> / <sub>16</sub> x 23 <sup>5</sup> / <sub>8</sub> x 25 <sup>7</sup> / <sub>16</sub> |
| RADS-253P*                           | Yes                 | 3               | 523                   | 3                | 11.8/10.8    | N/A          | 63/62/62              | 20                     | Yes               | Yes                            | C               | 10                               | 151                | 18 <sup>5</sup> / <sub>8</sub> x 26 <sup>1</sup> / <sub>2</sub> x 26 <sup>1</sup> / <sub>2</sub>    |
| RAD-283M                             | Yes                 | 3               | 523                   | 3                | 15.0/13.8    | N/A          | 63/61/58              | 30                     | Yes               | Yes                            | D               | 10                               | 156                | 18 <sup>5</sup> / <sub>8</sub> x 26 <sup>1</sup> / <sub>2</sub> x 26 <sup>1</sup> / <sub>2</sub>    |
| <b>COOLING WITH ELECTRIC HEAT</b>    |                     |                 |                       |                  |              |              |                       |                        |                   |                                |                 |                                  |                    |   |
| REG-81M                              | No                  | 3               | 277                   | 3                | 6.3          | 11.6         | 58/55/52              | 15                     | Yes               | Yes                            | A               | 6 <sup>1</sup> / <sub>8</sub>    | 82                 | 16 <sup>1</sup> / <sub>8</sub> x 22 <sup>5</sup> / <sub>8</sub> x 23                                |
| REG-123M                             | No                  | 3               | 279                   | 3                | 5.2/5.0      | 16.0/14.5    | 61/58/55              | 20                     | Yes               | Yes                            | C               | 6 <sup>1</sup> / <sub>8</sub>    | 93                 | 16 <sup>1</sup> / <sub>8</sub> x 22 <sup>5</sup> / <sub>8</sub> x 23                                |
| REG-183M                             | Yes                 | 3               | 446                   | 3                | 8.3/7.7      | 22.0/20.0    | 60/57/54              | 30                     | Yes               | Yes                            | D               | 8                                | 131                | 17 <sup>15</sup> / <sub>16</sub> x 23 <sup>5</sup> / <sub>8</sub> x 25 <sup>7</sup> / <sub>16</sub> |
| REG-253M                             | Yes                 | 3               | 523                   | 3                | 12.4/11.3    | 22.5/20.0    | 63/61/58              | 30                     | Yes               | Yes                            | D               | 10                               | 147                | 18 <sup>5</sup> / <sub>8</sub> x 26 <sup>1</sup> / <sub>2</sub> x 26 <sup>1</sup> / <sub>2</sub>    |
| <b>THRU-THE-WALL SERIES</b>          |                     |                 |                       |                  |              |              |                       |                        |                   |                                |                 |                                  |                    |   |
| BG-81P*                              | No                  | 3               | 270                   | 3                | 7.0          | N/A          | 57/54/52              | 15                     | No                | Yes <sup>▲</sup>               | A               | 18                               | 76                 | 14 <sup>1</sup> / <sub>2</sub> x 24 <sup>1</sup> / <sub>4</sub> x 20 <sup>5</sup> / <sub>16</sub>   |
| BG-101P*                             | No                  | 3               | 269                   | 3                | 8.3          | N/A          | 57/55/53              | 15                     | No                | Yes <sup>▲</sup>               | A               | 18                               | 80                 | 14 <sup>1</sup> / <sub>2</sub> x 24 <sup>1</sup> / <sub>4</sub> x 20 <sup>5</sup> / <sub>16</sub>   |
| BG-103P*                             | No                  | 3               | 275                   | 3                | 4.8/4.5      | N/A          | 58/56/54              | 15                     | No                | Yes <sup>▲</sup>               | B               | 18                               | 80                 | 14 <sup>1</sup> / <sub>2</sub> x 24 <sup>1</sup> / <sub>4</sub> x 20 <sup>5</sup> / <sub>16</sub>   |
| BG-121P*                             | No                  | 3               | 286                   | 3                | 10.0         | N/A          | 61/59/57              | 15                     | No                | Yes <sup>▲</sup>               | A               | 18                               | 87                 | 14 <sup>1</sup> / <sub>2</sub> x 24 <sup>1</sup> / <sub>4</sub> x 20 <sup>5</sup> / <sub>16</sub>   |
| BG-123P*                             | No                  | 3               | 286                   | 3                | 5.6/5.2      | N/A          | 61/59/57              | 15                     | No                | Yes <sup>▲</sup>               | B               | 18                               | 89                 | 14 <sup>1</sup> / <sub>2</sub> x 24 <sup>1</sup> / <sub>4</sub> x 20 <sup>5</sup> / <sub>16</sub>   |
| BG-143M                              | No                  | 3               | 296                   | 3                | 7.5/6.9      | N/A          | 61/60/59              | 15                     | No                | Yes <sup>▲</sup>               | B               | 18                               | 89                 | 14 <sup>1</sup> / <sub>2</sub> x 24 <sup>1</sup> / <sub>4</sub> x 20 <sup>5</sup> / <sub>16</sub>   |
| BGE-103M                             | No                  | 3               | 269                   | 3                | 5.4/5.0      | 15.0/13.5    | 57/55/53              | 20                     | No                | Yes <sup>▲</sup>               | C               | 18                               | 85                 | 14 <sup>1</sup> / <sub>2</sub> x 24 <sup>1</sup> / <sub>4</sub> x 20 <sup>5</sup> / <sub>16</sub>   |
| BGE-123M                             | No                  | 3               | 286                   | 3                | 5.9/5.5      | 15.0/13.5    | 61/59/57              | 20                     | No                | Yes <sup>▲</sup>               | C               | 18                               | 89                 | 14 <sup>1</sup> / <sub>2</sub> x 24 <sup>1</sup> / <sub>4</sub> x 20 <sup>5</sup> / <sub>16</sub>   |
| BGE-143M                             | No                  | 3               | 296                   | 3                | 7.5/6.9      | 15.0/13.5    | 61/60/59              | 20                     | No                | Yes <sup>▲</sup>               | C               | 18                               | 89                 | 14 <sup>1</sup> / <sub>2</sub> x 24 <sup>1</sup> / <sub>4</sub> x 20 <sup>5</sup> / <sub>16</sub>   |
| <b>HEAT PUMPS</b>                    |                     |                 |                       |                  |              |              |                       |                        |                   |                                |                 |                                  |                    |   |
| RAH-123M                             | No                  | 3               | 265                   | 3                | 5.3/5.1      | 5.6/5.1      | 72/70/68              | 20                     | Yes               | Yes                            | C               | 6 <sup>1</sup> / <sub>8</sub>    | 110                | 16 <sup>1</sup> / <sub>8</sub> x 23 x 22 <sup>5</sup> / <sub>8</sub>                                |
| RAH-183M                             | Yes                 | 3               | 541                   | 3                | 7.8/7.3      | 8.8/8.3      | 72/70/68              | 20                     | Yes               | Yes                            | C               | 10                               | 159                | 18 <sup>5</sup> / <sub>8</sub> x 26 <sup>1</sup> / <sub>2</sub> x 26 <sup>1</sup> / <sub>2</sub>    |
| <b>CASEMENT SERIES</b>               |                     |                 |                       |                  |              |              |                       |                        |                   |                                |                 |                                  |                    |   |
| CD-81M                               | Yes                 | 3               | 264                   | 3                | 6.6          | N/A          | 54/51/48              | 15                     | No                | Yes                            | A               | 8 <sup>1</sup> / <sub>2</sub>    | 82                 | 20 <sup>15</sup> / <sub>16</sub> x 14 <sup>5</sup> / <sub>8</sub> x 23 <sup>1</sup> / <sub>2</sub>  |
| CD-101M                              | Yes                 | 3               | 323                   | 3                | 8.5          | N/A          | 61/58/56              | 15                     | No                | Yes                            | A               | 8 <sup>1</sup> / <sub>2</sub>    | 85                 | 20 <sup>15</sup> / <sub>16</sub> x 14 <sup>5</sup> / <sub>8</sub> x 23 <sup>1</sup> / <sub>2</sub>  |
| <b>PORTABLE A/C</b>                  |                     |                 |                       |                  |              |              |                       |                        |                   |                                |                 |                                  |                    |   |
| PS-81B                               | Yes                 | 2               | 209                   | 2                | 8.0          | N/A          | 56/52                 | 15                     | N/A               | Yes                            | A               | N/A                              | 59.5               | 27 <sup>11</sup> / <sub>16</sub> x 13 <sup>5</sup> / <sub>8</sub> x 14                              |
| PS-101B                              | Yes                 | 2               | 206                   | 2                | 9.8          | N/A          | 55/51                 | 15                     | N/A               | Yes                            | A               | N/A                              | 62                 | 27 <sup>11</sup> / <sub>16</sub> x 13 <sup>5</sup> / <sub>8</sub> x 14                              |
| PS-121B                              | Yes                 | 3               | 292                   | 3                | 11.8         | N/A          | 51/49/47              | 15                     | N/A               | Yes                            | A               | N/A                              | 78                 | 30 <sup>1</sup> / <sub>8</sub> x 18 <sup>5</sup> / <sub>16</sub> x 15 <sup>5</sup> / <sub>8</sub>   |
| PSH-141A                             | Yes                 | 3               | 297                   | 3                | 13.8         | 10.8         | 55/54/53              | 15                     | N/A               | Yes                            | A               | N/A                              | 83                 | 34 <sup>5</sup> / <sub>8</sub> x 14 <sup>5</sup> / <sub>16</sub> x 17 <sup>7</sup> / <sub>16</sub>  |

▲ Interior trim kit for BG, BGE Series: Models use wall sleeve