

BRASS PIPE

WEIGHT OF SEAMLESS BRASS AND COPPER PIPE					
Iron Pipe Sizes REGULAR PIPE					
Pipe Size in Inches	DIMENSIONS IN INCHES			POUNDS PER LINEAL FOOT	
	O.D.	I.D.	Wall Thickness	Red Brass	Copper
1/8	.405	.281	.062	.253	.259
1/4	.540	.376	.082	.447	.457
3/8	.675	.495	.090	.627	.641
1/2	.840	.626	.107	.934	.955
3/4	1.050	.822	.114	1.27	1.30
1	1.315	1.063	.126	1.78	1.82
1 1/4	1.660	1.368	.146	2.63	2.69
1 1/2	1.900	1.600	.150	3.13	3.20
2	2.375	2.063	.156	4.12	4.22
2 1/2	2.875	2.501	.187	5.99	6.12
3	3.500	3.062	.219	8.56	8.75
3 1/2	4.000	3.500	.250	11.2	11.4
4	4.500	4.000	.250	12.7	12.9
5	5.563	5.063	.250	15.8	16.2
6	6.625	6.125	.250	19.0	19.4

WEIGHT OF SEAMLESS BRASS AND COPPER PIPE					
EXTRA STRONG PIPE					
Pipe Size in Inches	DIMENSIONS IN INCHES			POUNDS PER LINEAL FOOT	
	O.D.	I.D.	Wall Thickness	Red Brass	Copper
1/8	.405	.205	.100	.363	.371
1/4	.540	.294	.123	.611	.625
3/8	.675	.421	.127	.829	.847
1/2	.840	.542	.149	1.23	1.25
3/4	1.050	.736	.157	1.67	1.71
1	1.315	.951	.182	2.46	2.51
1 1/4	1.660	1.272	.194	3.39	3.46
1 1/2	1.900	1.494	.203	4.10	4.19
2	2.375	1.933	.221	5.67	5.80
2 1/2	2.875	2.315	.280	8.66	8.85
3	3.500	2.892	.304	11.6	11.8

RED BRASS 85%				
Pipe with Threaded Ends Allowable Pressure				
POUNDS PER SQUARE INCH				
Standard Size (Inches)	@ 100°F	@ 200°F	@ 300°F	@ 400°F
1/8	370	370	320	140
1/4	870	870	760	330
3/8	890	890	780	340
1/2	900	900	790	340
3/4	810	810	710	310
1	630	630	560	240
1 1/4	690	690	610	260
1 1/2	630	630	560	240
2	540	540	480	210
2 1/2	450	450	390	170
3	510	510	450	190
3 1/2	570	570	500	220
4	510	510	440	190
5	410	410	360	160
6	340	340	300	130

RED BRASS 85%				
Pipe with Threaded Ends EXTRA STRONG (XS) Allowable Internal Pressure				
POUNDS PER SQUARE INCH				
Standard Size (Inches)	@ 100°F	@ 200°F	@ 300°F	@ 400°F
1/8	1960	1960	1710	740
1/4	2210	2210	1930	830
3/8	1840	1840	1610	690
1/2	1760	1760	1540	660
3/4	1510	1510	1320	570
1	1340	1340	1180	510
1 1/4	1160	1160	1020	440
1 1/2	1090	1090	960	410
2	1000	1000	870	380
2 1/2	970	970	850	370
3	910	910	790	340

EVERY PRECAUTION HAS BEEN TAKEN IN PREPARING THIS PRICE SHEET. HOWEVER, MERIT BRASS COMPANY CANNOT BE HELD RESPONSIBLE FOR TYPOGRAPHICAL ERRORS OR OMISSIONS. PLEASE NOTE, MERIT FURNISHES RED BRASS PIPE CONFORMING TO ASTM B43, DRAWN GENERAL PURPOSE TEMPER (H58); UNLESS OTHERWISE NOTED. LIGHT ANNEALED (061) TEMPER IS ALSO AVAILABLE UPON REQUEST.

VISIT US AT WWW.MERITBRASS.COM • WWW.MBWEBXPRESS.COM • WWW.MBLEADFREE.COM

CLEVELAND HEADQUARTERS:	DALLAS DISTRIBUTION CENTER:	RENO DISTRIBUTION CENTER:	BIRMINGHAM DISTRIBUTION CENTER:
Local Tel: 216-261-9800	Toll Free Tel: 877-259-2591	Local Tel: 775-353-3184	Local Tel: 205-945-5700
Toll Free Tel: 800-726-9800	Toll Free Fax: 877-259-2596	Toll Free Tel: 855-912-0408	Toll Free Tel: 855-912-0409
Toll Free: 855-MBFAXIT	E-Mail: mbsalesTX@meritbrass.com	Toll Free Fax: 877-376-0093	Toll Free Fax: 866-668-9168
E-Mail: mbsales@meritbrass.com	Address: 10614 King William Drive	E-Mail: mbsalesNV@meritbrass.com	E-Mail: mbsalesAL@meritbrass.com
Address: P.O. Box 43127, One Merit Drive Cleveland, OH 44143	Dallas, TX 75220	Address: 200 Vista Blvd., Suite #106 Sparks, NV 89434	Address: 280 Oxmoor Ct., Suite D Birmingham, AL 35209

Merit Brass Cleveland Headquarters Has An ISO 9001:2008 Registered Quality Management System



DIRECTING THE FLOW OF *Quality*

©2013 Merit Brass All Rights Reserved.