


# DIMENSIONAL SPECIFICATIONS

## LEAD-FREE IMPORT BRASS FITTINGS\* 125 LB.

### REDUCING COUPLING CONTINUED

Part #	Size (IN.)	Approx. Net WT. (LB.)	A	B	C
XNL112-2412	1-1/2 X 3/4	0.92	1.42	2.38	1.80
XNL112-2416	1-1/2 X 1	0.90	1.72	2.38	1.80
XNL112-2420	1-1/2 X 1-1/4	0.99	2.10	2.38	1.80
XNL112-3208	2 X 1/2	1.28	1.17	2.92	2.03
XNL112-3212	2 X 3/4	1.25	1.42	2.92	2.03
XNL112-3216	2 X 1	1.39	1.72	2.92	2.03
XNL112-3220	2 X 1-1/4	1.05	2.10	2.92	2.03
XNL112-3224	2 X 1-1/2	1.74	2.38	2.92	2.03
XNL112-4020	2-1/2 X 1-1/4	2.08	2.10	3.49	3.25
XNL112-4024	2-1/2 X 1-1/2	1.94	2.38	3.49	3.25
XNL112-4032	2-1/2 X 2	2.11	2.92	3.49	3.25
XNL112-4824	3 X 1-1/2	2.35	2.92	4.20	3.69
XNL112-4832	3 X 2	2.40	2.92	4.20	3.69
XNL112-4840	3 X 2-1/2	2.40	3.49	4.20	3.69
XNL112-6448	4 X 3	4.58	4.20	5.31	4.38



\*Conforms with lead content requirements for lead-free plumbing as defined by the U.S. Safe Drinking Water Act. Certified <0.25 weighted average % lead.



# MERIT BRASS

DIRECTING THE FLOW OF *Quality*