

**NIBCO**

1516 Middlebury Street

Elkhart, IN 46516-4740

Phone: 574.295.3000 • **Fax:** 800.234.0557**E-Mail:** info@nibco.com • **Web site:** www.nibco.com**Material Number NLG100E, LD-2000 Butterfly Valve - Ductile Iron, Lug Type, 200 PSI, Handle**

The NIBCO® ductile iron lug butterfly valve provides ease of operation with quarter-turn (90 degrees) open to close. With the internal stem/disc geometric drive design, there is no need for pins or bolts that may create leak paths or turbulence in the waterway. An extended neck allows for insulation up to 2 inches. The unique molded-in EPDM seat liner with aluminum bronze disc is recommended for most water applications. Please refer to NIBCO technical data sheets, chemical resistance guides and

+ [more](#)**Specifications**

UPC Code	039923717764
Type	Butterfly Valve
Valve Size	2 1/2 in
Material	DI Ductile Iron
Description	LD20003 21/2 LUG BFV L/LK HNDL DUCT IRON
Turns / Operation	Quarter-Turn
Seat / Seal Material	EPDM Rubber
Connection Type	L - Lug
Operation Type	Lever-Lock Handle
Disc Material	Aluminum Bronze
Weight	11.395 lb