

## HCC Holdings, Inc.

4700 West 160th  
Cleveland, Ohio 44135

Phone: 800-321-9532  
Website: www.Oatey.com



### CUTTING OIL Oils and Lubricants

Date: August 2017

Application specific lubricants for both manual and machine metal working operations. Used for sawing, drilling, turning or thread cutting with all types of metals. These are superior quality cutting oils formulated to produce consistent results under all weather conditions. Hercules Cutting Oils contain activated sulfur to provide anti-weld properties, reduce friction and prevent excessive heat generation, thus minimizing material expansion resulting in ill-fitting joints. The high film strength of Hercules Cutting Oils maintains a continuous contact of the lubricant with the work assuring quick, accurate and high quality cuts with minimal tool wear. Lubricants contain no nitrosamine forming compounds or chlorinated oils.

#### Clear Cutting Oil

A blend of high quality mineral oils with sulfur base. Used for cutting clean, unbroken threads during manual or low rpm threading machine operations on small sizes of steel and brass pipe. Also applicable for hacksawing and light drilling. Will not stain copper or brass materials.

#### Dark Cutting Oil

Extra heavy blend of high quality mineral oils with sulfur-lard base. Compounded to keep tooling and work cool when used on high speed threading machines. Enables operators to cut clean, sharp threads on steel or brass pipe. Ideal for thread cutting, tapping, broaching, drilling or any application where high speeds and quality finishes are required. A superior quality product that significantly extends tool life and reduces labor time.



### APPROVALS & LISTINGS

USDA Listed

### SPECIFIC USES

Use **Clear Cutting Oil** for the cutting of clean, unbroken threads during manual or low rpm threading machine operations. Also for hack sawing or light drilling. Use **Dark Cutting Oil** for high-speed tapping/threading, broaching, turning or drilling applications.

## SPECIFIC APPLICATIONS\*

**Hercules Cutting Oils** are designed to improve quality and throughput of work, reduce friction, be an effective coolant and significantly increase tool life.

\*For special applications which may not be covered on this or other Oatey literature, please contact Oatey Technical Services Department by phone 1-800-321-9532, or fax 1-800-321-9535, or visit our technical database web-site at [www.Oatey.com](http://www.Oatey.com).

## DIRECTIONS FOR USE

1. Wear safety glasses with side shields to protect eyes from metal shavings.
2. Be sure to start the flow of oil before tooling is in contact with the work.
3. Oil flow should hit the point of friction for best results.
4. Always use properly ground chasers and dies with this quality cooling lubricant to obtain sharp, clean threads without burrs.

## PHYSICAL PROPERTIES

	<b>Clear</b>	<b>Dark</b>
Specific Gravity:	at 25°C .906	at 25°C .906
Solubility in water:	Insoluble	Insoluble
Boiling Point:	465-900°F	465-900°F
Appearance/color:	Light amber liquid	Dark brownish amber liquid
Odor:	Petroleum odor	Petroleum odor
Viscosity:	30-35 centipoises	45-50 centipoises

## SIZE & PACKING

STOCK NUMBER	SIZE	PACKING	WEIGHT/CASE
<b>Clear</b>			
40110	1 pt.	24	28.6 lbs.
40115	1 qt.	12	28.0 lbs.
40120	1 gal.	6	49.4 lbs.
40125	5 gal.	1	40.2 lbs.
<b>Dark</b>			
40210	1 pt.	24	28.6 lbs.
40215	1 qt.	12	28.0 lbs.
40220	1 gal.	6	49.4 lbs.
40225	5 gal.	1	40.2 lbs.
40240	55 gal.	1	452.0 lbs.

## WARNINGS OR CAUTIONS

---

- Read all cautions and directions carefully before using this product.
- **KEEP OUT OF REACH OF CHILDREN.**
- Avoid contact with eyes or skin. Prolonged or repeated skin contact may cause irritation.
- Avoid breathing vapor, mist or fumes. Use with adequate ventilation.
- Wash thoroughly after handling.

## MATERIAL SAFETY INFORMATION

---

FOR MORE INFORMATION ON THIS PRODUCT, REQUEST SAFETY DATA SHEET (SDS)-Clear #7335E, Dark #7336E

For Delivery By Fax	Call 1-800-321-9535
Internet	See SDS section of <a href="http://www.Oatey.com">www.Oatey.com</a>

HMIS® ratings Health: 1  
Flammability: 1  
Physical hazard: 0