

# Presstite & Virginia Cork Insulation Tape

Presstite is the premium product of its type. It may be used for either hot or cold temperature applications within its continuous duty service temperature range of -29°C to 93°C.

Presstite is designed to be use on pipes or tubes, in commercial or residential buildings, A/C units, refrigerated units and other similar types of applications.

Presstite will stop dripping caused by pipe condensation, will adhere to metal and will not crack or dry out.

Presstite is self an adhering tape.



## What's in it for you?

- High quality formulation to better stick to pipes and fitting
- Prevents condensation drip from forming on pipes and tubing
- Easy to cut in piece for molding around hard to wrap fitting

Product Name	Part Number	Quantity	Size - Type
PT1	475291	1	(0.3 cm x 7.5cm x 9m)
VCT2	475294	12	Bulk (0.3 cm x 7.5cm x 9m)

### Uses:

To use with any application in which piping or tubing need to be insulated to prevent heat transfer or condensate formation and drip.

### Applications Methods:

• Adhering surfaces should be clean and dry • Wrap the tape in a spiral around the tubing, butting the edges together with your fingers as you go.

### Note:

Do not stretch. Do not overlap edges. • Subsequent wrappings can be made as required. Reverse the direction of wrap with each subsequent wrapping.