

DW-600 DELUXE DRINKING WATER



- Point-of-Use filter system
- Features a single, compact quick-change cartridge
- Includes all installation hardware
- Works with copper, plastic or flexible tubing
- 500 gallon capacity



Tested and Certified by NSF International.

MODEL NUMBER	PART NUMBER	REDUCES	INLET/OUTLET	OVERALL DIMENSIONS	RATING (NOMINAL)	OPERATING PRESSURE	OPERATING TEMPERATURE
DW-600	158573	Lead, Cysts*, Lindane, Atrazine, Chlorine Taste & Odor, Sediment	1/4"	3" x 3" x 13-1/2"	0.5 micron	30 - 125 psi	40 - 100° F
Replacement Cartridge Kit							
600R	155785-51	Lead, Cysts*, Lindane, Atrazine, Chlorine Taste & Odor, Sediment	—	2-1/2" x 2-1/2" x 12-1/2"	0.5 micron	30 - 125 psi	40 - 100° F

*NSF/ANSI Standard 53 certified to reduce cysts such as *Cryptosporidium* and *Giardia* by mechanical means.

WLCS-1000 CHEMICAL/LEAD



- Point-of-Use filter system
- Effectively reduces a wide range of chemicals and other contaminants
- System includes an electronic monitor for filter replacement
- 1,000 gallon capacity
- No storage tank or recovery time is required
- Provides great-tasting water on demand
- Completely assembled and ready to install conveniently under the sink



Tested and Certified by NSF International.

MODEL NUMBER	PART NUMBER	REDUCES	INLET/OUTLET	OVERALL DIMENSIONS	RATING (NOMINAL)	OPERATING PRESSURE	OPERATING TEMPERATURE
WLCS-1000	152077	99% of Dissolved Lead, > 99.5% of Giardia and Cryptosporidium Cysts*, Mercury, Asbestos, Bad Taste and Odor, Chlorine Taste & Odor, Sediment	1/4"	11" x 6-1/2" x 15"	0.5 micron	30 - 125 psi	40 - 100° F
Replacement Cartridge Kit							
W-250	155584-51	99% of Dissolved Lead, 99.5% of Giardia and Cryptosporidium Cysts*, Mercury, Asbestos, Chlorine Taste & Odor, Sediment	—	—	0.5 micron	30 - 125 psi	40 - 100° F

*NSF/ANSI Standard 53 certified to reduce cysts such as *Cryptosporidium* and *Giardia* by mechanical means.

WIC-600 QUICK CHANGE

- Point-of-Use filter system
- Icemaker/water dispenser water system
- Change filter with easy 1/4 turn, no spilling of water
- Includes all installation hardware
- Works with copper, plastic or flexible tubing
- Reduces lead, Cysts*, Lindane, Atrazine, chlorine taste & odor and sediment



Tested and Certified by NSF International.

MODEL NUMBER	PART NUMBER	REDUCES	INLET/OUTLET	OVERALL DIMENSIONS	RATING	OPERATING PRESSURE	OPERATING TEMPERATURE
WIC-600	158582	Lead, Cysts*, Lindane, Atrazine, Chlorine Taste & Odor, Sediment	1/4"	3" x 3" x 13-1/2"	0.5 micron	30 - 125 psi	40 - 100° F
Replacement Cartridge							
600R	155785-51	Lead, Cysts*, Lindane, Atrazine, Chlorine Taste & Odor, Sediment	—	2-1/2" x 2-1/2" x 12-1/2"	0.5 micron	30 - 125 psi	40 - 100° F

*NSF/ANSI Standard 53 certified to reduce cysts such as *Cryptosporidium* and *Giardia* by mechanical means.



QUICK CONNECT IN-LINE

- Point-of-Use filters
- Refrigerator icemakers and water dispensers, coffee makers and other in-line applications
- Granular-activated carbon reduces bad taste and odor and chlorine taste & odor from water
- WICSA includes phosphate crystals to prevent lime/scale build-up. Not Performance Tested or Certified by NSF.
- Quick-connect fittings attach easily to 1/4" -copper or plastic cold water lines
- Polypropylene pre and postfilters



Tested and Certified by NSF International. for material requirements only!

MODEL NUMBER	PART NUMBER	MEDIUM	FLOW RATE (GPM)	OPERATING PRESSURE	TEMPERATURE RANGE	DIAMETER	LENGTH
WIC-6A	155702-51	Granular Activated Coconut Carbon	0.5	20 - 125 psi	40 - 100° F	2"	6"
WICA	155070-51	Granular Activated Coconut Carbon	8.5	20 - 125 psi	40 - 100° F	2"	10"
WICSA	155083-51	Granular Activated Coconut Carbon & Phosphate Crystals	0.5	20 - 125 psi	40 - 100° F	2"	10"
WIC	255521-51	Granular Activated Coconut Carbon	1.0	20 - 125 psi	40 - 100° F	2"	10"

