PHILIPS Lighting



MasterColor CDM ED17 Protected

MHC150/U/MP/4K ALTO 12PK

Direct retrofit with immediate energy savings!Range of protected, high-efficiency long life ceramic metal halide lamps with a stable color over lifetime and a crisp, sparkling light to be used in open fixtures.

Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Operating Position	UNIVERSAL [Any or Universal (U)]
Main Application	General Lighting (G)
Life To 50% Failures (Min)	20000 h
ANSI Code HID	C142/O
Features	ALTO® + FadeBlock™
Footnotes HID 1	Exclusive to Philips Lighting Company.
Light Technical	
Color Code	940 [CCT of 4000K]
Luminous Flux (Rated) (Min)	11000 lm
Luminous Flux (Rated) (Nom)	12000 lm
Color Designation	Deluxe Cool White
Lumen Maintenance - 40% Life	75 %
Lumen Maintenance - 10% Life	87 %
Design Mean Lumens	9000 lm
Chromaticity Coordinate X (Max)	0.387
Chromaticity Coordinate X (Min)	0.369
Chromaticity Coordinate X (Nom)	0.378

Chromaticity Coordinate Y (Max)	0.372
Chromaticity Coordinate Y (Min)	0.360
Chromaticity Coordinate Y (Nom)	0.366
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Min)	73 lm/W
Luminous Efficacy (rated) (Nom)	80 lm/W
Color Rendering Index (Min)	87
Color Rendering Index (Nom)	90
Operating and Electrical	
Lamp Current (Nom)	1.8 A
Ignition Supply Voltage (Min)	235 V
Re-Ignition Time (Min) (Max)	12 min
Ignition Time (Max)	10 s
Voltage (Max)	105 V
Voltage (Min)	85 V
Voltage (Nom)	95 V
Mechanical and Housing	
Bulb Finish	Clear

MasterColor CDM ED17 Protected

Cap-Base Information	Brass Cap
Bulb Material	Hard Glass
Approval and Application	
Picogram Per Lumen Hour	63.3 pg/lm.h
Mercury (Hg) Content (Max)	11.4 mg
UV	
Pet (Niosh) (Nom)	304 h.klx
Damage Factor D/fc (Nom)	0.281
Luminaire Design Requirements	
Bulb Temperature (Max)	400 °C

Cap-Base Temperature (Max)	190 °C
Product Data	
Order product name	MHC150/U/MP/4K ALTO 12PK
EAN/UPC - Product	046677377243
Order code	928601171701
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928601171701
Net Weight (Piece)	0.070 kg

Warnings and Safety

• R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)

Dimensional drawing

MHC150/U/MP/4K ALTO 12PK 2.125 in 5.438 in	D/U/MP/4K ALTO 12PK 2.125 in 5.438 in

MHC P 150W/940 E26 ED17P U ALTO+FB



© 2017 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com 2017, May 26 - data subject to change