

HVAC DUCT SEALANTS

CADS

FEATURES

- LEED EQ Credit 4.1
- Use to seal all types of HVAC systems
- For indoor and outdoor use
- Fiber reinforced for additional strength
- Excellent mold and mildew resistance

CADS is fiber reinforced water based duct sealant used to pressure seal all types of HVAC duct systems, including metal, fiberglass ductboard and flexduct.



CHOOSE YOUR PRODUCT

PRODUCT CODE	COLOR	SIZE	TEXTURE	PACKAGING	PALLET WEIGHT
CADS-1	<input checked="" type="radio"/> <input type="radio"/>	1gl Pail	Fibrous	4 - Pails Per Case / 45 Cases Per Pallet / 180 Gallons Per Pallet	2,225 lbs
CADS-2	<input checked="" type="radio"/> <input type="radio"/>	2gl Pail	Fibrous	80 Pails Per Pallet / 160 Gallons Per Pallet	1,960 lbs
CADS-5	<input checked="" type="radio"/>	5gl Pail	Fibrous	36 Pails Per Pallet / 180 Gallons Per Pallet	2,160 lbs

Gray

White



WATER BASED



SCAN HERE TO VIEW
MATERIAL SAFETY
AND TECHNICAL
INFORMATION FOR
CADS