



## EFLT Extra Flexible Liquid-Tight Conduit

Part Number	Internal Diameter		External Diameter		Bending Radius	Weight lbs per 100 ft.
	Min (inch)	Max (inch)	Min (inch)	Max (inch)		
EFLT-3/8	0.484	0.504	0.690	0.710	1.50	19.5
EFLT-1/2	0.622	0.642	0.820	0.840	2.00	24.5
EFLT-3/4	0.820	0.840	1.030	1.050	2.75	30
EFLT-1	1.041	1.066	1.290	1.315	5.00	60.5
EFLT-1-1/4	1.380	1.410	1.630	1.660	6.00	77.5
EFLT-1-1/2	1.575	1.600	1.865	1.900	7.00	92
EFLT-2	2.020	2.045	2.340	2.375	9.00	140
EFLT-2-1/2	2.480	2.505	2.840	2.875	11.00	170
EFLT-3	3.070	3.100	3.460	3.500	15.50	312
EFLT-3-1/2	3.500	3.540	3.960	4.000	18.00	372
EFLT-4	4.000	4.460	4.460	4.500	22.00	424

All values are nominal and subject to correction.

**Application:** EFLT gives lasting wiring protection on machine tools, portable tools, presses, welders, pumps, blowers, grinders, conveyors, heating equipment, and automated lines for forging, plating, molding, blasting, rolling, die casting, processing, extruding, etc.

**Construction:** Durable, abrasion resistant PVC jacket will not wrinkle or shrink from cut ends. The galvanized mechanical steel core provides complete protection against liquid and moisture vapor. EFLT resists sunlight, heat, oil, and chemical degradation. The smooth flexible interior provides extra easy wire pull through.

**Standards:** Resists sunlight, heat, oil and chemical degradation  
Generally applicable temperature range: -20° C to +50° C (-5° F to +122° F)

**1-800-945-5542**